

## Index

- A**
- ABAQUS computer program**, 1111, 1112, 1945, 2001
- Acceptable risk, defined**, 2821
- Acetone (CH<sub>3</sub>COCH<sub>3</sub>), heat of combustion**, 143
- Acetylene**. *See* Ethyne (C<sub>2</sub>H<sub>2</sub>)
- Acid rain**, 688
- Action**, 15, 152, 158, 167, 181, 230–233, 273–274, 325, 329–330, 335, 344, 346, 450, 676, 681, 693, 1040, 1057, 1137, 1245, 1247, 1307, 1315, 1366, 1469, 1485, 1589, 1591, 1593, 1604, 1635, 1772, 1816, 1847, 1849–1852, 1864, 1865, 1872–1873, 1879, 1883, 1884, 1891, 1892, 1899, 1900, 1906, 1917, 1943, 1966–1968, 2013, 2021, 2023, 2039, 2040, 2071, 2076–2084, 2088–2095, 2097, 2103–2108, 2263, 2299, 2301, 2347, 2435, 2436, 2448, 2461, 2462, 2781, 2821, 2877, 2893, 2920–2924, 2926–2928, 2952, 2964, 2965, 3048, 3056, 3088, 3108, 3120, 3125, 3133, 3173, 3187–3190, 3194, 3198, 3321, 3331, 3352, 3384, 3391
- Active error**, 2921
- Adams-Bashforth method, solving initial value problems**, 1096
- Adiabatic flame temperature**  
calculation, 147–149  
and dissociation, 148  
lower flammability limits (LFL), 536–538, 547  
premixed flames, 388, 389
- ADINA computer program**, 1111
- Aerosol(s)**  
defined, 1303  
in smoke, 1343
- AFFF**. *See* Aqueous film-forming foam (AFFF)
- Aircraft hangars**  
low-level application of AFFF, 1683–1685  
new hangar design concepts, 1687  
overhead sprinkler protection, 1681  
video image flame detection, 1689
- Aircraft rescue and fire-fighting (ARFF) vehicles**, 1673, 1677, 1679
- Airport Services Guide (ICAO)**, 1663–1665, 1667, 1669, 1673, 1674
- Air, thermophysical properties of**, 95
- ALARM 1.0 fire risk indexing model**, 3178
- ALARM 2.0 fire risk indexing model**, 3178
- Alarms and alarm systems**  
fire alarm audibility and intelligibility, 1368  
scenarios, 1362, 1367, 1368  
sound pressure level, 1360, 1362, 1363, 1367, 1368, 2031  
fire alarm visibility, 1370–1374  
hearing-impaired persons, 1372, 1373  
voice alarm system, 1361
- ALARP (as low as reasonably practical) risk assessment method**  
buildings, 2952  
mass transportation, 3383
- Aliphatic hydrocarbons**, 1211, 2277, 2278
- Alkanes**, 198, 213, 337, 382, 530, 536, 542, 559, 913, 1168–1170, 1189, 1211, 1212, 2739, 2755, 3460, 3472  
combustion of, 3460
- Alkenes**, 170, 182, 198, 199, 213, 214, 559, 913, 1211, 1212, 3460, 3461, 3472
- Alkynes**, 913, 1211, 1212, 3461, 3473
- ALOFT numerical model**, 1059, 1060
- Alumina trihydrate, arc tracking reduction with**, 673
- Aluminum**  
combustion of, 662  
electrical wiring overheating, 678, 680
- American Nuclear Society (ANS)**, 3334–3336, 3338, 3339, 3354
- American Society for Testing and Materials (ASTM)**. *See* ASTM entries
- Ammonia (NH<sub>3</sub>), heat of formation**, 145
- Amorphous material**, 171, 177, 178, 278
- AnalyticaT decision analysis model**, 3025, 3026
- ANSI/AISC, Specification for Structural Steel Buildings**, 1889–1890
- ANSYS computer program**, 1055–1057, 1111, 2687
- Apparent stresses**. *See* Reynolds stresses
- Aqueous film-forming foam (AFFF)**  
and aircraft hangar protection, 1680–1681  
application rates, 1667–1673  
aspiration, 1665, 1666, 1675, 1688  
hybrids, 1647  
portable fire extinguishers, 1709  
protection of flammable/combustible liquid storage, 1691, 1695  
protein foams compared, 1647, 1665, 1668, 1700  
spill fire data, 1657, 1659, 1687, 1691, 1694, 1709  
spreading coefficient, 1657–1659

- Arc fault circuit interruption (AFCI) devices**, 672
- Archimedes' principle**, 77
- Architectural Acoustics (Ginn)**, 1360
- Arcs, electrical**
- arc extinguishment, 669
  - arc flash, 668–669
  - arc tracking
    - and creepage, 673
    - dry/wet, 671
    - scintillations, 372
  - break-arcs, 668
  - defined, 666–667
  - make-arcs, 668
  - means of creating
    - arcing across carbonized path, 668, 671–673
    - contact arcs, 668
    - glow-to-arc transition
    - glow-to-arc transition: ionized gases between electrodes, 667, 668
    - glow-to-arc transition: raising voltage across electrodes, 667
  - temperature, 667, 696
- Area sample**, 2871
- Areas of refuge**, 1266, 1748, 2023, 2097
- Arenes**, 913, 1211, 3461, 3473
- Aromatic hydrocarbons**, 198, 220, 326, 1211, 2210, 2221
- Arrhenius expression, decomposition reactions**, 1041
- Arundel Park Hall fire (1956)**, 2099
- ASCE/SEI, Minimum Design Loads for Buildings and Other Structures**, 1889
- ASET**. *See* Available safe egress time (ASET)
- ASET-B zone fire model**, 3039–3040
- ASET zone fire model**, 1027
- ASME flow nozzle**, 1402, 1403
- ASME orifice meters**, 1402–1403
- ASTM D1331, Standard Test Methods for Surface and Interfacial Tension of Solutions of Surface-Active Agents**, 1657
- ASTM E2058 fire propagation apparatus**, 926, 1148, 1167, 1170, 1189–1191, 2242, 3471
- ASTM E691, Practice for Conducting an Interlaboratory Study to Determine the Precision of a Test Method**, 3093
- ASTM E1546, Standard Guide for Development of Fire-Hazard-Assessment Standards**, 3212
- ASTM E1355, Standard Guide for Evaluating the Predictive Capability of Deterministic Fire Models**, 2039, 2919
- ASTM E1776, Standard Guide for the Development of Fire-Risk-Assessment Standards**, 3212
- ASTM E2067, Standard Practice for Full-Scale Oxygen Consumption Calorimetry Fire Tests**, 937
- ASTM E698-01, Standard Test Method for Arrhenius Constants for Thermally Unstable Materials**, 630
- ASTM E1529, Standard Test Method for Determining Effects of Large Hydrocarbon Pool Fires on Structural Members and Assemblies**, 1867
- ASTM E1354, Standard Test Method for Heat and Visible Smoke Release Rates for Materials and Products Using an Oxygen Consumption Calorimeter**, 925
- ASTM E1515, Standard Test Method for Minimum Explosible Concentration of Combustible Dusts**, 2791
- ASTM E2257, Standard Test Method for Room Fire Test of Wall and Ceiling Materials and Assemblies**, 935
- ASTM E84, Standard Test Method for Surface Burning Characteristics of Building Materials**, 791–792
- ASTM E119, Standard Test Methods for Fire Tests of Building Construction and Materials**, 1866, 1867
- time-temperature curves, 789, 1102, 1866, 1867, 1911, 1957
- ASTM, Standard Guide for Evaluating Predictive Capability of Computer Fire Models**, 3010
- Atria**. *See* Large-volume spaces, smoke management in
- Authority having jurisdiction**
- acceptable risk and, 2821
  - aviation fire protection, 1673
  - building fire risk assessment, 2976
- Autoignition**
- ASTM E698-01 and, 630
  - criticality concept
  - body size, 625
- Autoignition (cont.)**
- critical ambient temperature (CAT), 410, 411, 557, 604, 610, 629, 630
  - critical stacking temperature (CST), 605, 609, 626
  - examples, 572, 625, 649
  - Frank-Kamenetskii theory (*see* Frank-Kamenetskii theory, autoignition)
  - hot stacking problem, 609
  - iodine number, 576
  - liquids in porous materials, 575–578
  - and parallel reactions, 620–622
  - and presence of water, 620
  - reference texts, 2694
  - self-accelerating decomposition temperature (SADT), 629
  - Semenov theory (*see* Semenov theory, autoignition)
  - thermal runaway, 583, 605
  - time to ignition (TTI)
    - other chemically kinetic difficulties, 624
    - theoretical treatment, 623–624
- Autoignition temperature (AIT)**, 373, 531–537, 539, 554, 560, 561, 573, 574, 576, 578, 579, 607, 625, 648, 1569, 2225, 2226, 2693, 2779, 3450, 3451
- Automobiles**. *See* Motor vehicles
- Availability**
- equations for calculating, 2900
  - instantaneous/average, 2900
  - Markov modeling
    - characteristics, 2901–2902
    - developing, 2902–2903
    - solving continuous time model, 2907–2909
    - solving discrete time model, 2904–2907
    - transition matrix, 2903–2904
- Availability analysis**, 2876, 2877, 2900, 2928, 3202
- Available safe egress time (ASET)**, 1066, 1067, 1099, 2115, 3133
- impact of tenability on, 2145–2148
- Available time/time available**, 368, 1211, 1252, 1588, 2100, 2120, 2146, 2213, 2214, 2220, 2230, 2262, 2299, 2320, 2328, 2337, 2402, 2435, 2771, 2921, 2922, 2924, 2926, 2964, 2965, 2994, 3004, 3189, 3231, 3232, 3234–3237, 3359, 3360, 3373, 3389

**Aviation fire protection**

- agent quantities/standards, 1673–1679
- foam concentration, 1675–1679
- loam expansion and drainage, 1674–1675
- underlying principle, 1673

**Avogadro's hypothesis**, 140**B****Bagasse, spontaneous ignition**, 605, 628**Balcony spill plume**, 992, 1092, 1834–1839**Barriers**

- fire, analysis of, 3350
- smoke, 1750, 1786, 1813, 1817, 2022, 2413, 3167, 3170

**Bayes's law**, 2830, 2855**Beams**

- concrete, 1957, 1960
- critical stress in steel, 1941–1943
- critical temperature determination in steel, 1938–1939
- fire resistance in steel, 1931, 1985, 1994, 1996, 2001
- heat transfer to I-beams, 765, 766, 768, 769
- statically indeterminate, 270
- steel spandrel, 1929–1930

**Bedding fires**

- cigarette smoldering and, 2396
- heat release rates, 599, 2400

**Behavioral response to fire/smoke**

- See also* Occupants
- altruistic behavior, 2073
- awareness of cues, 2106, 2108
- ambiguous cues, 2462
- British/U S. populations compared, 2104
- cognitive decision processes, 2077, 2928
- convergence clusters, 2097
- emotional instability, 2198
- emotional state, 2197
- fire-fighting behavior, 2072
- gender, response by, 2103–2105
- high-rise office buildings, 2087
- hotel fires, 2085–2087
- identified characteristics, 2084
- nonadaptive behavior, 2073
- panic behavior, 2072–2073
- anxiety/fear distinguished, 2073
- perception of incident stress model, 2916
- re-entry behavior, 2084, 2085

**Bending, structural, moment**, 1883**Bernoulli beam finite element**, 1904**Bernoulli distribution**, 2846–2847**Bernoulli equation**, 21–22, 67, 84, 1383, 1384, 1405**Beta distribution**, 2850, 2854**Beverly Hills Supper Club fire (1977)**, 675, 2072, 2077, 2096, 2406, 3143**Binomial distribution**, 2847–2849, 2863, 2867, 2930**Biot number**, 26, 31, 33, 34, 606, 618, 622–623, 640**Blackbody radiation**, 105, 2616**Boiling liquid expanding vapor explosion (BLEVE)**, 558, 2646, 2664, 2745, 2758, 2792–2814

defined, 2792

**Boltzmann constant**. *See* Stefan-Boltzmann constant**Bookcases, heat release rates**, 816, 2397**Bouguer's law**, 1081**Boundary layers, convection heat transfer**

- boundary layer approximation, 65, 66, 68, 70, 83
- laminar flow over flat surface, 67–71

**Boundary layers, fluid flow**

- thickness, 17, 18, 65, 69, 73, 76–79, 90

**Bourbonnais (III.) grade crossing accident (1999)**, 3373**Bourdon gauge**, 1381–1382**Boussinesq approximation**, 64, 78, 98**Boxes, heat release rates**, 816, 837, 842–844, 846**Bradford stadium fire (1985)**, 706, 714, 2406**BRANZFIRE two-zone fire model**, 1028, 2968**Breathing effect, compartment fires**, 985**Brick**

- compressive strength, 305
- density, 305
- dilatometric/thermogravimetric curves, 305
- modulus of elasticity, 305
- specific heat, 306
- thermal conductivity, 288, 306

**British Standards Institute (BSI)**. *See* *BS entry***Browns Ferry nuclear plant fire (1975)**, 2923, 3328, 3331**BSI (British Standards Institute)**. *See* *BS entry***BS 7974, "Part 7-Probabilistic Risk Assessment"**, *Code on the Application of Fire Safety Engineering Principles to the Design of Buildings (BSI)*, 2977–2979**Building aerodynamics****Building assemblies and frames, fire resistance**

- fire protection materials/systems
  - concrete/masonry, 1877
  - flame shielding, 1917
  - gypsum, 314, 315, 1817
  - intumescent/mastic coatings, 1817
  - spray-applied materials, 1915–1916
  - water-cooled columns, 919
- floor systems, 1885
- frames, 1884, 1890–1895
- heat transfer/temperature profiles
  - composite steel-concrete members, 1950
  - concrete members, 1949–1977
  - steel members, 289, 1112, 1909–1945
  - temperature variation along members, 1852
  - thermally protected steel members, 1917
  - timber members, 1979–2005
  - unprotected steel members, 1105, 1118
- high-temperature thermal degradation
  - concrete/masonry, 301, 311, 1877
  - steel, 1877
  - thermal strains, 1876
  - timber, 290
- individual members
  - bending along the span, 1883
  - bending strength in concrete sections, 1885
  - bending strength in steel-concrete sections, 1885
  - bending strength in steel sections, 1885
  - bending strength in timber sections, 1885
  - with concrete in compression, 1884
  - with concrete in tension, 1884
  - elements in compression, 1884
  - elements in tension, 1884
  - section bending strength, 1884
  - steel in compression, 1884
  - steel in tension, 1884
  - timber in compression, 1884
  - timber in tension, 1884
- input/modeling uncertainties
  - Bernoulli hypothesis, 1904–1905
  - boundary conditions, 1902
  - connections, 1905
  - fixed geometry, 1898–1899
  - lack of convergence, 1903–1904
  - limitations of tests, 1905–1906
  - localized fire effects, 1900–1901

**Building assemblies and frames, fire resistance (cont.)**

- mechanical calculations, 1901–1905
- perfect contact, 1899–1900
- spalling, 1902–1903
- thermal calculations, 1897–1901
- thermal properties, 1897–1898
- very large structures, 1901–1902
- limit states design
  - collapse prevention, 1874
  - fire exposures, 1866–1868
  - and heat transfer analysis, 1868–1871
  - reliability, 1865–1866
  - resistance, 1864–1865
  - and structural analysis (see Structural analysis and fire resistance)
- load combinations, 261, 1874–1875
- structural analysis
  - before fire, 1877–1878
  - during fire, 1878–1881
  - at required resistance time, 1881–1882
  - utilization of substructures, 1882–1883
- structural steel design criteria, 1889–1890
- walls, 1886–1889
  - load-bearing, 1886
  - separating function in fire conditions, 1886
  - separating function in normal conditions, 1886
  - thermal gradient across thickness, 1888

**Building Code Requirements for Reinforced Concrete (American Concrete Institute), 1964****Building Envelope**

- exterior wall and enclosure systems, 3248
- exterior wall openings, 3272–3276
- Fire spread between buildings, 3242–3245
- loss history, 3276–3279
- risk assessment factors, 3279–3281
- vertical fire spread, 3245–3248

**Building Fire Simulation Model, 2987****Building materials. See also specific materials**

- burnable/nonburnable, 279
- classification, 277–278
- composite materials
  - porosity, 286
- creep, 282–283
- density, 285–286
- elevated temperatures and, 280–281

**Building materials. See also specific materials (cont.)**

- fire performance groupings
  - Group I (insulating), 280
  - Group I/F (insulating/fuel), 280
  - Group L (load-bearing), 280
  - Group L/I (load-bearing/insulating), 280
  - Group L/I/F (load-bearing/insulating/fuel), 280
- homogeneous/heterogeneous, 277–278
- information sources, 291
- mass loss, 284–285
- material-specific properties, 281–283
- mixed composition, 279
- modulus of elasticity, 281–282
- moisture sorption, 278–279
- porosity, 278–279, 285–286
- and reference condition, 281
- specific heat, 286–287
- stress-strain relationships, 281
- structure-sensitive/-insensitive properties, 278, 288, 292, 293
- thermal conductivity, 287–288
- thermal diffusivity, 288
- thermal expansion, 284
- thermal properties, 284–288
- ultimate strength, 281–282
- yield strength, 281–282

**Building Research Institute**

(Japan). See National Research Institute for Fire and Disaster (Japan)

**Buildings**

- smoke movement in tall, 1789, 1791
- vent flows in, 474

**Buildings, fire risk analysis,**

- approaches/methods/models, 2957–2962
  - event tree analysis, 2960
- assessing probabilities, 2981
- data-gathering methods
  - causal relationship of initiating events/hazards/consequences, 2948–2949
  - consequence analysis, 2944
  - hazard assessment, 2944–2948
  - as low as reasonably practicable (ALARP), 2952
- fire risk characterization, 2943
- fire safety concepts tree, 2949–2950
- FN curves, 2951–2952
- guidance documents, 2975–2980
- risk-cost assessment models (see also specific models)
  - building fire safety evaluation method (BFSEM), 2973–2975
  - hazard/risk matrices, 2969–2970
  - performance matrix, 2970–2973

**Buildings, fire risk analysis (cont.)**

- uncertainty/variability/unknowns, 2956–2957
- Buoyancy forces**
  - center of, 500
  - and convection heat transfer, 71–73, 77, 81, 98
  - fire plumes, 400
  - smoke movement, 1045
  - and vent flows, 467, 469, 470
- Burning rate**, 145, 151, 236, 354, 361–364, 378, 390, 398, 400, 403, 434, 490, 499, 508, 520, 524, 525, 740, 799, 800, 808, 813, 828, 830, 857, 867, 883, 920, 929, 931, 943, 985, 986, 996, 997, 999–1002, 1010, 1013, 1027, 1272, 1273, 1356, 1591, 1592, 1606, 1659, 1666, 1786, 1849, 1856, 2390, 2553, 2556–2558, 2571, 2572, 2574–2583, 2585–2587, 2593–2595, 2600, 2612, 2622, 2629, 2638, 2741, 2750, 2810, 2964, 3006, 3074, 3246, 3356
- Burning velocity, flames**, 376, 377, 2739, 2742

**BURNSIM model**, 2384**Burns, skin**

- classifications, 2380
- conducted heat, 2377
- consequences, 2379–2380
- convected heat, 2377–2378
- over large areas, 2379
- pain and, 2378–2379
- radiant heat, 2378

**Bushes, heat release rates**

- natural, 861–863
- plastic, 863

**Business protection, goals**, 1315**Butane, boiling point**, 537, 559**C****Calorimeters**

- industrial-scale, 937, 943, 946
- intermediate-/large-scale
  - furniture calorimeter, 932–934
  - intermediate-scale calorimeter (ICAL), 931–932
  - room/corner test, 934–936, 938
- single burning item test, 936–937
- standard hood/exhaust duct, 930–931
- open-burning calorimeters, 799–802, 852
- oxygen consumption calorimeter (see Oxygen consumption calorimeter)

**Calorimeters** (*cont.*)

- small-scale
  - comparative studies, 929–930
  - cone calorimeter (*see* Cone calorimeter)
  - fire propagation apparatus, 926–927
  - Ohio State University (OSU) calorimeter (*see* Ohio State University (OSU) calorimeter)
  - use/application of heat release rate data, 937–943

**Calorimetry**

- combustion bomb calorimeter, 142
- factors affecting small-scale measurements
  - airflow, 922
  - edge effects, 921–922
  - open/closed configuration, 918–919
  - other measurements, 922
  - specimen orientation, 922
  - specimen size, 920–921
  - type of heater, 919–920
  - type of ignition pilot, 920
- heat release rate measurement techniques
  - carbon dioxide generation, 926, 927, 1145–1147, 1149, 1183, 1187
  - compensation method, 911
  - oxygen consumption method, 911–915
  - sensible enthalpy rise method, 907–910
  - substitution method, 910–911
- oxygen bomb calorimeter test, 906
- gross/net heat of combustion, 906–907
- oxygen consumption, 146, 239, 896, 912–914, 917, 918, 924, 928, 934, 945, 952, 956, 1144–1147, 1182–1184, 1187, 1188
- uncertainty of heat release rate measurements, 943–945
- use/application of industrial-scale data, 943
- use/application of intermediate-scale data, 942
- use/application of small-scale data
  - analytical models, 938–939
  - physics-based models, 939–942
  - regression models, 938

**Carbon dioxide (CO<sub>2</sub>)**

- asphyxiant, 1540
- CO and generation efficiency, 1206–1208
- fire concentrations
  - and hyperventilation, 1540
- fire product yield, 1196, 1199, 1200, 1210–1211

**Carbon dioxide (CO<sub>2</sub>)** (*cont.*)

- heat of formation, 144, 145
- incapacitation from, 2243, 2244
- oxygen consumed and amounts generated, 1201–1202
- specific heat, 1537, 1539
- systems
  - fire extinguishing mechanisms, 1536
  - health and safety, 1540–1545
  - local applications, 1531, 1532, 1534, 1567–1573
  - nozzle selection, 1575–1584
  - thermal-physical properties, 1536–1540
  - total applications, 1554–1567

**Carbon dioxide generation**

- calorimeter**, 571, 1144–1147, 1149, 1183, 1184, 1187, 1188

**Carbon monoxide (CO)**

- CO<sub>2</sub> and generation efficiency, 1206–1208
- fire product yields, 1196, 1200, 1202, 1203, 1210, 1211, 1215
- fire ventilation and, 1202–1204
- heat of combustion, 143
- heat of formation, 145
- predicting uptake in humans, 2359
- and smoke generation efficiency, 1208
- smoke management and, 1826–1827
- smoldering fires, 595, 2287, 2355, 2392, 2393
- specific heat, 140, 141, 2667
- toxicity
  - Ct* product dose, 2332
  - fractional effective dose (FED), 2324, 2393, 2405, 2416
  - fractional incapacitating dose (FID), 2405
  - interaction with carbon dioxide, 2232
  - interaction with hydrogen cyanide, 2222
  - and low-oxygen hypoxia, 2292, 2370

**Carbon tetrachloride, as early**

- extinguishing agent**, 1451, 1452

- Carboxyhemoglobin (COHb)**, 1239, 2220, 2221, 2299, 2301, 2313, 2315, 2322, 2326, 2329, 2331, 2333, 2346, 2362, 2396, 2407
- predicting concentrations, 2419

- Carpeting, heat release rates**, 818, 866, 878

- Cars, passenger.** *See* Motor vehicles

- Case goods, heat release rates**, 816
- CEFICOSS computer program**, 1944

**Ceiling fires**

- CFD model application to coffered ceiling, 1059, 1060
  - corridor flame spread, 713–714
  - corridor heat transfer, 761–765
  - flame spread, 713–714
  - heat transfer beneath, 765–769
- Ceiling jet flows**
- buoyancy and, 429, 430, 449
  - confined ceilings
    - channel configuration, 445–446
    - general enclosure configurations, 447–449
  - convective heat transfer
    - ceiling jet region, 439
    - weak plume impingement region, 438
  - development in corridors, 449–451
  - entrainment and, 434, 445, 451
  - excess temperature, 430–435
  - excess velocity, 430–435
  - flame length, 437
  - friction factor, 439
  - heat release rates, 431, 432, 434, 435, 437–444, 446–450
  - nondimensional relations, 435–437
  - sloped ceilings, 439–441
  - steady fires
    - strong plume-driven flow field, 437
    - weak plume-driven flow field, 429–437
  - submerged/two-layer environment, 429, 431, 441, 443, 447, 449, 451
  - temperature, 429, 430, 435–437, 439–449
  - thickness, 430, 437
  - time-dependent fires
    - power-law fire growth, 442–445
    - quasi-steady assumption, 441–442
- Ceiling jet stage, compartment fires**, 1067–1068
- Ceiling layer, fire plumes**, 414. *See also* Compartment fires, two-layer system
- Ceiling linings.** *See* Wall/ceiling lining materials
- Ceiling temperature, polymer decomposition**, 199
- Cellulose, heat of combustion**, 143
- Cellulosics**, 172, 179, 227, 502, 581, 583, 591, 592, 600, 613, 615, 620, 622, 637, 662, 830, 890, 1001, 1003, 1137, 1174, 1264, 1301, 1456, 1511, 1533, 1589, 2235, 2237, 2240, 2246, 2250, 2277, 2281–2283, 2291, 2295, 2296, 2942, 3215, 3244, 3272, 3311
- thermal decomposition, 181



- Central Limit Theorem**, 2835, 2862
- CET89 computer code**, 2751
- CFAST multiroom zone model**, 942, 956, 1028, 1097, 1249, 1274, 1818, 2243, 2244, 3009, 3016, 3039, 3233–3235, 3356, 3364
- CFD**. *See* Computational fluid dynamics (CFD) models
- CFX Flow3D CFD model**, 1056, 1610, 1611
- Chain scission mechanisms, thermal decomposition**, 183, 213–216, 220
- Chairs**  
heat release rates of lightly upholstered, 818  
heat release rates of stackable, 818 upholstered, room effects on heat release rates, 800
- Chapman-Jouguet theory, detonations**, 2751, 2752
- Char(ring)**  
building materials, 290–291  
decomposition of polymers, 197  
and ignition of solid fuels, 639  
intumescent, 241, 247  
rate, 290, 291, 309, 1984–1986, 1988, 1991, 1992, 1994, 1997–1999, 2002, 2003  
wood, 265, 290, 291, 1985–1994
- Checklists**  
evacuation computer models, 2088, 2174  
fire risk analysis method, 2825, 2981
- Chemical equilibrium**  
carbon formation in oxygen-deficient systems, 157–158  
computer programs for calculations, 165–166  
constant, 151–153  
departure from equilibrium, 158  
and dissociation, 151, 156  
quantification of constants, 154–156  
sample problems, 158–165  
simultaneous, 153–154
- Chemical heat**, 1187, 1188, 1194
- Chemical heat of combustion**, 1182, 1185, 1186, 1188, 1192, 1193, 1196, 1209, 1210, 1218, 1224
- Chemical heat release rate**  
determined by CO<sub>2</sub> generation  
calorimetry, 1146, 1147, 1183  
determined by oxygen consumption calorimetry, 1183–1184  
and flame height, 398, 402
- Chemical reactions, exothermic/endothermic**, 377, 616, 1898, 3164
- c-Hexane (c-C<sub>6</sub>H<sub>12</sub>), heat of combustion**, 143
- Children, arousal by smoke detector**, 2463
- Chi-square distribution**, 2839–2840, 2854, 2866, 2867, 2869, 2915
- Chlorinated polyvinyl chloride (CPVC), thermal decomposition**, 1154, 3453, 3458
- Chlorine, heat of formation (atomic)**, 145
- α-chloroacetophenone (CN)**, 2233, 2250
- o-chlorobenzylidene malonitrile (CS)**, 2233, 2250
- Christmas trees, heat release rates**  
artificial, 863, 864  
natural, 859–863
- CIB**. *See* Conseil International du Bâtiment (CIB)
- Cigarette smoldering**, 592, 2342, 2392, 2999, 3214
- Class A foams**, 1300, 1737–1739, 3286
- Clean agent halon replacements**  
characteristics, 1483–1485  
environmental concerns  
global warming potential, 1483–1485, 1503–1504  
ozone depletion, 1502–1503  
explosion inerting, 1498  
explosion suppression, 1498–1499  
extinguishing mechanisms, 1485–1486  
flammable gas/liquid extinguishing concentration  
cup burner apparatus, 1486–1492  
opposed-flow diffusion flame apparatus, 1488, 1492, 1493  
halocarbon compounds (*see* Halocarbon extinguishing agents)  
inert gas mixtures (*see* Inert gas extinguishing agents)  
solid fuel extinguishing concentration, 1492–1495  
system design  
agent hold time and leakage, 1526–1527  
agent quantity, 1512  
compartment pressurization, 1525–1526  
and decomposition products, 1513–1516  
design concentration, 1509–1512  
discharge time, 1513  
flow division at tees, 1519, 1521–1522  
hydraulic flow characteristics, 1517–1520
- Clean agent halon replacements (cont.)**  
nozzle area coverage/height limitations, 1524  
pressure drop due to friction loss, 1522, 1523  
testing/approval of design methods, 1522–1524  
thermophysical properties, 1505–1508  
toxicity, 1499–1502  
use on energized cables/equipment, 1494, 1496–1498
- Cleanrooms, fire propagation index for polymeric materials**, 1162, 1163
- Cleveland open cup apparatus**, 566
- Clothing items, heat release rates**, 818–820
- Cluster sample**, 2871
- CMA wood charring model**, 1994
- Coburn-Forster-Kane (CFK) equation**, 2331, 2350, 2352, 2354, 2367, 2416, 2417, 2419–2421
- Codes**  
design disadvantages, 1236–1237  
design requirements, 2309  
safety factors, 1137, 2309–2311, 3209
- Coffee makers, heat release rates**, 821
- COFRA fire risk indexing model**, 3178–3179
- Cognition**, 2078, 2921
- Cognitive error**, 2921
- Columns**  
buckling, 265–267, 270, 1443, 1893, 1904, 1905, 1939–1941, 1996, 1999  
critical stress in steel, 1941  
critical temperature determination in steel, 288–289, 293, 294, 296, 312, 1938–1940, 2838, 2889  
Euler equation, 1095–1097  
failure, 264, 270  
fire resistance in steel, 1910, 1911, 1913, 1916, 1919, 1936  
fire resistance testing, 1910  
heat transfer analyses, 1911, 1927–1936  
liquid-filled, 1919, 1930  
reinforced concrete, 1973–1974  
slenderness ratio, 1939, 1941, 1974
- Combustion bomb calorimeter**, 142
- Combustion efficiency**, 145, 398, 399, 403, 424, 496, 522, 523, 582, 866, 909, 1001, 1013, 1014, 1137, 1139, 1159, 1182, 1186–1188, 1192, 1200, 1209, 1212–1214, 1221, 1223, 2289, 2291, 2394, 2640, 3038

**Combustion kinetics**

- branching, 329, 624
- chain-branching, 329, 340, 341
- chemical equilibrium in flame/
  - postflame gases, 328
- combustion products, 486, 493, 504, 511, 512, 514, 515, 517, 519, 520, 1181
- competition between elementary reactions
  - and action of extinguishing/retardant agents, 595
  - oxidation rates and degradation of fuel, 337–339
  - rate of oxidation of CO by hydroxyl radicals to that of fuel molecules, 339–340
  - rates of reaction between H atoms and molecular oxygen, 340–341
  - role of chain branching, 335, 336, 340, 341, 342, 344
- free radicals, 328–329
- fundamentals
  - concentrations, 332, 336, 344
  - order of reaction, 331
  - rate constant, 332
  - rate of reactions, 335, 1041
  - temperature dependence of reaction rates/activation energy, 333–335
  - gas-phase reactions, 335, 336
  - hydrocarbon oxidation mechanisms, 507, 509
  - initiation, 1147–1150
  - propagation, 1154–1156
  - soot formation, 2640
  - temperature range breadth, 627
  - termination, 329

**Combustion products.** *See* Fire products; Species production, effect of combustion conditions on

**Compartment fire modeling**

- breathing effect, 985
- computational fluid dynamics models (*see* Computational fluid dynamics (CFD) models)
- conduction heat transfer, 990
- conservation equations
  - energy, 984–985
  - mass, 983
  - species, 984
- convective heat transfer, 988–989
- door vent, 982
- entrainment, 981, 983, 987
- fire growth rate, 991
- forced flow effects, 991
- radiative heat transfer, 989–990

**Compartment fire modeling (cont.)**

- submodels
    - embedded, 991–992
    - mass/heat transport, 987–991
    - source term, 986
  - unresolved phenomena, 992, 993
  - upper/lower layers, 981, 982, 986, 989, 990
    - mixing between, 990–991
  - vent flows through horizontal openings, 988
  - vent flows through vertical openings, 987–988
  - volumetric expansion effect, 985
  - zone models (*see* Zone models)
- Compartment fires**
- conservation of energy and, 1002
  - conservation of mass and, 1000–1002
  - corner tests (*see* Room/corner tests)
  - defined, 996
  - energy generated, 999–1000
  - flame spread, 992
  - free-burning/fuel-controlled, 1000, 1015
  - heat release rates, 997, 1005, 1009, 1011, 1015–1018
    - equivalence ratio, 1010
  - ISO 9705 standard test, 504, 711, 712, 757, 788, 801–803, 848, 852, 853, 859, 891, 892, 935–938
  - and measurement of heat release rates, 1014, 1015
  - predicting flashover
    - Babrauskas method, 1018–1019
    - comparison of methods, 1020–1021
    - McCaffrey et al method, 1019–1020
    - Thomas method, 1020
  - predicting postflashover temperatures
    - Babrauskas method, 1010–1014
    - Law method, 1013–1015
    - Swedish method, 1016, 1017
  - predicting preflashover temperatures
    - Beyler and Deal method, 1006–1007
    - Beyler method, 1008–1009
    - Foote et al. method, 1005–1006
    - McCaffrey et al. method, 1002–1005
    - Peatross and Beyler method, 1007–1008
  - radiative heat transfer, 989–990, 1003
  - secondary/remote ignition, 1271
  - species product formation
    - compartment fire experiments, 499–505
    - full-scale studies, 504
    - hood experiments, 493–499

**Compartment fires (cont.)**

- stages
    - enclosure smoke-filling, 1068–1069
    - fire plume/ceiling jet, 1067–1068
    - postflashover vented, 1069, 1070
    - preflashover vented, 1069
    - temperature calculation, 998–999
    - temperature-time estimation
      - assumptions, 988, 989, 998
      - CIB data, 1001, 1013, 1014
      - duration of temperature, 1016, 1018
      - experimental results, 1013, 1014, 1020, 1021
      - factors affecting temperature rise, 998
      - heat release rate, 997, 1017–1019, 1132
      - increased fuel load, 1016
      - level of protection/location, 996, 1002
      - manner of ignition/enclosure lining, 996
      - standards, 1017
      - temperature-time history, 146, 1017, 1018
      - ventilation, 997, 999–1002, 1004–1008, 1013, 1015–1020
  - transport to adjacent spaces
    - burning in unconfined adjacent areas, 512
    - burning in confined adjacent areas, 512–515
    - effects of burning outside compartment, 511
    - effects of oxygen-deficient smoke layers, 517–519
    - forced ventilation and, 519
    - predicting species levels, 515–517
    - two-layer system, 487, 489, 490, 500, 523
    - ventilation-controlled, 997, 999–1002
    - vent openings, 487
- Compartment fires, modeling smoke filling**
- comparisons with experimental data, 1097–1099
  - conditions in descending smoke layer, 1085–1087
  - descending smoke layer analysis, 1082–1085
  - forced ventilation effects on smoke layer
    - ceiling leakage path, 1093–1095
    - floor leakage path, 1091–1093
    - global effects, 1087–1091
    - smoke layer analysis, 1091
    - global (one-zone) analysis, 1088
    - concentrations of smoke/other species, 1078–1080

**Compartment fires, modeling****smoke filling** (*cont.*)

- leaky compartment, 1074–1075
- light attenuation/visibility through smoke, 1081–1082
- oxygen limitations on heat release, 1080–1081
- sealed compartment, 1073–1074
- temperature rise, 1075–1078
- modeling background, 1067
- numerical methods for solving initial value problems
  - Adams-Bashforth method, 1096
  - explicit or forward Euler method, 1095
  - Heun's method, 1096
  - Runge-Kutta methods, 1096
- phenomena associated with, 1070–1072

representative models, 1096–1097

**COMPBRN III zone fire model**, 1027**Compensation calorimeter**, 911**COMPF2 postflashover zone fire model**, 867, 1010, 1027, 1028**Components**

- mean time between failures (MTBF), 2789–2790, 2877, 2891, 2908, 2909
- mean time to failure (MTTF), 2877, 2880, 2929, 2930
- mean time to repair (MTTR), 2877, 2900, 2908, 2909
- nonrepairable/repairable, 2876

**Composites**, 29–30, 32–33, 121, 186, 189, 216, 222, 224, 273, 274, 278, 279, 285, 286, 309, 310, 313, 413, 585, 641, 707, 717, 774, 775, 785–787, 808–810, 831, 852, 890, 921, 969, 974–975, 1098, 1134, 1135, 1152, 1162, 1165–1167, 1170, 1190, 1362, 1370, 1673, 1869, 1871–1873, 1885, 1886, 1889, 1899, 1905, 1917, 1943–1945, 1950, 1956, 1957, 1974–1976, 1984, 1986, 1996, 2001–2002, 2004, 2185, 2296, 2538, 2962, 3022, 3094, 3248, 3250, 3252, 3257, 3265, 3268, 3371, 3379, 3453, 3454, 3469

**Composites and fiberglass-reinforced materials, fire propagation index**, 1164

**Compressible fluid motion**, 1380, 1382, 1624

**Computational fluid dynamics (CFD) models**

- applications
  - smoke filling, 1057, 1060
  - smoke movement, 1055

**Computational fluid dynamics (CFD) models** (*cont.*)

- computer hardware/software, 1049–1050
- explosion venting, 1056–1058
- finite volume method, 1048–1049
- fire spread, 1035, 1054, 1058
- general, 1035
- governing equations
  - assumptions, 1036–1037
  - conservation of energy, 1036
  - conservation of mass, 1036
  - conservation of momentum, 1036
- limitations, 1080–1081
- numerical solution
  - conservative/nonconservative, 1047
  - explicit/implicit, 1047
  - finite difference approximation, 1046–1047
  - order of accuracy, 1047–1048
  - spatial dimension, 1048
  - staggered/co-located variables, 1047
- outdoor applications/wind, 1059
- and quantifying fire scenarios, 1052–1054
- references, 1036, 1042, 1043
- smoke movement
  - example applications, 1055
  - fire source, 1037, 1058
  - large-volume spaces, 1055
  - open boundary conditions, 1045
  - visibility, 1045
- source terms and boundary conditions
  - combustion, 1041–1042
  - energy exchange at boundaries, 1044–1045
  - generation of species, 1042
  - mass exchange at boundaries, 1043
  - momentum exchange at boundaries, 1043–1044
  - radiation heat transfer, 1042–1043
- sprinkler activation with coffered ceilings, 1045
- tunnel applications, 1057–1058
- turbulence modeling
  - direct numerical simulation, 1037
  - isotropic turbulence assumed, 1039
  - large eddy simulation, 1039–1040
  - Reynolds-averaged Navier-Stokes approach, 1037–1039
  - verification/validation, 1050–1051
- visualization, 1050
- water mist fire suppression systems, 1591

**Computer fire models**, 981, 1000, 1024–1032, 1357, 1840, 2036, 2269, 2918, 2919, 3000, 3009, 3010, 3039, 3133. *See also* Computer simulation models; Zone models

**Computers**

- CPU heat release rates, 821, 822
- heat release rates of racks with equipment, 822, 823, 826, 827
- heat release rates of tapes, 821–822, 827
- keyboard heat release rates, 821, 822
- message passing interface, 1050
- mice heat release rates, 821
- monitor heat release rates, 821, 823–826
- parallel processing, 1049, 1050
- printer heat release rates, 821, 826

**Computer simulation models.** *See also*

- Evacuation computer models applications, 3125–3128 (*see also specific models*)
- compartment fires (*see* Compartment fire modeling)
- descriptive models, 3118
- Monte Carlo procedures, 3122–3123
- output analysis, 3132–3133
- physical models, 3118
- sensitivity analysis, 3122–3125
- simulation models
  - continuous, 3120–3122
  - discrete, 3119–3120
- symbolic models, 3118
- uncertainty and, 3129–3132
- validation, 3128–3129

**COMSOL computer program**, 1127, 1994, 2001

**Concrete**

- aggregates, 1950, 1952–1953, 1955–1957, 1959, 1961, 1962, 1976
- bond with fiber-reinforced polymers, 1976
- compressive strength, 1949, 1950, 1952, 1961, 1962, 1969, 1973, 1976
- creep, 298, 299, 1880
- density, 1950, 1953, 1954
- fiber-reinforced (*see* Fiber-reinforced concrete (FRC))
- as fire protection material, 1949
- heterogeneous material, 278
- high-strength (*see* High-strength concrete (HSC))
- lightweight, 296, 299, 300, 1363, 1876, 1912, 1922, 1923, 1957, 1960, 1966
- mass loss, 285



**Concrete** (*cont.*)

- modulus of elasticity, 1950, 1951, 1953, 1954
- normal-strength (*see* Normal-strength concrete (NSC))
- properties,
  - modulus of elasticity, 1950, 1951, 1953, 1954
  - strength, 1950–1953
  - thermal expansion, 1965–1968
- reinforced, bond between rebar and concrete, 1951, 1970, 1975
- spalling, 1903, 1976
- specific heat, 1950, 1953, 1955
- thermal conductivity, 1950, 1955–1956
- thermal properties, 1951, 1953
- volumetric heat capacity/temperature relation, 298–300

**Concrete members**

- beams, 1950, 1961–1962
- bending strength, 1974, 1975
- composite steel-concrete construction, 1974–1975
- fire resistance determination by analytical methods
  - continuous one-way span example, 1962–1965, 1969
  - continuous unrestrained flexural members, 1962–1964
- heat transmission, 1956–1960
- members restrained against thermal expansion, 1965–1968
- simply supported slabs/beams, 1961–1962
- floor slabs, 1935
  - and thermal thrust force, 1965, 1966, 1968
- heat transfer/temperature profiles, 1949–1950
  - determination methods, 1949
- prestressed concrete assemblies, 1950, 1974
- recent developments
  - Eurocodes, 1950, 1961, 1974, 1975
  - fiber-reinforced concrete, 1976
  - high-strength concrete, 1976
  - hollow-core slabs, 1976–1977
  - spalling, 1976
  - temperature calculation, 1950, 1975
- reinforced concrete columns, 1973–1974
- reinforced concrete frames, 1974
- reinforced concrete walls, 1974
- thermal degradation at high temperatures, 1985

**Concrete structures, temperature in fire-exposed**

- fire-insulated, 1126–1127
- one-dimensional calculations, 1124–1126
- penetration depth in semi-infinite structures, 1122–1124

**Conduction heat transfer**

- compartment fire modeling and, 990
- Fourier's law and, 27
- heat diffusion equation, 1107
- integral (Duhammel's) analysis method, 40–42
- limitations on analytic solutions, 48
- modeling in materials, 29
- numerical techniques, 45
- models, 3009
- separation of variables analysis method, 38–39
- steady-state examples, 30
- thermally thin material, 33–34
- thick plates, 33–34
- through cavity walls, 3248–3250
- through laminated plates, 3271
- through pipe walls, 2747
- through plates, 38
- through solid wall, 1362, 3250
- through spherical solid with internal generation, 33, 40

**Cone calorimeter**

- additional gas analyzers, 972
- airflow, 962–963
  - exhaust system, 963
- calibration equipment, 961, 962, 971, 972
- controlled-atmosphere type, 977
- edge frame, 969
- features, summary of, 952–954
- means of ignition, 963–965
- measurements taken with, 975–976
- and nonambient pressures, 977
- operating principle, 956–957
- optical density measurement, 971
- orientation of heater/specimen, 960–962
- paramagnetic oxygen analyzer, 957
- radiant heater
  - choice of heater type, 957–958
  - conical shape, 958–959
  - convective fraction of heating flux, 959–960
  - design details, 958
  - emissivity of, 959
  - range of heat fluxes needed for testing, 957
  - uniformity of heating flux, 960
- repeatability/reproducibility of tests, 976
- ring sampler, 971, 973
- smoke measurement, 970–971

**Cone calorimeter** (*cont.*)

- specimen area, 965–966
- specimen thickness, 966, 967
- standard version, 925, 926
- testing specifications
  - edge effects, 969
  - intumescent samples, 969–970
  - load cell, 961, 962, 967–968
  - specimen orientation/holders, 966–968
  - toxicity test, 2270, 2275
  - wire grid use on specimens, 969, 970

**Cone Calorimeter Annotated Bibliography (Babrauskas), 898****Confidence coefficient/limits, 295, 896, 2234, 2861–2862, 3238****Configuration factors, 120, 121, 2601, 2604, 2606–2609, 2613–2616, 2619, 2645, 2654, 2655, 3243–3246, 3476–3492****CONFIRE computer program, 1974****Conseil International du Bâtiment (CIB), compartment fire experiments, 1001****Consequence analysis, 1276–1277, 2758, 2943, 2944, 2948, 2949, 2969, 3185–3186, 3200****Consequences**

- decision analysis and, 3048, 3049, 3059
- defined, 3049

**Conservation equations, convection heat transfer, 58–64. *See also* Energy, conservation of; Mass, conservation of; Momentum, conservation of****Consumer Product Safety Commission (CPSC), 675, 853, 3079, 3084, 3095, 3108, 3223****Consumer products, fire risk analysis. *See* Products (finished), fire risk analysis****CONTAM multizone fire model, 1027, 1029, 1788, 1791, 1794, 1797, 1799, 1801, 1804, 1807–1809, 1818****Contingency table, 2870****Continuity equation. *See* Mass, conservation of****Continuous probability distribution, 2831–2835, 2857, 3034, 3036****Control volume fire models. *See* Zone models**

- Convection heat transfer**  
 boundary layer concept  
 boundary layer approximation, 66–67  
 heated, vertical plate, 71–75  
 laminar flow over flat surface, 67–71  
 laminar free convection, 71  
 calculations  
 electrical strip heater, 94–97  
 fire door, 98–99  
 glass-door fire screen, 97–98  
 coefficient of  
 basic laws and, 54–58  
 experimental determination, 88–89  
 compartment fire modeling and, 988–989  
 complications in practical problems  
 changes in fluid properties, 85  
 complex geometry, 83–85  
 effect of mass transfer, 85–86  
 effect of turbulence, 80–83  
 conservation equations for, 58–64  
 simplifications, 64  
 empirical relations, 86–94  
 to fire-exposed structures, 1105–1107  
 natural/forced, 53  
 simple example, 53–54
- Convective heat release rate**, 406, 407, 409, 413, 415, 417, 424, 431, 432, 434, 435, 437–439, 442, 443, 926, 943, 1146, 1148, 1166, 1167, 1184, 1188, 1192, 1210, 1316, 1324, 1327, 1329, 1833, 1842, 1852
- Conversion factors**, 146, 2126, 2134, 2801, 3161, 3397–3424
- Conveyor belts, fire propagation index**, 1161
- Cook County Administration Building fire (2003)**, 901, 1065, 2113
- Copper pipes, properties**, 1389, 1392, 1408, 1430, 3491
- Corners**  
 effect on ceiling jet flows, 434, 446–447  
 effect on flame spread, 707, 712  
 effect on plume, 396, 420–422  
 heat transfer from fires in, 751–759
- Correlation coefficient**, 929, 944, 1203–1205, 1207–1209, 2620, 2622, 2836, 2857–2860, 3011, 3018, 3023, 3041, 3070
- Corridors**  
 ceiling fire heat transfer, 450  
 ceiling flame spread, 713–714
- Corridors (cont.)**  
 development of ceiling jet flow, 449–451  
 heat transfer in, 761–765  
 transient flows, 992, 993
- Corrosion**  
 measurement methods, 732–733  
 nonthermal damage, 1219
- Cost-benefit analysis**  
 air transportation risk management, 3382–3383  
 engineering economies, 3137, 3143, 3146, 3148  
 residential fire sprinklers example, 2818, 3025, 3026  
 risk assessment example, 3184
- Cottonseed meal, autoignition**, 627
- Couette flow, liquids**, 720
- CPSC**. *See* Consumer Product Safety Commission (CPSC)
- CRC Handbook of Chemistry and Physics (Weast and Astle, eds.)**, 558, 1168
- Creepage, arc tracking and**, 673
- Creep, building materials**, 282–283  
 concrete, 298, 299, 1880  
 steel, 293  
 in tension members, 264–265
- Cribs**  
 center-ignited, 829  
 heat release rates, 828–830  
 ignited uniformly, 829  
 room fire effects, 830
- CRISP II fire risk assessment model**, 3125
- CRISP risk assessment model**, 3125
- Critical heat flux (CHF)**, 211, 239, 586, 588, 1147, 1149, 1150, 1152, 1154, 1161, 1166, 1171, 1198, 1216–1217, 1256, 2656, 2722, 2724, 3243, 3451–3455, 3465, 3468
- Critical stress**  
 steel beams, 1941–1943  
 steel columns, 1941, 1942
- Critical temperature, algebraic equations for steel members**  
 beams, 1938–1939  
 columns, 1939  
 computer programs, 1943–1945
- Cross-linking mechanisms, thermal decomposition**, 179, 182, 183
- Crowd management/control**, 2034, 2040, 2042–2044
- CRSI Handbook (Concrete Reinforcing Steel Institute)**, 1969, 1971
- CSTBZ1 postflashover fire model**, 1028
- Curisk risk assessment program**, 2968
- Curtains, heat release rates**, 830–832
- D**
- Daegu (Korea) subway fire (2003)**, 3374
- Damköhler number**, 369, 370
- Dangerous Substances and Explosive Atmospheres Regulations (U.K.)**, 571
- Darcy-Weisbach equation**, 1388, 1391, 1395
- Decile**, 2856
- Decision analysis**  
 consensus  
 alternative stability approach, 3069–3070  
 comparative, 3070  
 compound, 3070  
 definitive, 3069  
 decision classifications  
 decision making under certainty, 3051  
 decision making under risk, 3051–3052  
 decision making under uncertainty  
 Hurwicz paradigm, 3054  
 Laplace paradigm, 3053  
 Savage paradigm, 3053–3054  
 Wald (minimax/maximin) paradigm, 3053  
 fire safety attribute weighting  
 effectiveness matrices, 3061–3062  
 hierarchy approach, 3061  
 measurement  
 interval scale, 3066–3067  
 nominal scale, 3066  
 ordinal scale, 3066  
 ratio scale, 3067  
 multiobjective decisions  
 additive weighting, 3057  
 attributes, 3056  
 disjunctive, 3056  
 dominance, 3056  
 illustration, 3057–3060  
 objectives, 3055–3056  
 satisficing, 3056  
 values/utilities, 3056  
 weighting, 3056, 3057  
 panels of experts  
 committee, 3067  
 computer conferencing, 3068  
 DACAM group, 3068–3069  
 Delphi panel, 3068  
 nominal group, 3067–3068  
 payoff matrices, 3173–3174

- Decision analysis** (*cont.*)  
 probability  
 axioms of, 3050  
 frequentists, 3049  
 objective/subjective, 3049  
 subjectivists, 3049  
 subjectivity, 3049  
 uncertainty, 3049  
 weighting methods, fire safety  
 evaluation  
 analytic hierarchy process (AHP),  
 3064–3065  
 Edinburgh cross-impact analysis,  
 3062  
 hierarchical cross-impact analysis  
 (HCIA), 3063–3064
- Decision tree**  
 decision analysis, 2946, 3384–3385  
 fire risk analysis, 2824, 2950, 3053  
 risk decision making in rail  
 transport, 3381
- Decks**  
 fire resistance, 1999–2000  
 heat release rates, 831
- Deep storage fires**  
 flame height, 401  
 virtual origin, 413, 414
- Deflagrations.** *See* Explosion  
 protection, closed vessel  
 deflagrations
- Degrees of freedom, distribution  
 parameters,** 2915
- Delphi panels,** 3068–3070, 3086
- Deluge sprinkler system,** 1620,  
 1686, 1767, 2029
- Density**  
 building materials, 305–309, 314,  
 316  
 fluids, 1, 29, 64, 71, 77, 1378, 1408,  
 1573, 1574
- Depolymerization,** 252
- Depropagation reactions, thermal  
 decomposition,** 215
- Design for Fire Resistance of  
 Precast Prestressed Concrete  
 (Prestressed Concrete  
 Institute),** 1974
- Desks, heat release rates,** 831–832
- DETECT-QS heat detector  
 response program,** 943, 1325,  
 1444
- Detect-t2 model,** 3235
- Detection system design**  
 cost analysis, 1369–1370  
 delay to detection, 1316  
 design fire, 1316, 1317  
 detection, 1317  
 fire alarm audibility  
 and intelligibility, 1368, 1369
- Detection system design** (*cont.*)  
 scenarios, 1369–1370  
 sound pressure level, 1360–1363,  
 1365–1368  
 fire alarm visibility, 1370–1374  
 fire signature, 1317, 1318  
 heat detection  
 data selection, 1331–1334  
 design examples, 1334–1343  
 detector spacing, 1331–1333  
 error sources, 1325–1326  
 growing fires, 1324–1325  
 power-law fires, 1326–1330  
 response time index (RTI), 1321,  
 1322, 1324, 1326  
 steady-state fires, 1323–1324  
 heat flux setting, calculating, 132  
 precision/rounding off,  
 1314–1315  
 process goals, 1315  
 radiant energy, 1357–1358  
 example, 1358–1359  
 smoke detector response  
 calculation examples,  
 1350–1357  
 entry resistance, 1348–1350  
 and forced ventilation systems,  
 1351–1354  
 modeling, 1344–1345  
 and obscuration/attenuation,  
 1344–1345  
 temperature approximation theory  
 and, 1356–1357  
 system elements, 1317  
 use of models, 1320, 1322, 1323,  
 1328, 1330
- Detention/correctional occupancies,  
 fire risk indexing model,**  
 3178
- Deterministic fire models,** 1024,  
 1031, 2039, 2919, 3364
- Detonations.** *See* Explosion  
 protection, detonations
- D-Glucose (C<sub>6</sub>H<sub>12</sub>O<sub>6</sub>), heat of  
 combustion,** 143
- Diagnosis time,** 2899, 2922
- DIANA computer program,** 1974
- Diesel fuel, pool fire emissive  
 power,** 1683, 2598, 2599
- Differential scanning calorimetry  
 (DSC),** 178, 179, 184,  
 186–188, 191, 192, 203, 218,  
 246, 286, 299, 307, 606, 630,  
 1168–1171, 1175
- Differential thermal analysis  
 (DTA),** 178, 179, 184,  
 186–189, 246, 287, 606
- Differential thermogravimetry  
 (DTG),** 185, 186, 195, 206
- Diffusion flames**  
 fire plumes and, 397, 398  
 flammability limits, limiting oxygen  
 index (LOI), 545, 546  
 premixed flames distinguished, 145,  
 235, 354  
 reduction/oxidation zones, 1194  
 wind effect on turbulent jet flames,  
 396
- DIN 53 436 toxicity test,** 2273–2274,  
 2289–2290
- Directional sounders,** 1365, 1366
- Discrete probability distribution,**  
 2831, 2832, 2835, 2846–2850
- Discretization, conduction heat  
 transfer analysis,** 1121
- Dishwashers, heat release rates,** 832
- Doors**  
 effect of mechanism on evacuation  
 time, 1259, 1751, 1752, 2021  
 number of open and smoke control,  
 478, 1001, 1030, 1043, 1057,  
 1343, 1745, 1751, 1752, 1759,  
 1768, 1799
- Dow Indices software,** 3179
- Dow's Fire and Explosion Index,**  
 3162
- Draft curtains,** 1028, 1029, 1325,  
 1843, 1844, 1849–1852, 2996
- Drag,** 53, 58, 77, 84, 726, 729, 1385,  
 1386, 1444, 1598, 1655, 2528,  
 2535–2537, 2562, 2596, 2753,  
 3287, 3288
- Dressers, heat release rates,**  
 833, 834
- Dry chemical fire extinguishers, static  
 electricity and,** 687, 1302
- Dry pipe sprinkler system,** 1748,  
 2780
- DSC.** *See* Differential scanning  
 calorimetry (DSC)
- DTA.** *See* Differential thermal  
 analysis (DTA)
- DTG.** *See* Differential  
 thermogravimetry (DTG)
- Dublin Stardust disco fire (1981),**  
 2405, 2406
- Ductility,** 170, 281, 301, 1865, 1873,  
 1876, 1904, 1976
- Ducts**  
 flame propagation in, 2777, 2787,  
 2788  
 fluid flow in  
 hydraulic radius, 365  
 laminar/turbulent, 20
- Duhammel's method, heat transfer  
 analysis,** 41–42, 51
- Dupont Plaza hotel fire (1986),**  
 2338, 2406, 2447

**Dust(s)**

- clouds
  - ignition by arcing, 670–671
  - minimum ignition energy, 670, 671, 684
  - minimum ignition temperature, 671
- explosion protection
- explosibility testing, 2766, 2767
- minimum explosible
  - concentration, 2771
  - particle size, 2766
- layers, minimum ignition
  - temperature, 2771
- lower flammability limits, 670
- particle size, 2766, 2768, 2769, 2771, 2772, 2784
- static electricity and, 671

**E****The Economies of Fire Protection (Ramachandran), 3098****Eddy thermal conductivity**, 81**Eddy viscosity**, 15, 81, 367, 1038–1040, 1062**EFSES fire risk indexing model**, 3172**Egress**

- available safe egress time (*see* Available safe egress time (ASET))
- elevators, 2026–2027
- escalators, 2027, 2029
- exit capacity, 2012, 2014–2015
- exit width, 2014–2016
- fire escapes, 2019
- pedestrian walkways, 2029–2030
- protect-in-place, 1743, 2021–2022
- refuge floors, 2029
- required safe egress time (*see* Required safe egress time (RSET))
- scenarios, 2032
- trains, 2027
- vessels, 2153

**Elastomers**, 171, 179, 220–222, 224, 803, 1161, 1165, 1452, 1457, 2234, 2788, 3452, 3459, 3465**Electrical cables, fire propagation index**, 1160**Electrical fires**

- defined, 662
- electrical discharges
  - arcs (*see* Arcs, electrical)
  - breakdown, 663–664
  - defined, 663
  - dielectric strength, 666
  - dielectric strength of solid/liquid insulators, 666
  - in gas, 663
  - glow discharge, 667

**Electrical fires (cont.)**

- ionization, 663
- in liquids, 663
- Paschen's Law, 664–666
- self-healing media, 663
- in solids, 663
- sparks, 663
- electric current, 662–663
- ignition and values of voltage/
  - current/power, 693–694
- ignition modes involving electric
  - current
    - arcing across a carbonized path, 671–673
  - dust clouds, 670–671
  - ejection of hot particles, 681
  - excessive thermal insulation, 681
  - floating neutral, 675, 676
  - gases, 670
  - gross overloads, 674
  - high voltage into low voltage
    - wiring, 675
  - lightning, 675
  - minimum ignition energy, 670, 671
  - miscellaneous phenomena, 681
  - overheating connections, 678–681
  - overloads and related phenomena, 674–678
  - sparking/arcing, 670
  - stray currents/ground faults, 675
  - surface flashover, 673–674
  - voltage spikes, 676
- ignition modes involving electric
  - currents/solids, 670–681
- static electricity discharge
  - charge separation, 682
  - discharge types, 682–683
  - general, 681–682
  - granular materials, 687–688
  - liquids, 668–6899
  - persons, 686–687
  - solids, 685–686
- time for fire to initiate, 681

**Electric cable trays, heat release rates**, 834**Electronic equipment**

- heat release rates, 823
- heat release rates of cabinets, 827

**Elevators**

- and evacuation use, 3128
- safe for handicapped/impaired
  - persons, 3129

**Elevator shafts, smoke control**, 1807**Emergency flaring**, 2630**Empirical distribution, reliability analysis and**, 2886, 3162**Enclosure fires. *See* Compartment fires****End-chain scission, decomposition mechanism**, 197**Endothermic reactions**, 142, 155, 1992**Energy, conservation of**

- computational fluid dynamics
  - models and, 2668, 2669
- convection heat transfer, 81
- in flames, 985

**EN, Eurocode 2: Design of Concrete Structures**, 1950**EN, Fire Extinguishing Media-Foam Concentrates**, 1661**EN 1363, Fire Resistance Tests**, 1127**Engineering analysis**

- coding categories and, 3089–3090
- data half-truths/myths, 3083–3084
- data sources
  - incident/event data, 3096
  - laboratory data, 3093–3094
  - usage/exposure data, 3093–3094
- field observation data
  - incident/field data on systems
    - performance, 3088
  - inspections/testing, 3087
  - judgment/opinions, 3087
  - product life tracking systems, 3088–3089
  - simulations/laboratory studies, 3087–3088
- handling unknown data, 3079–3084
- incident data, sources, 3076, 3089
- types of analysis/data needs, 3073–3076
- usage and exposure data, 3095–3096

**Engineering economics**

- benefit-cost analysis, 3146
- cash-flow concepts
  - diagrams, 3138
  - interest calculations, 3138–3139
  - notation symbols, 3138
  - time value of money, 3147
- comparison of alternatives, 3145
  - annual cost, 3145
  - discount rate, 3143–3144
  - inflation and discount rate, 3143–3144
  - present worth, 3144–3145
  - rate of return, 3145–3146
- Cost-Effectiveness Tool, 3151–3153
- extreme events, 3149
- identifying relevant benefits/costs, 3146–3147
- interest factors
  - beginning-of-period payments, 3142
  - capitalized costs, 3142
  - capital recovery factor, 3142
  - compound amount factor, 3139
  - continuous cash flow, 3142
  - continuous interest, 3140
  - discounting, 3139

- Engineering economics** (*cont.*)  
 gradients, 3142  
 interest periods, 3140–3141  
 interest tables, 3139, 3142, 3155  
 nominal/effective interest, 3140  
 present worth, 3139–3140  
 present worth factor, 3140, 3142  
 series compound amount factor, 3141  
 series payments, 3141–3142  
 series present worth factor, 3142  
 simple/compound, 3141  
 sinking fund factor, 3141  
 maximum possible loss (MPL), 3147  
 measurement of benefits/costs, 3146–3149  
 selection of best alternative, 3147–3149  
 software tools for interest calculations, 3143  
 standards development, 3150–3151  
 three-step protocol (NIST), 3149–3150  
 treatment of uncertainty, 3149
- Engineering Guide on Pool Fire Radiation (SFPE)**, 2600
- Engineering thermoplastics**, 174, 227
- English Channel tunnel fire (1996)**, 3374
- Enthalpy**, 4, 8, 9, 57, 63, 139, 140, 142, 144, 150, 154, 159, 161, 165, 180, 187, 188, 198, 286, 320, 375, 378, 381, 389
- Entrainment**  
 ceiling jet flows and, 429–451  
 ceiling layer and, 451  
 compartment fire modeling and, 981–993  
 fire plumes, 396–425  
 and species transport to adjacent spaces, 510–511
- Entropy**, 3, 154, 155, 166, 179–181, 183, 199, 1536, 1537, 1539, 1540, 2801, 2814, 3398
- Environmental Protection Agency (EPA)**, 1500, 1502, 1503, 1505, 1533, 1542, 1544, 1545, 1601, 1602, 1697, 2263, 2342
- Environmental protection concerns**  
 contamination from runoff water, 1276  
 e-folding lifetimes, 1503  
 foam agents  
 assessment methods, 1699–1701  
 biodegradability, 1699–1701  
 foaming/emulsification of fuels, 1701  
 mitigation strategies, 1701–1702  
 potential hazardous situations, 1699  
 system discharge testing, 1699
- Environmental protection concerns** (*cont.*)  
 toxicity, 1701  
 training evolutions, 1699  
 uncontrolled fires, 1698  
 halocarbon extinguishing agents  
 global warming potential, 1502  
 ozone depletion, 1502  
 halogenated agents, 1501  
 statutes, 629  
 toxic products of combustion, 1276
- EPA**. *See* Environmental Protection Agency (EPA)
- Epoxy resins, thermal decomposition**, 1276, 1277
- Equation of state, fluids**, 3–4
- Equivalence ratio**  
 and fire products generation rates, 926  
 heat release rates in compartment fires, 997–998
- Erlang distribution**, 2842–2843
- Error-forcing context**, 2921
- Error of commission**, 2921
- Error of omission**, 2921
- Ethane (C<sub>2</sub>H<sub>6</sub>)**  
 heat of combustion, 143  
 heat of formation, 145
- Ethanol (C<sub>2</sub>H<sub>5</sub>OH), heat of combustion**, 142, 144
- Ethene (C<sub>2</sub>H<sub>4</sub>)**  
 heat of combustion, 143  
 heat of formation, 145
- Ethylene 130**, 165, 174, 176, 181, 192, 193, 213, 368, 381, 382, 534, 540, 561, 625, 670, 773, 774, 1154, 1164, 1170, 1209, 1214, 1215, 1298, 1699, 2235, 2634, 2635, 2638, 2641, 2642, 2667, 2690, 2694, 2696, 2739, 2746, 2749, 2752, 3431, 3439, 3441, 3442, 3450, 3453, 3455, 3460, 3472
- Ethyne (C<sub>2</sub>H<sub>2</sub>)**  
 heat of combustion, 143  
 heat of formation, 145
- Euler column equation**, 1095
- Eulerian method, describing fluid motion**, 1610
- EUREFIC (European Reaction to Fire Classification) model**, 936
- Eurocode 4: Design of Composite Steel and Concrete Structures**, 1950
- Eurocode 2: Design of Concrete Structures**, 1950
- Eurocode 5: Design of Timber Structure**, 1979
- Evacuation**  
 aircraft, 1587  
 areas of refuge, 1266  
 available safe egress time, 1066  
 building characteristics, 1243  
 before building collapse, 2806  
 crowd movement and, 2034  
 delay time to start, 2435  
 calculating, 2091  
 directional sound guidance system, 2202  
 drill studies, 2441  
 egress time model, 1067  
 elevator use, 1343, 1752  
 engineering data  
 delay times, 2435  
 pre-evacuation, 2448  
 travel data, 2477, 2499  
 escape guidance systems, 2204  
 handicapped/impaired occupants, 2524  
 high-rise residence building, 2176  
 hydraulic model (*see* Hydraulic model, egress performance)  
 incident studies, 221  
 large retail store, 414  
 models (*see* Evacuation computer models)  
 movement in smoke, 1789  
 movement of people and, 2042  
 Fruin's level of service, 2016  
 occupant characteristics, 1243–1244, 1257  
 office buildings, 2087–2089  
 perception of time available for, 2014  
 premovement (*see* Evacuation, delay time to start)  
 required safe egress time, 2053  
 road tunnels, 2043  
 underground rapid transit station, 2053
- Evacuation computer models**  
 behavioral models, 2157  
 computer models, 2152  
 empirical engineering approach, 2152–2153  
 manual engineering approach, 2153  
 modeling process, 2154  
 model selection  
 age/generation, 2158  
 checklist, 2176  
 current models, 2157  
 distribution/cost, 2158  
 level of refinement, 2158  
 model characteristics, 2156–2158  
 modeling method, 2156–2157  
 origin (development/validation) of model, 2155–2156  
 output, 2157  
 scope of representation, 2157



- Evacuation computer models** (*cont.*)  
 movement models, 2156  
 partial behavior models, 2156–2157  
 project requirements, 2154  
   deliverables of the project, 2155  
   information availability, 2154  
   nature/scope of project, 2155  
   timing/funding, 2155  
 scenario development  
   additional building information, 2155  
   behavior of occupants, 2037  
   building configuration, 2169–2171  
   checklist, 2177  
   coarse network (building configuration approach), 2169–2171  
   continuous network (building configuration approach), 2172–2173  
   example, 2166, 2167  
   fine network grid (building configuration approach), 2171  
   fire information, 2167  
   inclusion of emergency responders/building staff, 2176  
   movement of occupants, 2165  
   number of people, 2174  
   occupant characteristics, 2164  
   occupant route choice, 2166  
   population configuration, 2163–2164  
   pre-evacuation time, 2164–2165  
   procedural configuration, 2166–2167, 2176  
   structure generation/representation, 2162
- Events, sample space**, 2828
- Event trees**  
 fire risk analysis, 2822  
 fire risk assessment, 2822  
 occupant response, 2462  
 performance-based design, 2542  
 releases of flammable material, 2592  
 and selection of design fire scenarios, 1267–1268
- Exhibition Stadium crush (1980)**, 1755
- Exothermic reactions**, 142, 287, 374, 588, 620, 630
- Explicit (forward Euler) method, solving initial value problems**, 1095–1096
- Explosibility limits**, 2768
- Explosion hazard mitigation via water mist**, 1594
- Explosion prevention**, 1307  
 clean agent inerting, 1524
- Explosion protection**  
 blast waves, 2756–2763  
 vapor cloud explosions, 2756–2763  
 Chapman-Jouguet theory, 2751  
 closed vessel deflagrations, 2741  
 computer programs, 1943–1945  
 deflagrations compared, 2692  
 deflagration-to-detonation transition distance, 2754  
 detonation cell width, 2753–2754  
 detonations, 2750–2756  
 dusts/powders  
   explosibility testing, 2766–2768  
   minimum explosible concentration, 2771  
   minimum ignition energy, dust clouds, 2692  
   minimum ignition temperature, dust clouds, 2771  
   minimum ignition temperature, dust layers, 2771  
   particle size, 2771  
   vapors, 2763  
 explosion suppression systems  
   clean agent systems, 1522  
   components, 2818  
   explosion venting compared, 2781  
   suppression sequence, 2566  
   total suppressed pressure, 2784  
 explosion venting  
   standards, high-strength enclosures, 2744  
   standards, low-strength enclosures, 2031  
 test data/correlations, 2242  
 theoretical models, 1992–1994  
   vent area needed, 2781  
 flammability/explosibility limits, 2738  
 gases, 2738  
 inerting, 2784  
 isolation systems, 2788, 2789  
 limiting oxidant concentration, 540, 541  
 pressures, 812  
 secondary explosions, 2812
- Exponential distribution**, 2840–2842, 2844, 2845, 2852–2854, 2880, 2881, 2883, 2885, 2886, 2900–2902, 2907, 2912, 2913, 2929, 2938, 3114  
 reliability analysis and, 2875
- External burning, compartment fires**, 488, 511, 512, 515, 517–519
- Extinguishing agents**. *See* Aqueous film-forming foam (AFFF); Clean agent halon replacements; Fire protection mechanisms; *Foam entries*; Halocarbon extinguishing agents; *Halogenated entries*; *Halon entries*; Inert gas extinguishing agents; *Sprinkler entries*; Water; Water mist fire suppression systems
- Extraneous error**, 2921, 2924
- Extreme value theory**  
 applications, 2210  
 average loss, 2245  
 building collapse example, 2415, 2418  
 extreme order distributions, 2844–2846  
 factors affecting fire damage, 2923  
 fire protection measures, economic value of, 1240, 1459  
 fire severity and fire resistance, 1029  
 fire tests, analysis of, 2412  
 large fire loss behavior, 1252, 1315
- F**
- FAA**. *See* Federal Aviation Administration (FAA)
- Factory Mutual Research Corporation (FMRC)**, 799, 842, 843, 846, 926, 956, 965, 981, 1145, 1157, 1158, 1185, 1186, 1318, 1334, 1496, 1511, 1667, 1681–1686, 1688, 1695. *See also* FM Global
- Factory Mutual Research Corporation Flammability Apparatus**, 956
- Failure mechanism**, 270, 271, 733, 2875, 2878, 2916, 3358
- Failure mode**, 264, 266, 267, 272, 273, 1786, 1815, 1816, 1884, 1893, 1939, 1941, 2793, 2877, 2878, 2945, 2949, 3184, 3256, 3350–3351
- Failure Modes and Effects Analysis (FMEA)**, 2878, 2945, 3183, 3184, 3209, 3388
- FASBUS-II computer program**, 1943
- Fault trees**  
 fire risk analysis, 1269, 2920, 2927, 2932–2935, 2978, 3031, 3341, 3352  
 reliability analysis, 2932–2935  
 risk assessment, 2824  
 system analysis, 2877, 2928, 2960

- F distribution**, 2840
- FDT fire modeling tool**, 3356, 3364
- Federal Aviation Administration (FAA)**, 194, 923, 924, 928–930, 1144, 1452, 1588, 1668, 1669, 1671–1673, 1677, 1679, 2406, 3104, 3371, 3373, 3381–3382
- Federal Railroad Administration (FRA)**, 2817, 2978, 3373, 3374, 3393
- Fiber-reinforced concrete (FRC)**  
compressive strength, 296, 301, 302  
polypropylene fibers, 296, 301, 304  
steel fibers, 296, 1976  
tensile strength, 301, 302
- Fiber-reinforced polymers (FRP)**  
bond with concrete, 311  
critical temperature, 312  
fiber types, 312, 313  
glass transition temperatures, 171, 172, 179, 187, 189, 190, 310, 311, 314, 642  
mechanical properties, 310  
modulus of elasticity, 310  
stress-strain diagram, 311  
thermal properties, 312
- Fibers, construction**, 278, 280, 285, 301–314
- Fick's law of mass diffusion**, 56
- Field models, turbulent flow**, 1609
- Film-forming fluoroprotein (FFFP) foam**, 1647, 1660, 1663, 1665, 1674, 1709
- Finite-differencing technique**, 1046–1048, 1935, 1983
- Fire**  
categories, 1272  
classes, 1024, 1025  
stages  
  decay stage, 997  
  flashover, 997  
  fully developed fire, 997  
  growth stage, 996–997  
  ignition stage, 996  
  tetrahedron of, 1455
- Fire alarms**. *See* Alarms and alarm systems
- Fireballs**  
point source model, 2654  
radiation, 2654  
size/dynamics, 2652–2654  
spherical model, 2654–2655
- FiRECAM integrated computer modeling suite**, 3125–3127  
design fires, 1271, 1277–1278
- Fire consequences, measuring in economic terms**  
certainty monetary equivalent, 3113  
costs/benefits based on level, 3104–3106  
indirect loss estimation  
  costs not usually calculated, 3104  
  NFPA approach, 3099–3101  
  private sector, 3102–3103  
  unpublished U.K. study, 3101–3102  
  U.S. examples, 3103–3104  
insurance industry measurement  
  approaches, 3106  
  risk premium, 3106  
monetary equivalents for  
  nonmonetary costs/consequences  
  deaths/injuries, 3106–3108  
  donated time, 3108–3109  
total national fire cost, 3100, 3101  
utility theory  
  cash equivalent, 3112, 3113  
  expected monetary value, 3110, 3111, 3113, 3115  
  probability distributions, 3114–3115  
  risk averse behavior, 3109, 3111, 3115  
  risk avoider/preferer, 3109, 3111–3113  
  utility/disutility, 3111  
  utility functions, 3112
- Fire Data Management System, calorimetry data**, 975
- Fire Dynamics Simulator (FDS), turbulent fire model**, 397
- Fire extinguishers**. *See also* Aqueous film-forming foam (AFFF); Clean agent halon replacements; Fire protection mechanisms; Foam entries; Halocarbon extinguishing agents; Halogenated entries; Halon entries; Inert gas extinguishing agents; Sprinkler entries; Water; Water mist fire suppression systems  
dry chemical, 687, 1302–1306, 1646, 1648, 1662, 1680, 2899  
portable foam, 1737
- Fire hazard analysis**, 805, 865, 1029, 1058, 2247, 2265, 2318–2321, 2584–2588, 2819, 3184, 3188, 3189, 3191, 3216, 3220, 3224, 3386, 3388.  
*See also* Fire risk entries
- Fire load**  
derated fire load, 1133, 1136  
effective fire load, 1133, 1137  
fire load density, 1131–1141, 1264, 1868, 1989–1992, 2838
- Fire plume(s)**, 399–400  
balcony spill plume, 992, 1092, 1837–1839  
calculation methods, 405–411  
ceiling layer, 134, 451, 1194, 1200, 2746, 2747. *See also* (Compartment fires, two-layer system)  
compartment fire stage, 499, 500, 505, 508–512, 982–983  
diameter of fire source, 416  
entrainment, 414–417  
equivalent confined plume width, 1839  
features, 397–399  
flame height  
  buoyancy and, 400–403  
  momentum and, 403–405  
flame pulsations, 421  
heat release rates, 398  
rise of plume front, 421  
and species product formation, 508–509  
strong, 415, 430, 436–439, 441, 446–447  
strong plume relations, 407  
temperatures, 2838, 2887, 2889  
temperature-stratified ambients, 410–411  
turbulence and, 409, 508, 3291  
velocities, 405–410  
virtual origin, 406, 407, 409, 411–414  
wall/corner effects, 421–422  
weak, 406, 407, 414
- Firepoint**, 555, 565–570
- Fire products**  
enthalpies of, 161–165, 1538, 1540  
nonthermal damage  
  corrosion, 1219  
  smoke, 1219  
toxicity patterns, 2215
- Fire products, generation of**  
concepts governing  
  equivalence ratio and, 1208–1211  
  fire propagation, 1154–1157  
  flame heat flux, 1172–1174  
  flaming/nonflaming fires, 1167–1174  
  heat of gasification, 1168–1172  
  heat release rate, 1181–1182  
  ignition, 1147–1150  
  relation between fire propagation rate, flame height, pyrolysis front, heat release rate, 1157–1159  
generation of chemical compounds/consumption of oxygen

- Fire products, generation of** (*cont.*)  
 efficiencies of oxygen mass consumption and mass generation of products, 1197–1200  
 fire ventilation and, 1200–1201  
 and mass loss rate, 1223–1224  
 reduction/oxidation zones, 1194, 1201, 1205–1208  
 halogenated polymers, 1152, 1154, 1209, 1210  
 heat release rates and  
 chemical heat release rate, 1183–1184  
 CO<sub>2</sub> generation calorimetry, 1183  
 complete/incomplete combustion, 1182–1184, 1186–1187  
 convective heat release rate, 1184  
 energy released in a fire, 1184–1185  
 and fire ventilation, 1191–1193  
 heat release parameter, 1185–1186  
 oxygen consumption calorimetry, 1183–1184  
 radiative heat release rate, 1184  
 nonhalogenated polymers, 1209–1210  
 and nonthermal damage (*see* Fire products, nonthermal damage)
- Fire propagation apparatus**, 926–930, 1144–1146, 1148, 1150, 1159, 1166, 1167, 1170–1173, 1175, 1178, 1181, 1183, 1187, 1189–1192, 1195, 1201, 1212, 1213, 1215, 1216, 1218, 1220, 1224, 2242
- Fire propagation index (FPI)**, 1159–1167, 1216  
 application to classify materials, 1159–1167
- Fire propagation rates**, 1154–1157
- Fire protection engineering**  
 quantitative risk assessment, 3207–3208  
 risk-informed industrial, 3183–3185  
 consequence analysis, 3185–3186  
 evaluation method selection, 3186  
 FPS-LOPA (*see* Fire protection system-layer of protection analysis (FPS-LOPA))  
 hazard evaluation, 3183–3185  
 qualitative risk analysis, 3186–3188  
 treatment of uncertainty  
 combining safety factors, 3004–3005  
 derivation of safety factors, 3005  
 with safety factors, 3002–3003  
 selection of safety factor, 3003–3004
- Fire protection engineering** (*cont.*)  
 uncertainties in  
 behavior variability, 2996–2997  
 and design process, 2998  
 identifying, 2995–2998  
 life-cycle use/safety of buildings, 2998  
 providing for equity/incorporation of social values, 2998  
 scientific, 2995–2296  
 variability in risk perceptions/values, 2997–2998
- Fire Protection Equipment Directory (UL)**, 1660, 1661
- Fire protection mechanisms**  
 active  
 and firepoint theory, 1219–1221, 1224  
 large-scale water extinguishment/suppression tests, 1603, 1667–1673  
 by processes in gas phase, 1222–1223  
 by reduced mass fraction of oxygen, 1223–1224  
 small-scale water tests, 929–930  
 water application rate, 943, 1689, 1713, 1720  
 passive  
 changing molten behavior of materials, 179, 181  
 changing nature of fire products, 1219  
 decreasing thermal response parameter/flame heat flux, 1218–1219  
 increasing critical heat flux/thermal response parameter, 1150–1152, 1216–1217
- Fire protection system-layer of protection analysis (FPS-LOPA)**  
 basics, 3188–3189  
 conduct risk tolerance comparison, 3199  
 definition/steps, 3189–3190  
 determine likelihood of initiating fire event, 3192, 3193  
 enabling event/probability of ignition, 3192–3194  
 human error, 3192, 3193  
 develop accident scenarios, 3190–3191  
 estimate scenario risk, 3198–3199  
 evaluate target vulnerability, 3197–3198  
 example, 3200  
 make decisions on risk reduction, 3204–3206  
 monitor risk, 3206–3207
- Fire protection system-layer of protection analysis (FPS-LOPA)** (*cont.*)  
 quantity performance of independent fire protection layers  
 engineering assessment approach/model, 3195–3196  
 engineering judgment/subjective probabilities, 3197  
 fault tree analysis, 3196–3197  
 reliability data/engineering design assessment, 3195
- Fire protection system selection**  
 desired outcomes, 1294–1295  
 identifying fire fighting agents, 1297–1298  
 insurance company objectives, 1297  
 stakeholders concerns, 1291–1292
- Fire Rated Wood Floor and Wall Assemblies (American Forest & Paper Assn.)**, 2000
- Fire Research Station (U.K.)**, 429, 435, 937, 1035, 2287, 2290, 2392, 2966, 3125
- Fire resistance**  
 building assemblies/frames (*see* Building assemblies and frames, fire resistance)  
 structural analysis and, 1871–1874  
 structural members, 239, 260, 316, 317, 1910–1911  
 test standards  
 ASTM E119, 789–790  
 ISO 834 and EN 1363-1, 789–790
- Fire Resistance Design Manual (Gypsum Assn)**, 1979
- Fire Resistance Directory (UL)**, 1920
- Fire risk analysis**  
 buildings (*see* Buildings, fire risk analysis)  
 computer simulation, 3117–3134  
 health care facilities (*see* Health care facilities, quantitative fire risk analysis)  
 industrial processes, 2952, 3212–3214  
 methods, 2822–2824  
 categories, 2822  
 nuclear power plants (*see* Nuclear power plants, fire risk analysis)  
 process, 2822–2824  
 products (*see* Products (finished), fire risk analysis)  
 resources, 2825–2826  
 terminology, 2819–2822  
 transportation vehicles (*see* Mass transportation)  
 value judgments and, 2818, 2821

- Fire risk assessment**  
and fire scenarios, 2960, 2961, 2964, 2966, 2968–2970, 2973, 2977, 2979  
mass transportation (*see* Mass transportation)  
and software reliability, 2918–2919
- Fire risk estimation**, 2817, 2818, 2979, 2980
- Fire risk indexing**  
computer models, 3178–3179 (*see also specific models*)  
development/evaluation criteria for risk ranking, 3176–3178  
Dow's Fire and Explosion Index  
index calculation, 3163–3165  
risk analysis, 3165  
fire safety evaluation system (*see* Fire safety evaluation system)  
hierarchical approach, 3173, 3175  
application, 3176  
attribute weighting/evaluation, 3175–3176  
insurance rating, 3160–3162  
Mond fire, explosion, and toxicity index, 3165  
risk index  
applications, 3159–3160  
defined, 3158–3159  
significance, 3160
- Fire risk management**, 2818, 2980, 3049, 3370, 3382, 3383
- FIRE-RISK risk-cost model**, 2962, 2963
- Fire safety concepts tree**, 2949–2950, 2980, 3174, 3177
- Fire safety evaluation system**  
derivative applications, 3172–3173  
equivalency concept, 3167  
equivalency evaluations, 3168–3170  
fire safety parameters, 3168  
fire safety redundancies, 3168  
fire zone concept, 3167  
optimization, 3171–3172  
risk, 3167–3168  
supplemental requirements, 3168, 3171
- Fire scenarios**  
characteristics  
building, 1263–1264  
fire, 1268–1269  
occupant, 1266  
clusters, 1269  
consequence analysis  
business interruption, 1276  
damage to building/contents, 1276  
environmental damage, 1276–1277  
injuries/fatalities, 1276
- Fire scenarios** (*cont.*)  
development of  
building characteristics, 1263–1264  
detection/suppression systems, 1265–1266  
fire department actions, 1266  
fuel loads, 1264  
functions in building, 1265  
identification of potential scenarios, 1263, 1266–1267  
occupant actions, 1266  
occupant load/characteristics, 1266  
passive fire protection systems, 1265  
types of combustibles, 1264–1265  
fire risk analysis of finished products, 3212–3215  
functions in building, 1265  
identification, 1266–1267  
performance-based design and, 1262, 1263  
quantifying  
decay phase, 1271–1273  
design fires, 1271–1273  
detection/suppression systems, 1274  
fire department intervention, 1276  
fire/impacts, 1273  
impact on structure, 1274–1275  
occupant response/evacuation, 1275–1276  
postflashover fires, 1273  
preflashover fire growth, 1271–1273  
smoke movement, 1274  
selection of  
event trees, 1268–1269  
examples, 1268  
expected consequences, 1269  
frequency calculation, 1269  
risk ranking, 1269–1270  
scenario selection, 1271  
statistics and historical information, 1269  
smoke management design in large-volume spaces, 1826–1827  
and victim incapacitation  
closed-room fires, 2396–2404  
flaming fires, 2394–2395  
fully developed fires, 2404–2406  
mitigation of toxic hazard, 2406–2407  
room-of-origin deaths, 2396  
smoldering fires, 2392–2394
- Fire SERT Centre (University of Ulster), studies of evacuation capabilities of disabled persons**, 3135
- FIRE SIMULATOR zone fire model**, 1029
- FIRES-RC-II computer program**, 1974
- FIRE STATION simulation model**, 3125
- FIRES-T3 computer program**, 1931–1937
- First Interstate Bank building fire (1988)**, 3103, 3278
- FIRST zone fire model**, 1025
- FIVE fire modeling tool**, 3356, 3364
- Flame(s)**  
adiabatic temperature, calculation, 147–148  
burning velocity, 345, 347, 376, 377, 382, 383, 385, 389, 542, 2636, 2637, 2648, 2738, 2739, 2741–2743, 2746–2748, 2750, 2760  
candle, 350, 351, 354, 366, 1069, 1080  
composition profiles  
distinct regions, 351–354  
diffusion/premixed, 354, 373–377, 379, 386–391, 529–531  
effect of additives on propagation, 2256, 2327, 2385, 2391  
heat flux calculation, 131–133  
premixed burning velocity, 391, 539, 2647
- Flame front**, 239, 352, 356, 384, 386, 387, 390, 529, 587, 708, 711, 785, 1154, 1256, 1467, 1498, 1499, 1533, 1594, 1595, 2553, 2580, 2649, 2664, 2693–2695, 2701, 2738, 2741, 2748, 2758, 2761, 2766, 2769, 2787, 3242, 3245, 3277, 3287, 3289, 3292
- Flame height**  
buoyancy and, 365  
and chemical heat release rate, 398, 1154, 1157, 1158  
effect of wind, 422  
fire plumes, 397, 399  
mean, 397–399, 402–404, 407–409, 412, 413, 415–417, 419  
momentum and, 403–404  
and pyrolysis front, 1154–1158  
wall/corner effects, 421–422
- Flamelets**, 367, 370, 421, 1042, 2596
- Flame radiation scaling technique**, 1173, 1188
- Flame radiation to external target, pool fires**  
atmospheric absorption, 2615–2619  
calculation methods  
examples, 2622–2627  
Mudan method, 2612–2615, 2620, 2624, 2625, 2628

- Flame radiation to external target, pool fires** (*cont.*)  
 point source model, 2601–2605  
 safety factor, 2601, 2603–2605, 2610–2611  
 Shokri and Beyler correlation, 2601  
 Shokri and Beyler detailed method, 2605–2610  
 summary/recommendations, 2620–2628  
 calculation steps, 2600–2601
- Flame retardants**  
 combustion kinetics and, 231  
 effect on thermal decomposition of polymers, 181, 229–231
- Flame spread, liquid fuels**  
 empirical data, 2564–2570  
 liquid/gas phase-controlled, 2559–2561, 2568  
 theory  
 flame spread regimes, 2559–2561  
 pool dimensions, 2561–2562  
 temperature effects, 2562–2563
- Flame spread, surface.** *See* Surface flame spread
- Flame trailing,** 422
- Flaming ignition of solids.** *See* Solids, flaming ignition
- Flammability diagrams,** 538–539, 2687, 2688, 2691  
 stoichiometric limit and, 537, 542, 547
- Flammability limits**  
 combustion outside limits, 530  
 diffusion flames, 545–548  
 dusts/mists, 544–545  
 effect of temperature/pressure, 532  
 explosibility limits compared, 2766–2768, 2771, 2774  
 ignition energies and, 544  
 ignition of liquids and, 554, 555, 559–565, 567–568, 570, 573  
 and ignition of solids, 647  
 limiting oxygen concentration (LOC) and, 539–540, 548  
 lower (LFL)  
 adiabatic flame temperature, 536–538, 542, 547, 551  
 predicting, 531–532  
 premixed flames, 529–531  
 quenching diameters, 544  
 upper (UFL), 529, 533–536  
 vertical tube measuring apparatus, 529, 530
- Flaring,** 2629, 2630, 2644
- Flashover**  
 electrical, 673–674  
 predicting in compartment fires, 512–519, 1002
- Flashpoint**  
 closed cup, 554, 555, 562, 564–570, 576, 1467, 2562, 2564–2569, 2587  
 effect of atmospheric pressure on, 564–565  
 and ignition of solid fuels, 650–651  
 measurement of, 565  
 open cup, 567–570  
 spills and, 558, 574
- Floor coverings, heat release rates,** 816–818
- Floors**  
 composite (concrete/steel)  
 concrete-filled steel sections, 1917–1919  
 heat transfer/temperature profiles, 1927–1936  
 concrete slab, 273, 1935, 3277  
 hollow-core, 1959, 1960, 1976, 1977  
 fire resistance, 3255
- Fluent CFD model,** 956, 1032, 1035, 1037, 1044, 1045, 1050, 1056, 1061, 1066, 1252, 1605, 1610, 1611, 1817, 3234
- Fluid element,** 77, 1380, 1383
- Fluid motion, dynamics of**  
 Bernoulli equation, 21–22  
 boundary layers (*see* Boundary layers, fluid flow)  
 dimensional analysis, 1383, 1401, 1869  
 energy conservation equation, 1040, 1047  
 flow in ducts (*see* Ducts, fluid flow in)  
 flow in pipes (*see* Pipes, fluid flow in)  
 Navier-Stokes equations, 1035, 1037, 1040  
 turbulence, 1037
- Fluid motion, kinematics of**  
 assumptions, 356  
 circulation, 1434, 1919, 2034, 2035, 2053, 2063, 2157, 2566  
 classification  
 steady/unsteady, 5, 6, 11, 12, 1401  
 turbulent, 12–21  
 equation of continuity, 1383  
 Eulerian method of describing, 1610, 1611  
 flow concepts  
 pathline, 1382, 1383, 1385, 1518, 1570  
 stream filament, 4, 21, 22, 81, 83, 987  
 stream function, 68, 73
- Fluid motion, kinematics of** (*cont.*)  
 streamline, 4, 21, 22, 1383, 1386  
 streamtubes, 4  
 flow in a channel, 445  
 flow similarity, 68, 73, 74  
 Lagrangian method of describing, 1610, 2686  
 rotational/irrotational, 1382  
 velocity potential, 56, 57, 59, 81, 87, 99
- Fluids.** *See also* Liquids  
 buoyancy, 9–10  
 compressibility, 1407  
 defined, 1  
 incompressible, dynamics of, 5, 6, 14, 66, 1386, 1401, 1517  
 properties  
 density, 1  
 physical, 1378  
 pressure, 3, 1379–1380  
 shear force, 54, 60  
 shear stress, 1, 2, 6, 7, 9, 17, 54, 55, 58, 60, 61  
 specific gravity, 1379  
 specific volume, 1, 375, 1512, 1562, 1563, 2802  
 specific weight, 1378–1379, 1381, 1383, 1418  
 surface tension, 572, 719, 720, 1299  
 thermal expansion, 72, 78, 189, 267, 271–274, 284  
 vapor pressure, 558–565  
 viscosity, 1–2  
 specific heat, 2  
 statics, 1380
- Fluid systems**  
 body force, 60–62, 64, 71  
 floating/submerged bodies, 429, 431, 441, 443, 447, 449, 451, 1382, 1825, 1839  
 forces on submerged surfaces  
 buoyant force, 431, 432, 449, 450  
 plane-inclined and curved, 439–440, 2582, 3258, 3259  
 hydrostatic equation, 458  
 pressure at a point, 3  
 statics and buoyancy, 9–10  
 surface force, 60, 63, 64
- Fluoroprotein foam,** 1647, 1664, 1669, 1671, 1673, 1697, 1713, 1715, 1720, 1722, 1727, 2554
- FM fire products collector,** 937
- FM Global,** 646, 915, 921, 926, 943, 1035, 1144, 1146, 1160, 1162, 1165, 1166, 1168, 1170, 1425, 1445, 1446, 1593, 1594, 1613, 1614, 1621, 2781, 2785. *See also* Factory Mutual Research Corporation (FMRC)



- FMRC.** *See* Factory Mutual Research Corporation (FMRC)
- FMRC corner test,** 842, 843, 846, 847
- Foam(s)**
- aspiration
    - air-aspirated, 1665
    - non-air-aspirated, 1665, 1674, 1675
  - assessment of extinguishing/ burnback performance
    - comparison of small-scale tests, 1665, 1667
    - critical application rates/ correlation between small-/ large-scale tests, 1667–1673
  - EN, 1663–1665, 1667, 1674
  - ICAO *Airport Services Guide*, 1663
  - MIL-F-24385 specification, 1661–1662
  - standard test methods, 1659–1667
  - UL Standard, 1661, 1665, 1667
  - aviation fire protection
    - agent quantities/standards, 1673–1674
    - expansion and drainage, 1674–1675
    - foam concentration, 1675–1679
    - hangar protection (*see* Aircraft hangars)
    - nozzle design, 1680–1688
    - underlying principle, 1673
    - video image flame detection, 1689
  - Class A, 1330, 1737–1739
  - composite constituents, 1647
  - concentration determination
    - conductivity method, 1677–1679
    - refractive index method, 1677
  - depletion rate, 1650
  - design considerations
    - extinguishment and spreading theory, 1648
    - extinguishment modeling, 1656–1657
    - foam loss mechanisms, 1649–1653
    - spread over liquid fuels, 1653–1656
    - surface tension and spreading coefficient, 1657–1659
  - discharge device classifications, 1660, 1661
  - drainage, 1647–1653, 1657, 1662, 1663, 1674–1675, 1687, 1688
  - evaporation rate, 1649–1651
  - foam-water sprinkler systems (*see* Foam-water sprinkler systems)
  - high-expansion type
    - mass loss, 1649, 1652
    - warehouse protection calculations, 1646, 1688–1690
- Foam agents**
- AFFF (*see* Aqueous film-forming foam (AFFF))
  - environmental concerns, 1695–1697
  - film-forming fluoroprotein (FFFP)
    - foam, 1647, 1660, 1663, 1665, 1709
  - fluoroprotein foam, 1664, 1669, 1673, 1713, 1715, 1720, 1722, 1727, 2554
  - protein foam, 1647, 1656, 1665, 1668, 1669, 1673, 1681, 1682
- Foam systems**
- hazards/fires suitable for protection with, 1692, 1695
  - high-expansion foams, 1646, 1688, 1729–1737
  - incipient spill protection, 1709
  - objectives for evaluating protection with, 1707–1708
  - protection limitations, 1736–1737
  - for roof storage tanks, 1725–1728
  - storage tank protection, fixed roof
    - discharge outlets, 1710–1711
    - foam handlines, 1710
    - foam monitors, 1710
    - portable foam towers, 1709
    - semisubsurface injection of foam, 1725
    - subsurface application of foam, 1718
    - surface application of foam, 1710–1711
  - storage tank protection, floating roof
    - catenary system method, 1725
    - fixed foam maker, 1725–1726
    - portable nozzle method, 1725
  - storage tank protection, high-expansion foam, 1728
  - storage tank protection, low-expansion foam
    - fixed system calculations, 1711–1716
    - subsurface application calculations, 1718–1723
  - types
    - fixed, 1708
    - mobile, 1709
    - portable, 1709
    - semifixed, 1708–1709
- Foam-water sprinkler systems**
- codes/standards/regulations, 1689–1690
  - protection of stored flammable/combustible liquids, 1691
  - drum/tank storage, 1691–1693
  - liquid spill and container storage, 1693–1695
- Fog, defined,** 1587, 2185
- Foodstuffs, heat release rates,** 834, 836
- Forest fires.** *See* Wildland fires
- Forest Products Laboratory (FPL),** 911, 924–925
- Formaldehyde (CH<sub>2</sub>O),** 1205, 1207
- generated in pyrolysis of wood, 1206
- Forward Euler method, solving initial value problems,** 1095–1096
- FOSM (first-order second-moment) method, safety factor derivation,** 3005
- Fourier's law, heat conduction and,** 55
- steady-state examples, 55
- FPETOOL computer program,** 1029, 3360
- Frames.** *See* Building assemblies and frames, fire resistance
- FRAME works risk assessment model,** 2966, 2967
- Frank-Kamenetskii theory, autoignition**
- and Biot number, 606, 618, 622
  - experimental testing methods, 618, 619
  - and parallel reactions, 620–621
- Free-burning fires,** 486, 1000
- FREM fire risk evaluation model,** 3179
- FRIM-MAB risk index method,** 2967–2968
- Froude modeling,** 708, 1827, 1828, 2594
- Froude number,** 10–12, 365, 366, 399, 400, 403, 463, 468–470, 1051, 1052, 1603, 1827, 2596, 2597, 2632, 2636, 2650, 2684
- FSSIM zone fire model,** 1029
- Fuels, properties/combustion data,** 3437–3475
- Furniture.** *See* Upholstered furniture
- Furniture calorimeter,** 800, 844, 847, 852, 854, 885, 890, 932–934, 942–943, 946, 1337
- Furniture calorimeter tests,** 852, 932–933, 1331
- G**
- Gamma distribution,** 2842–2843, 2850, 2854, 2868, 2869
- Gas(es)**
- compressibility, 556, 557, 695, 697, 1484, 1536, 1573, 1612, 1620, 1623, 1624, 1626, 1634–1636, 2665, 2738, 2742, 2743, 2747, 2756, 2759, 2792, 2795, 2805

**Gas(es)** (*cont.*)

- explosion protection, 2751, 2752, 2811
- gray, 124, 750, 777, 941, 958, 1042
- ideal, 1, 3–4, 8, 56, 62, 64, 78, 138–140, 142, 146, 154, 155, 159, 329, 330, 335, 345, 352, 406, 459, 474, 494, 556, 558, 562, 697, 698, 983, 985, 993, 1073–1075, 1085, 1089, 1093, 1100, 1505, 1508, 1605, 1798, 1833, 1844, 1853, 2739, 2745, 2801, 3400
- ignition by arcing, 670, 2692
- molecular weights, 140, 390, 459, 460, 489, 556, 983, 1036, 1168, 1215, 2678, 2694, 2744, 2748, 2756
- nonscattering, 1042
- perfect, 402, 988, 1036, 1037
- properties, 56, 126, 127, 359, 371, 727, 1168, 1507, 1833, 2638, 2646, 2665, 2666, 2672, 2678, 2689, 2739, 3425
- vapor distinguished, 2665
- work done during expansion, 139, 140
- GASEQ computer program**, 165, 2740, 2751
- Gasoline**
  - enclosure fire example, 1084
  - pool fire emissive power, 2599
- Gas temperature rise calorimetry**, 1144, 1146, 1149, 1184
- Gaussian distribution.** *See* Normal distribution
- Gels, amorphous material**, 278
- General Services Administration**, 1235, 1778, 2043, 3223
- Geometric distribution**, 2848
- Geometric mean**, 125, 126, 730, 742, 2856
- Gibson (Calif.) Amtrak sleeping car fire (1982)**, 3374
- Glass**
  - amorphous material, 171, 179, 278
  - fire screen, 97
- Glass transition, phase change**, 314, 642
- Glass transition temperature, polymers**, 171, 172, 179, 310, 311
- Grashof number**, 11, 72, 81, 89, 93, 94, 100, 470, 484
- Gray body radiation**, 958
- Great Hanshin (Japan) earthquake and fires (1995)**, 717
- Gretner method, insurance rating**, 3161

**Guidelines for Evaluating the Characteristics of Vapor Cloud Explosions, Flash Fires, and BLEVEs (AIChE Center for Chemical Process Safety)**, 2745, 2758

- Gypsum wallboard**
  - coefficient of thermal expansion, 314
  - dilatometric/thermogravimetric curves, 316
  - protection of steel members, 1916
  - specific heat, 315
  - thermal conductivity, 315
  - thermal properties, 314
  - types, 314

**H**

- Haber's rule, toxicity**, 2216, 2235, 2245, 2300, 2330, 2332, 2359, 2368
- Hagerbach tunnel research facility (Switzerland)**, 3321
- Halocarbon extinguishing agents.** *See also* Clean agent halon replacements
  - characteristics, 1301, 1302, 1450–1451, 1483, 1484
  - environmental concerns
    - global warming potential, 1301, 1503–1504
    - ozone depletion, 1301, 1502–1503
  - extinguishing mechanisms, 1301, 1485–1486
  - minimum extinguishing concentration, 1302, 1486–1498
  - thermophysical properties, 1505–1507
  - toxicity, 1302, 1499–1501
- Halogenated agent extinguishing systems**
  - agent delivery, 1462–1463
  - agent requirements
    - agent quantity, 1468–1469
    - application rate, 1469
    - compensation for leakage, 1470–1472
    - discharge time/soaking period, 1469
    - effects of ventilation, 1469–1470
    - liquid/gas fires, 1466–1468
    - solid fuels, 1465–1467
  - configurations, 1460
  - control panels
    - economics, 1461–1462
    - features, 1460–1461
    - modes of operation, 1461
- Halogenated agent extinguishing systems** (*cont.*)
  - design guidelines, 1463–1464
  - detection, 1460
  - flow calculations
    - guidelines/limitations, 1474
    - pipng theory and, 1471–1474
    - procedure, 1474–1479
  - halon zone, 1463
  - local application, 1464–1465
  - postdesign considerations, 1479–1480
  - total flooding, 1465–1471
- Halogenated agents.** *See also* specific agents
  - computer room protection, 1459
  - environmental issues, 1480–1481
  - halogens found in, 1451
  - history of use, 1451–1453
  - physical properties, 1454–1455
  - toxicity, 1457–1459
- Halogenated polymers, calculating combustion yields**, 1209
- Halon 122**, 1451
- Halon 1011**, 1451, 1452
- Halon 1211**, 1301, 1451–1454, 1456, 1458, 1464, 1673
- Halon 1301**
  - agent requirements
    - agent quantity, 1468–1469
    - application rate, 1469
    - compensation for leakage, 1470–1472
    - discharge time/soaking period, 1469
    - effects of ventilation, 1469–1470
    - liquid/gas fires, 1466–1468
    - solid fuels, 1465–1467
  - attributes/limitations, 1453–1454
  - combustion kinetics, 328
  - corrosive effects, 1456–1457
  - decomposition products, 1457–1458
  - design concentration, 1466–1468
  - environmental issues, 1480–1481
  - extinguishing effectiveness, 1456
  - physical properties, 1454–1455
  - protection of electronic data
    - processing equipment, 1453
  - total flooding systems, 1465–1471
  - toxicity, 1457–1459
  - water mist fire suppression systems
    - as replacement for, 1601–1602
- Halon 2402**, 1451–1453
- Halons.** *See* Halogenated agents
- Handbook of Military Infrared Technology (Office of Natl. Research)**, 2660

- Handicapped/impaired persons**  
 alarm systems and, 2524  
 areas of refuge, 2023  
 buddy system, 2023, 2524  
 evacuation response, 2023, 2524, 2525  
 prevalence, 2524  
 and signage, 2524  
 wheelchair users, 2524
- Handrails, and effective evacuation width**, 2122–2124, 2132
- Harmonic mean**, 2856
- Harvard code**, 3217
- Harvard/NIST Mark VI zone model**, 987
- Harvard V5 program**, 1028
- Hazard(s)**  
 defined, 572  
 thermal/nonthermal, 2593, 2597–2600
- Hazard evaluation**, 1601, 2268, 2774, 3183–3186, 3191, 3201, 3205, 3208
- HAZARD I integrated computer modeling suite**, 3125–3127
- Health care facilities**  
 fire risk indexing model, 3158, 3159, 3178–3179  
 occupant response to fire/smoke, 2968, 2981  
 handicapped/impaired persons, 2039, 2056, 2316, 2320, 2412
- Health care facilities, quantitative fire risk analysis**  
 assumptions/limitations, 3227–3228  
 available escape time, 3232–3234  
 door open/closed, 3234  
 calculation of consequences, 3236  
 detection time, 3234, 3235  
 event tree, 3232, 3233  
 extended procedure, 3226, 3239  
 facility conditions, 3228–3229  
 fire frequency, 3230–3231  
 fire growth, 3231–3232  
 individual risk, 3237–3238  
 model uncertainty, 3235  
 movement time, 3235  
 occupants, 2021, 2031, 2038, 2104, 2343, 2445, 2448, 2458, 3166, 3167  
 patients/staff, 3229–3230  
 societal risk, 3236–3237
- Hearing-impaired persons, alarm systems and**, 1746, 1747, 2031, 2039
- Heat capacity**. *See* Specific heat
- Heat detectors**  
 ceiling jet flows and, 429, 430  
 error sources, 1321  
 fixed-temperature, 727, 1322
- Heat detectors (cont.)**  
 rate-compensated, 1322  
 rate-of-rise, 727, 1322  
 response time index (RTI), 1321  
 spacing, 1319
- Heat, exposure of fire victims to**  
 convected heat, 1070, 2316, 2375, 2377–2378  
 damage to respiratory tract, 2316, 2373, 2380–2381, 2418  
 heat stroke (hyperthermia), 2373–2376, 2417  
 predicting time to incapacitation, 2371–2374  
 skin burns, 2373, 2376–2377
- Heat flux**  
 to adjacent surfaces, 746  
 boundary conditions, 43, 44  
 burning parallel vertical surfaces, 782–785  
 ceiling fires, 780–783  
 corner wall fires, 774–780  
 critical, 211, 239, 586, 588, 978, 1147, 1149, 1150, 1166, 1216, 1217, 2656, 2722, 2724, 3243, 3451  
 effect of other variables, 793  
 exposure fires  
 adjacent to flat walls, 750–751  
 beneath I-beams, 765–769  
 beneath unconfined ceilings, 759–761  
 corner fires, 751–756  
 in corridors, 761–765  
 effects of fire standoff distance, 757–759  
 room environment effects, 756–757  
 and flame spread, 789  
 heat release rates and, 750, 753, 757, 758, 764, 765, 771, 773–778, 780, 783, 787, 788  
 near ignition source, 211, 239, 655, 807  
 objects immersed in flames, 749–750  
 postflashover room fires, 808  
 preflashover room fires, 807  
 standard tests  
 ASTM E84 tunnel test, 789, 791–792  
 fire resistance, 789  
 wall fires, 669–774, 807–808  
 from windows, 787–789
- Heat generation**. *See* Fire products, generation of
- Heating equipment, database coding categories**, 3089–3090
- HEATING7 program**, 1934
- Heat of combustion**  
 ambient/elevated temperatures, 142  
 defined, 141–142  
 effective, 238, 582, 799, 800, 837, 860, 866, 889, 908, 940, 952, 975, 976, 978, 999, 1001, 1002, 1021, 1041, 1185, 2242, 2269, 3074  
 measurement, 141–144  
 net/gross, 142  
 selected fuels, 142, 143
- Heat of formation**, 144–145, 150, 287, 1182, 1374
- Heat Release in Fires (Babrauskas and Grayson, eds.)**, 814
- Heat release rates (HRRs)**  
 bench scale measurement  
 modeling with data from, 805–808  
 predicting, 809–813  
 burning foam sofa, 442–444  
 bushes, 861–863  
 ceiling jet flows, 449–451  
 chemical heat release rate (*see* Chemical heat release rate)  
 Christmas trees, 859–861  
 compartment fires, 101, 997, 1005, 1009  
 computer equipment, 821–828  
 convective (*see* Convective heat release rate)  
 dependence on heat flux, 808–810  
 estimating for general combustibles, 895  
 fire plumes, 828  
 fires, 799–809, 811, 812, 814, 816, 818, 828–831, 833, 837, 839, 841, 842, 847, 848, 850, 852–855, 857, 860, 863, 865–867, 869, 872, 874–876, 879, 881–885, 887–892, 894, 896  
 and generation of fire products, 814, 866  
 intermediate scale measurement  
 effect of ignition source on full-scale HRR, 804  
 using full-scale HRR data, 802–803  
 mattresses, 848–853  
 measurement techniques  
 compensation method, 911  
 open-burning calorimeters, 799–800  
 oxygen consumption method, 911–915  
 room fire tests, 800–801  
 sensible enthalpy method, 907–910  
 substitution method, 910–911  
 motor vehicles, 873, 943

- Heat release rates (HRRs)** (*cont.*)  
 predicting full-scale HRR from bench-scale data  
 boundary conditions, 806  
 effect of orientation, 811–812  
 effect of thickness, 809–811  
 other variables, 812–813  
 overview, 805–806  
 role of irradiance, 806–808  
 radiative, 864–867  
 for real products, 813–821  
 uncertainty of measurements, 895–896, 943–945  
 vehicle tires, 879, 882, 1686
- Heat stroke**, 2300, 2373–2376, 2381, 2417
- Helium (He), specific heat**, 141
- Heptane, pool fire velocities/temperatures**, 361, 399, 401, 408, 432, 934, 1514, 1739, 2597, 2598
- Herald of Free Enterprise ferry capsizes (1987)**, 3377–3378
- Hess's law**, 144
- Heun's method, solving initial value problems**, 1096
- Highly Flammable Liquids and Liquefied Petroleum Gases Regulations (U.K.)**, 570, 571
- High-rise evacuations**, 1743
- High-strength concrete (HSC)**  
 compressive strength, 1976  
 porosity, 303–304  
 spalling, 289–290, 304
- Hillhaven Nursing Home fire (1989)**, 3231
- Hinsdale (Ill.) telephone exchange fire (1988)**, 3104
- Histogram**, 2373, 2374, 2384, 2385, 2850–2853, 2866–2868, 2873, 3068, 3069, 3133
- Historic structures**  
 CFD smoke movement application, 1055, 1274  
 Historic Fire Risk Index, 3172
- Hooke's law, stress/strain**, 189, 264, 265, 268, 274
- Horizontal-surface fires, flame height**, 398
- Hotel fires, occupant response**, 2085–2087, 2097, 2449, 3080, 3103, 3217, 3266
- HRR**. *See* Heat release rates (HRRs)
- Human action**, 2876, 2877, 2919, 2920, 2927, 2928, 2946
- Human error**, 2919–2925, 2928, 2932, 2947, 3087, 3189, 3191, 3192, 3208, 3280, 3326, 3329, 3351, 3352
- Human error probability (HEP)**, 2920, 2927, 3192, 3352
- Human factors**, 2920, 2997
- Human failure event (HFE)**, 2921, 3352
- Human reliability analysis**. *See* Reliability analysis, human
- Hydrants, discharge at opening**, 1405–1407, 1414
- Hydraulic model, egress performance**  
 calculating escape time  
 basic variables, 2133, 2137–2139  
 factors influencing evacuation, 2119, 2137  
 movement attributes of evacuees, 2138–2139  
 routes available, 2138  
 time taken to respond, 2139  
 use of available routes, 2138  
 establishing egress performance  
 model approaches, 2118–2119  
 model limitations, 2119–2120  
 estimating evacuation time  
 calculated flow, 2128  
 consideration of door mechanism, 2126–2128  
 effective width, 2122–2124  
 effect of stairs, 2123, 2134  
 example, 2132–2137  
 fundamental movement  
 calculations, 2121–2132  
 intrusion of handrails, 2122, 2124  
 population density, 2122–2124  
 specific flow, 2126–2128  
 speed, 2124–2126  
 time for passage, 2128  
 transitions, 2128–2132  
 first-order hydraulic model, 2132, 2133  
 high-density scenario, 2140  
 impact of tenability on ASET/RSET, 2145–2148  
 including effects of smoke, 2147, 2148  
 low-density scenario, 2140  
 modeling error, 2142–2143  
 required safe egress time, 2115, 2116, 2121, 2137, 2139, 2141–2143, 2145–2148  
 safety margin, 2143  
 second-order hydraulic model, 2132, 2133  
 use with other models, 2143–2146
- Hydraulics**  
 conservation laws in fluid flows, 1382–1385  
 energy losses in pipe flows  
 boundary layer concept, 1385, 1386
- Hydraulics** (*cont.*)  
 compound networks, 1400–1401  
 critical zone, 1388–1389  
 equations, 1387–1389, 1392, 1394  
 Hazen-Williams-based data, 1391–1395  
 laminar/turbulent, 1386–1387  
 minor losses, 1395–1399  
 pipes in parallel, 1399–1400  
 pipes in series, 1399  
 flow measurement  
 ASME flow nozzle, 1402–1403  
 ASME orifice meters, 1402–1404  
 free discharge at opening, 1405–1407  
 pitot tube, 1401–405  
 Venturi flow meter, 1402  
 fluid statics  
 force on submerged plane areas, 1382  
 gauge/absolute pressure, 1380, 1382, 1384  
 pressure measuring devices, 1380–1382  
 properties of fluids, 1378–1380  
 static pressure head, 1380  
 pumps  
 centrifugal pump affinity relations, 1420–1422  
 operating characteristics, 1416–1419  
 selection, 1419–1420  
 water hammer, 1407–1409
- Hydrocarbon fires, thermal radiation**  
 event tree, 2591–2593  
 hazards to personnel, 2655–2658  
 pool fires  
 emissive radiation, 2598–2600  
 flame height/length, 2594–2595  
 flame tilt angle, 2595–2596  
 geometry, 2593–2594  
 hazards, 2597, 2599, 2600  
 radiation to external target (*see* Flame radiation to external target, pool fires)  
 targets within the fire, 2628–2629  
 trench/line fires, 2596, 2597  
 wind effects, 2594  
 turbulent jet flames  
 aerodynamic effects, 2591, 2630, 2636–2638  
 fire impingement exposure, 2645–2646  
 flame diameter, crosswind, 2636–2638  
 flame geometry, 2630  
 flame height/length, crosswind, 2633–2636  
 flame height, still air, 2630–2633

- Hydrocarbon fires, thermal radiation** (*cont.*)  
 hazards, 2638–2640  
 line/cylinder models, 2644–2645  
 point source model, 2638–2640  
 radiative fraction, 2640–2644  
 unsteady thermal radiation analysis  
 burning vapor clouds (*see* Vapor clouds)  
 fireballs (*see* Fireballs)  
 pressurized gas incidents, 2646
- Hydrocarbons**  
 aliphatic/aromatic, 1211  
 fire ventilation and yields, 1201, 1204
- Hydrogen**  
 dissociation example, 159  
 heat of formation (atomic), 145
- Hydrogen bromide (HBr), as inert diluent**, 1458
- Hydrogen chloride gas (HCl)**  
 corrosivity, 732  
 heat of formation, 145  
 as inert diluent, 542
- Hydrogen cyanide (HCN)**  
 fire yield, 2231, 2287, 2346  
 generation efficiency, 1205, 1206  
 heat of formation, 145  
 toxicity  
   fractional incapacitating dose (FID), 2373, 2417  
   interaction with carbon dioxide, 2369  
   interaction with carbon monoxide, 2369–2370
- Hydrostatic equation**, 9–10
- Hydroxyl (OH), heat of formation**, 145
- Hypergeometric distribution**, 848–849
- Hyperthermia**, 2300, 2374–2376, 2418
- Hyperventilation, and incapacitation from toxic effects**, 2366–2368
- Hypothesis testing**, 2861–2870
- Hypoxia**  
 and carbon dioxide, 2369  
 carbon monoxide and, 2370
- I**
- ICAO**. *See* International Civil Aviation Organization (ICAO)
- ICC Performance Coder® for Buildings and Facilities (International Code Council)**, 1235, 1238, 1242, 2022, 2035, 2041
- Ideal gas(es)**  
 constant, 139, 556, 558  
 law, 1, 3–4, 138, 142, 155, 159, 329, 330, 335, 406, 459, 474, 475, 556, 1073, 1085, 1798, 1843, 1844
- Ignition**  
 autoignition (*see* Autoignition)  
 defined, 554–555  
 of liquids, 554–578, 635, 670, 1256, 3439, 3451  
 modes involving electric current (*see* Electrical fires, ignition modes involving electric current)  
 piloted, 389, 572, 649–650, 653, 707, 714, 920, 921, 1147, 1149, 1150, 1258, 3244, 3312  
 secondary/remote, 151, 1272, 2592, 3219, 3312  
 self-ignition (*see* Autoignition)  
 solids, flaming ignition in (*see* Solids, flaming ignition)  
 spontaneous combustion (*see* Autoignition)  
 thermal radiation and, 572  
 and values of voltage/current/power, 693–694
- Ignition Handbook (Babrauskas)**, 607, 665, 667, 668, 670–673, 676, 678, 680, 681, 683, 686, 694, 807, 955, 3194
- Ignition source, defining**, 892, 2570, 2691
- Ignition zone**, 1144, 1154, 1158, 1159, 1216
- IMO**. *See* International Maritime Organization (IMO)
- Implementation time**, 2922
- Incapacitation**  
 fire scenarios and  
   closed-room fires, 2396–2401  
   flaming fires, 2394–2395  
   fully developed fires, 2404–2406  
   mitigation of toxic hazard, 2406–2407  
   room-of-origin deaths, 2396  
   smoldering fires, 2392–2394  
 heat exposure  
   predicting time to incapacitation, 2353, 2361, 2371–2373, 2387  
 from toxic effects  
   carbon dioxide, 2218, 2220  
   carbon monoxide, 2218  
   hydrogen cyanide, 2222, 2224  
   hyperventilation and, 2220, 2223  
   hypoxia, 2220, 2221  
   predicting, 2215, 2219, 2220, 2225
- Incompressible fluid motion**, 5, 6, 14, 66, 483, 1386, 1401, 1517, 1624
- Independent fire protection layers**, 3188–3190, 3194–3197, 3200, 3202–3203, 3208, 3209
- Indexing, fire risk analysis method**, 2825, 2981
- Industrial fire protection**  
 consequence analysis, 3185–3186  
 fire risk evaluation, 3186  
 FPS-LOPA, 3188–3207  
 hazard evaluation, 3183–3185
- Inert gas extinguishing agents**  
 characteristics, 1483–1485  
 extinguishing mechanisms, 1485–1486  
 minimum extinguishing concentration, 1492–1494  
 thermophysical properties, 1505  
 toxicity, 1499–1502
- Influence diagram, fire risk analysis**, 2824
- Information technology (IT) equipment, flammability concerns**, 1291, 1453
- Institute for Operations Research and the Management Sciences (InFORMS)**, 2826
- Insulation**  
 thermal conductivity, 35, 1932  
 thermal properties, 1105
- Insurance rating, fire risk indexing**  
 class/schedule rates, 3160  
 Gretener method, 3161–3162  
 mercantile/Dean schedules, 3161  
 Specific Commercial Property Evaluation Schedule, 3161
- Integral method, heat transfer analysis**, 75, 77
- Interior finish wall/ceiling materials, fire propagation index**, 1165–1167
- Intermediate-scale calorimeter (ICAL)**, 802, 803, 813, 896, 921, 931–932, 942, 3043
- International Building Code (ICC)**, 1304, 1742, 1753, 1776, 1808, 1819, 2000, 2027, 2030, 2042, 3172, 3254
- International Civil Aviation Organization (ICAO)**, 1663
- International Convention for the Safety of Life at Sea (SOLAS)**, 935, 1535, 1547, 1556, 1561–1566, 1614, 3377, 3379
- International Electrotechnical Commission (IEC)**, 235–237, 2269, 2270, 2284, 2772



- International Fire Engineering Guidelines (ICC)**, 1138, 1262
- International Foam-Water Sprinkler Research Project**, 1694, 1695
- International Maritime Organization (IMO)**, 621, 935, 956, 1535, 1588, 1589, 1613, 1614, 3377
- International Organization for Standardization (ISO)**. *See ISO entries*
- Interquartile range**, 2856
- Intumescent coatings**, 974, 1871, 3319, 3453, 3454
- Inviscid fluid**, 16, 65, 84, 992
- Ionization**, 194, 663, 695, 727, 1195, 1318, 1344, 1345, 1347–1349, 1353, 1356, 1460, 2398, 2401, 2402, 2692
- ISO (International Organization for Standardization)**. *See ISO entries*
- Iso-butane, heat of formation**, 130, 145
- ISO 834, Fire-Resistance Tests-Elements of Building Construction**, 789, 1102, 1105, 1116–1118, 1122, 1124–1129, 1866, 1928, 1949, 1956, 1988  
time-temperature curves, 789, 1935
- ISO 5657, Fire Tests-Reaction to Fire-Ignitability of Building Products**, 235, 958, 959, 964, 976
- ISO 14520, Gaseous Fire Extinguishing Systems-Physical Properties and System Design**, 1486, 1494–1496, 1498, 1509–1511, 1527
- ISO Technical Specification 16733, Fire Safety Engineering-Selection of Design Fire Scenarios and Design Fires**, 1263, 1266, 1269, 2048, 2056, 2057, 2060, 2067
- ISO Technical Specification 16732, Guidance on Fire Risk Assessment**, 2826
- Isotropic materials**, 28, 278
- IT equipment**. *See* Information technology (IT) equipment, flammability concerns
- J**
- JASMINE CFD model**, 1035, 1048, 1609
- Jet flames**  
flame height, 403  
horizontal discharge, 396, 422–423  
virtual origin, 413
- JET two-zone fire model**, 2566
- JP-5, flame spread rate**, 1669, 1683, 1687, 2564, 2566, 2567, 2569, 2582
- JP-8, flame spread rate**, 1687, 2564, 2566, 2567, 2569, 2582
- Judgment sample**, 2871
- K**
- Kinematic viscosity**, 2, 17, 18, 56, 351, 416, 438, 1321, 1375, 1379, 1393, 1655, 2750, 3398
- Kings Crossing fire (1987)**, 706, 1056, 2406
- Kiosks, heat release rates**, 846–847
- Kirchoff's law**, 119–120
- Kurtosis, probability distributions**, 2834
- L**
- Large eddy simulation approach**. *See* Computational fluid dynamics (CFD) models, turbulence modeling, large eddy simulation
- Large-volume spaces, smoke management in**  
approaches to  
analytical approach, 1827  
factors affecting, 1832  
scale models, 1827–1828  
comparison of mechanical exhaust/natural venting designs, 1842–1851  
computational fluid dynamics models, 1867–1868  
draft curtains, 1843, 1844, 1849–1852  
fire scenarios, 1824, 1827, 1829, 1831, 1843  
hazard parameters  
light obscuration, 1825–1826  
smoke layer interface position, 1825  
temperature/gas species concentration, 1826  
limited fuel, 1857  
mechanical venting systems, 1842–1843  
design aspects, 1842–1843  
natural venting systems  
design aspects, 1843–1847  
flow through vents, 1843, 1844, 1847  
limitations, 1845–1847  
makeup air supply, 1844–1845  
smoke buoyancy and, 1843, 1844  
wind conditions and, 1846, 1847  
opposed airflow, 1857–1858
- Large-volume spaces, smoke management in (cont.)**  
smoke filling period  
empirical correlations, 1831–1833  
smoke layer interface position, 1830–1831  
steady fires, 1829–1830  
t<sup>2</sup> fires, 1829, 1830, 1832  
theoretically based approach, 1833–1834  
transport lag, 1829–1830  
special conditions  
confined flow, 1852  
intermediate stratification, 1852–1854  
makeup air supply, 1856  
plugholing, 1855–1856  
sprinkler/vent systems  
computer simulations, 1850–1851  
consensus approach to design, 1851–1852  
design considerations, 1849  
interaction of spray and smoke layer, 1849–1850  
past studies, 1848–1849  
sprinkler skipping, 1851  
vent skipping, 1851  
thermal activation of vents, 1847–1848  
vented period  
axisymmetric plume, 1834–1836  
balcony spill plume, 1837–1839  
carbon monoxide concentration, 1841–1842  
equilibrium smoke layer interface position, 1834–1839  
light obscuration, 1841  
properties of smoke layer, 1839–1842  
temperature rise in smoke layer, 1839–1840  
wall/corner plumes, 1836–1837  
zone models, 1828–1830
- Latent error**, 2921, 2924
- LAVENT two-zone fire model**, 1029–1030
- Law of large numbers, probability distributions**, 2835
- Layer burning, compartment fires**, 488, 491
- Le Chatelier's rule**, 531–536, 547
- Lewis number**, 3, 9, 57, 351, 355, 358, 388, 569
- Life safety**  
defend-in-place strategy, 1315, 2309, 2315, 2328  
stay-in-place strategy, 1315
- LIFT (lateral ignition and flame spread test) apparatus**, 646, 717, 1155

- Lightning, ignition cause**, 691
- Limiting oxidant concentration, explosion prevention**, 540–541
- Limiting oxygen index (LOI)**, 234, 235, 237–238, 247, 545, 1165  
test method, 235
- Liquefied natural gas (LNG)**, 398, 401, 422, 865, 2573, 2594–2596, 2646–2648, 2650, 2657, 2665, 2671, 2678, 2814
- Liquefied petroleum gas (LP-gas)**, 570, 571, 2638, 2645, 2646, 2648, 2651, 2653, 3091
- Liquid fuel fires. *See also* Pool fires**  
blended fuels, 2573, 2574  
fire growth rate  
empirical data, 2564–2570  
flame spread regimes, 2559–2561  
pool dimensions, 2561–2562  
temperature effects, 2562–2563  
theory, 2559–2563  
fire size  
enclosure fires, 2582  
flame height, 2582–2583  
fuel burning regression rate, 2572, 2574  
inclined/cluttered surfaces, 2582  
pool tank lip height, 2582  
wind speed, 2582  
flame spread velocities and rate of pool/spill involvement, 2570–2572  
liquid/gas phase-controlled flame spread, 2559, 2560, 2564  
pool size, 2552–2558  
porous surfaces, 2559, 2569  
spill size, 2552–2558
- Liquids. *See also* Fluids**  
autoignition, 573–575  
liquids in porous materials, 575–578  
classification of fuels, 570–572  
ignition of  
calculation of vapor pressure, 558–562  
critical temperatures/pressures, 557  
flashpoint (*see* Flashpoint)  
latent heat of evaporation, 558, 561  
phase diagrams, 555–557  
vaporization process and, 555–558  
vapor pressure of blends, 562–564  
properties, 573  
sustained ignition of, 572–573  
effect of wick, 572, 573
- Livonia (Mich.) automotive plant fire (1954)**, 3147
- Log-normal distribution**, 1133, 1138, 1609, 2141, 2460, 2838–2839, 2844, 2846, 2852, 2854–2856, 2882, 2883, 2886, 2887, 2895, 2913, 3106, 3114  
reliability analysis and, 2840–2853
- Lower flammability limits (LFL)**  
adiabatic flame temperature, 148  
dusts, 670  
predicting, 570
- Luggage, heat release rates**, 848
- M**
- Magazine racks, heat release rates**, 848, 849
- MAGIC two-zone fire model**, 1030
- MAGIC zone fire model**, 3356, 3364
- Maintainability**  
downtimes and, 2898–2900  
inspections, 2910  
maintenance, 2910  
preventive, 2876–2879, 2898, 2899  
quantification, 2899–2900  
testing, 2910
- Maintainability analysis**, 2877–2879  
process, 2877
- Making Hard Decisions (Clemen)**, 3024
- Malls. *See* Large-volume spaces, smoke management in**
- Manchester Airtours fire (1984)**, 2220, 2404
- Manchester Woolworth's fire (1979)**, 2406
- Manometer tube**, 1380–1381
- Marchioness collision/sinking (1989)**, 3378
- Marine transportation**  
combustible materials, 3387–3388  
cruise ships, 3377–3379  
fire risk decision making  
analytical hierarchy processes, 3392  
NFPA 301 and, 3392–3393  
USCG Safety Alert and, 3377, 3390–3392  
fire safety objectives, 3380–3381  
incidents, 3373, 3374, 3376, 3387  
risk-informed decision making, 3379–3381  
sources of ignition, 3392
- Markov model, fire growth**, 2901–2903, 2910
- Masonry**  
as fire protection material, 1877, 1950, 3318  
thermal degradation at high temperatures, 296, 3249
- Mass, conservation of**  
computational fluid dynamics models and, 1036  
continuity equation, 4–6, 59  
convection heat transfer, 58–64  
in flames, 375
- Mass flow rates, fire plumes**, 407, 414–417, 1000
- Mass fuel-to-air ratio**, 490, 491, 500, 1182, 1191, 1199, 1215
- Mass loss rate**, 200, 201, 203, 210, 211, 236, 361, 364, 431, 432, 489, 491, 499, 509, 593, 636, 773, 782, 799, 813, 837, 866, 922, 940, 941, 952, 975, 976, 986, 999, 1011, 1016, 1029, 1078, 1089, 1167, 1170–1174, 1179–1181, 1185, 1187, 1188, 1191, 1192, 1194, 1196, 1200, 1219–1224, 1649, 2209, 2210, 2226, 2242, 2243, 2246, 2286, 2319, 2385, 2387, 2394, 2411, 3074
- Mass optical density**, 1351, 1357, 1818, 1841
- Mass spectrometry (MS)**, 192–194, 203, 1700
- Mass transportation. *See also* Aviation fire protection; Marine transportation; Rail transportation**  
decision-making methods, 3381  
fire safety objectives, 3380–3381  
risk-based decision making, 3379–3380
- Mathematical fire models**, 1024, 1848, 1851–1852
- Mattresses**  
fire test method, 933  
heat release rates, 848–853  
room effects on heat release rates, 800
- McCaffrey-Quintiere-Harkleroad (MQH) correlation of temperature rise**, 1002–1005, 2860
- Mean**  
geometric, 125, 126, 729, 2856  
harmonic, 2856  
testing, 295, 2862–2866
- Median, probability theory**, 2833
- Melting temperatures**, 179, 180, 187, 283, 1168
- Melting, thermal decomposition**, 179–181
- Mental model**, 2080, 2922
- Meshes, finite-differencing technique**, 1046, 1048
- Metals, properties**, 3432–3434

- Methane (CH<sub>4</sub>)**  
 heat of combustion, 143  
 heat of formation, 145  
 specific heat, 141
- Methanol (CH<sub>3</sub>OH)**  
 heat of combustion, 143  
 heat of formation, 145
- MGM Grand Hotel fire (1980)**,  
 2085–2087, 2097, 2449, 3103,  
 3217
- Mica, dielectric strength**, 666
- MIL-F-24385 procurement/  
 performance specification**,  
 1661, 1662
- Milk-drying process, autoignition**,  
 628
- Mode, statistical**, 2333
- Mole, defined**, 140
- Momentum, and flame height**,  
 403–405, 422, 423
- Momentum, conservation of**  
 computational fluid dynamics  
 models and, 1036  
 convection heat transfer, 59–62
- Mond Fire, Explosion, and Toxicity  
 Index**, 3165–
- Mont Blanc tunnel fire (1999)**,  
 1058, 2323, 2328, 2407
- Monte Carlo sampling/simulation**,  
 2896, 2907, 2966, 3010–3011,  
 3013, 3016, 3025, 3027, 3041,  
 3125, 3133–3134, 3151–3153,  
 3240, 3354
- Montreal Protocol**, 1301, 1450,  
 1483, 1504, 1588
- Moody diagrams**, 20, 21, 1388,  
 1389, 1391, 1393
- Motor vehicles**  
 heat release rates, 943  
 heat release rates of components, 943  
 heavy goods vehicle cargo heat  
 release rates, 881, 883  
 tire heat release rates, 879
- MS.** *See* Mass spectrometry
- Multimodal data**, 2855
- Multinomial distribution**,  
 2849–2850
- N**
- NanoMist**, 1625, 1626
- Narratives, fire risk analysis  
 method**, 2822, 2823
- NARR2 computer program**, 1944
- National Building Code® (BOCA)**,  
 3172
- National Bureau of Standards  
 (NBS).** *See* National Institute  
 of Standards and Technology  
 (NIST); NBS toxicity text
- National Electronic Injury  
 Surveillance System  
 (NEISS)**, 3084, 3085, 3095
- National Fire Incident Reporting  
 System (NFIRS).** *See* NFIRS  
 fire incident database
- National Fire Prevention and  
 Control Act (1974)**, 3084
- National Fire Prevention and  
 Control Administration**,  
 3084
- National Fire Protection  
 Association (NFPA).** *See also*  
 NFPA entries  
 Fire Incident Data Organization  
 (FIDO), 3085, 3086  
 Fire Safety Concepts Tree, 1242,  
 1291, 2038, 2825, 2949–2950,  
 3052, 3174, 3177  
 survey of fire departments, 2871,  
 3076
- National Fire Protection Research  
 Foundation (NFPRF)**, 1619,  
 1694, 1695, 1737, 3380
- National Institute of Standards and  
 Technology (NIST)**  
 investigation of Station Nightclub  
 fire, 2096  
 investigation of World Trade Center  
 terrorist attack, 1936  
 radiant method toxicity test, 2275  
 zeroth order sprinkler effectiveness  
 model, 1447
- National Research Council of  
 Canada (NRCC)**, 937, 1277,  
 1798, 1806, 1981, 3272, 3276
- National Research Institute for Fire  
 and Disaster (Japan)**, 855
- Navier-Stokes equations**, 7, 9–13,  
 16, 17, 358, 1040, 3118
- NBS toxicity test**, 227–2272
- n*-Butane (n-C<sub>4</sub>H<sub>10</sub>)**  
 heat of combustion, 143  
 heat of formation, 145
- Negative binomial distribution**,  
 2848
- NEISS.** *See* National Electronic  
 Injury Surveillance System  
 (NEISS)
- Net heat of complete combustion**,  
 1182–1184, 1186, 1187, 1215,  
 1219, 1224, 1225
- Newton's law of viscosity**,  
 54, 55
- Newton's second law of motion**, 60,  
 77, 1036. *See also* Momentum,  
 conservation of
- NFIRS fire incident database**  
 product categories, 2889–2891  
 Version 5.0, 3077–3078
- NFIRS fire incident database (cont.)**  
 errors/uncertainty in national  
 estimates, 3081–3084  
 unknown data issues,  
 3080–3081
- NFPA.** *See* National Fire Protection  
 Association (NFPA)
- NFPA 101A, Guide on Alternative  
 Approaches to Life Safety**,  
 3086, 3166
- NFPA 11A, Standard for Medium-  
 and High-Expansion Foam  
 Systems**, 1737
- NFPA 92A, Standard for Smoke-  
 Control Systems**, 1785
- NFPA 12A, Standard on Halon 1301  
 Fire Extinguishing Systems**,  
 1453, 1509, 2899
- NFPA 30B, Code for the  
 Manufacture and Storage of  
 Aerosol Products**, 1425
- NFPA 92B, Standard for Smoke  
 Management Systems in  
 Malls, Atria, and Large  
 Spaces**, 424, 1067, 1352
- NFPA 12B, Standard on Halon 1211  
 Fire Extinguishing Systems**,  
 1453
- NFPA 301, Code for Safety to Life  
 from Fire on Merchant  
 Vessels**, 3379, 3392–3393
- NFPA 231C, Standard for Rack  
 Storage of Materials**, 1424
- NFPA 231D, Standard for Storage of  
 Rubber Tires**, 1424
- NFPA 13D, Standard for the  
 Installation of Sprinkler  
 Systems in One- and Two-  
 Family Dwellings and  
 Manufactured Homes**, 1424
- NFPA 30, Flammable and  
 Combustible Liquids  
 Code**, 570, 1425, 1689,  
 1691, 1692
- NFPA 231F, Standard for Storage of  
 Roll Paper**, 1424
- NFPA 551, Guide for the Evaluation  
 of Fire Risk Assessments**,  
 1291, 2825, 2976–2977, 3380
- NFPA 325, Guide to Fire Hazard  
 Properties of Flammable  
 Liquids, Gases, and Volatile  
 Solids**, 3163
- NFPA 550, Guide to the Fire Safety  
 Concepts Tree**, 1242, 1291,  
 2038, 2825, 2950, 3052
- NFPA 49, Hazardous Chemicals  
 Data**, 3163
- NFPA 204M, Guide for Smoke and  
 Heat Venting**, 1849

- NFPA *National Fire Codes*<sup>®</sup>, 2823
- NFPA 805, *Performance-Based Standard for Fire Protection for Light Water Reactor Electric Generating Plants*, 3334
- NFPA 5000<sup>®</sup>, *Building Construction and Safety Code*<sup>®</sup>, 1235, 1304, 1742, 3254
- NFPA 101<sup>®</sup>, *Life Safety Code*<sup>®</sup>, 1235, 1266, 2018, 2125, 2174, 3086, 3166, 3379, 3386
- NFPA 72<sup>®</sup>, *National Fire Alarm Code*<sup>®</sup>, 443, 451, 1318, 1689, 2899
- NFPA 403, *Standard for Aircraft Rescue and Fire-Fighting Services at Airports*, 1673
- NFPA 17, *Standard for Dry Chemical Extinguishing Systems*, 1305, 2899
- NFPA 412, *Standard for Evaluating Aircraft Rescue and Fire-Fighting Foam Equipment*, 1663, 1674, 1676
- NFPA 130, *Standard for Fixed Guideway Transit and Passenger Rail Systems*, 2027, 2043, 3385–3386
- NFPA 231, *Standard for General Storage Materials*, 1424
- NFPA 11, *Standard for Low-, Medium-, and High-Expansion Foam*, 1308, 1688, 1690
- NFPA 10, *Standard for Portable Fire Extinguishers*, 1533, 1709
- NFPA 502, *Standard for Road Tunnels, Bridges, and Other Limited Access Highways*, 1616, 2043
- NFPA 25, *Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems*, 2898
- NFPA 16, *Standard for the Installation of Foam-Water Sprinkler and Foam-Water Spray Systems*, 1425, 1689, 1690
- NFPA 13, *Standard for the Installation of Sprinkler Systems*, 1424, 1587, 1683, 1717
- NFPA 14, *Standard for the Installation of Standpipe and Hose Systems*, 1424
- NFPA 20, *Standard for the Installation of Stationary Pumps for Fire Protection*, 1424, 1630
- NFPA 75, *Standard for the Protection of Information Technology Equipment*, 1453
- NFPA 15, *Standard for Water Spray Fixed Systems for Fire Protection*, 1425, 1587
- NFPA 22, *Standard for Water Tanks for Private Fire Protection*, 1424
- NFPA 286, *Standard Methods of Fire Tests for Evaluating Contribution of Wall and Ceiling Interior Finish to Room Fire Growth*, 788
- NFPA 265, *Standard Methods of Fire Tests for Evaluating Room Fire Growth Contribution of Textile Coverings on Full Height Panels and Walls*, 935
- NFPA 251, *Standard Methods of Tests of Fire Resistance of Building Construction and Materials*, 1866
- NFPA 409, *Standard on Aircraft Hangars*, 1425, 1683, 1689, 1690
- NFPA 12, *Standard on Carbon Dioxide Extinguishing Systems*, 1496, 2899
- NFPA 2001, *Standard on Clean Agent Fire Extinguishing Systems*, 1453, 1494, 2899
- NFPA 69, *Standard on Explosion Prevention Systems*, 541
- NFPA 68, *Standard on Explosion Protection by Deflagration Venting*, 2811
- NFPA 750, *Standard on Water Mist Fire Protection Systems*, 1299, 1308, 1587
- NFPA 704, *Standard System for the Identification of the Fire Hazards of Materials (1990 ed.)*, 3163
- NFPA 259, *Standard Test Method for Potential Heat of Building Materials*, 906
- NFPA 70T, *National Electrical Coder*, 1751
- NIBS *toxicity test*, 2289
- NIST. *See* National Institute of Standards and Technology (NIST)
- Nitric oxide (NO), *heat of formation*, 145
- Nitrogen dioxide (NO<sub>2</sub>)  
generation efficiency, 1206  
*heat of formation*, 145
- Nitrogen (N<sub>2</sub>), *specific heat*, 141
- n*-Octane (n-C<sub>8</sub>H<sub>18</sub>), *heat of combustion*, 143
- Nonhalogenated polymers, *calculating combustion yields*, 1209, 1210
- Nonmetals, *properties*, 3435–3436
- Noodles, *autoignition of instant*, 627
- NORDTEST furniture calorimeter, 800
- Normal distribution, 2837
- Normal-strength concrete (NSC)  
compressive strength, 297–299  
spalling, 289–290  
stress-strain curves, 296
- Nozzles  
flow calculation, 472  
flow coefficients, 458  
hose, 456, 1298  
sprinkler, 456  
water mist fire suppression systems, twin-fluid/single-fluid, 1624
- n*-Pentane (n-C<sub>5</sub>H<sub>12</sub>), *heat of combustion*, 143
- Nuclear power plants  
fire risk analysis, 3326–3365  
historical view of assessments, 3331–3333  
human error and, 3351–3352  
incidents, 3358  
probabilistic risk assessment assembly of results, 3352  
current/future directions, 3361–3365  
equipment damage probability, 3348  
equipment response analysis, 3358  
fire barrier analysis, 3360–3361  
fire detection/suppression analysis, 3358–3360  
fire environment analysis, 3355–3358  
fire frequency analysis, 3342–3344  
fire-modeling tools, 3355  
plant response analysis, 3341–3342  
process, 3336–3338  
structure/methodology, 3331, 3360
- Nuclear Regulatory Commission, *risk-informed decision making*, 3028
- Null hypothesis, 2861–2867, 2869, 2870, 2893
- NUREG/CR-6738, *Risk Methods Insights Gained from Fire Incidents (Nuclear Regulatory Commission)*, 2922



- Nusselt number.** 70, 80, 84, 85, 87–89, 100, 361, 362
- Nylon(s)**  
heat of combustion of Nylon 6,6, 143  
thermal decomposition, 1165
- O**
- Occupants**  
available safe escape time (ASET)  
(*see* Available safe egress time (ASET))  
dependent processes for escape, 2318  
handicapped/impaired, 2039, 2524  
movement through smoke, 1259, 2213, 2337  
required safe escape time (RSET)  
(*see* Required safe egress time (RSET))  
response to fire/smoke  
awareness of Cues, 2054  
British/U.S. populations  
compared, 3109  
cognitive decision processes, 2082  
commitment, 1243  
convergence clusters, 2097  
definition, 2070–2072  
evaluation, 1244  
fire-fighting behavior, 2084  
gender, response by, 1244  
health care facilities, 2021  
high-rise office buildings, 2103  
hotel fires, 2085–2087  
nonadaptive behavior, 2073  
panic behavior, 2072–2073  
recognition, 2092  
re-entry behavior, 2084  
residential experience, 2038  
stress model, 2916  
validation, 2919
- Office workstations, heat release rates,** 854
- Ohio State University (OSU) calorimeter**  
oxygen consumption versions, 924–925  
thermopile version, 923–924
- One Meridian Plaza fire (1991),** 3103
- Open-burning calorimeters,** 799, 802, 852
- Optical density**  
measurement with helium-neon laser, 970  
measurement with turbidimeter, 728
- Orifices**  
fire vents as, 456  
flow coefficients, 457, 458
- Oxygen**  
concentration effect on heat flux, 1071  
heat of formation (atomic), 145  
specific heat, 141
- Oxygen bomb calorimeter,** 905–907, 909, 912, 930, 945, 999, 1182, 3465
- Oxygen consumption calorimeter**  
implementation of method  
O<sub>2</sub>, CO<sub>2</sub>, and CO measured, 916–917  
only O<sub>2</sub> measured, 915–916  
practical considerations, 917–918  
Thornton's rule, 912  
volatiles/condensed phase, 912
- Oxygen index.** *See* Limiting oxygen index (LOI)
- P**
- Packaging, heat release rates,** 816
- Palletized storage**  
heat release rates of other commodities, 1692, 1696  
heat release rates of plastic-based commodities, 836
- Pallets, heat release rates of stacked idle,** 857–859
- PAN.** *See* Polyacrylonitrile (PAN)
- Paper, file storage arrangement,** 1559
- Pareto distribution,** 2846, 3114
- Pascal distribution,** 2848
- Pascal's law,** 1379
- Paschen's Law,** 664–666
- Passenger cars.** *See* Motor vehicles
- Passenger ships, sprinklers required,** 1589. *See also* Marine transportation
- PC.** *See* Polycarbonates (PC)
- PE.** *See* Polyethylene (PE)
- Pearson product-moment correlation coefficient,** 2857–2859
- Pedestrian Planning and Design (Fruin),** 2044, 2149, 2179, 2544
- Pensky-Martens closed cup apparatus,** 566
- Perceived risk, defined,** 2820
- Percentiles,** 1264, 1868, 1998, 2017, 2018, 2141, 2585, 2833, 2834, 2836, 2838–2840, 2843, 2856, 2889, 2893, 2969, 3006, 3037, 3238, 3240, 3346
- Perfect gas(es),** 402, 988, 1036, 1037, 2758
- Performance-based design**  
advantages, 1236  
application  
use as stand-alone methodology, 1247  
use with performance-based regulations, 1246  
use with prescriptive-based regulations, 1246  
attributes, 1242  
defined, 1233  
disadvantages, 1236–1237  
fire scenarios  
building characteristics, 1243  
design fire curves, 1244  
fire characteristics, 1244  
occupant characteristics, 1243–1244  
quantifying, 1243  
hazard/risk  
deterministic analysis, 1247  
event trees, 1247–1249  
risk-based analysis, 1247  
historical developments, 1235–1236  
performance types  
component performance, 1233–1234  
environment performance, 1234  
risk potential performance, 1234–1235  
threat potential performance, 1234  
prescriptive-based design compared, 1236, 1238  
process  
define objectives, 1239  
define project scope, 1237–1238  
develop fire scenarios, 1240–1242  
develop performance criteria, 1239–1240  
develop trial designs, 1242  
document design process, 1245–1246  
evaluate trial designs, 1244–1245  
fire protection engineering design brief, 1242–1243  
identify goals, 1238  
quantifying design fire scenarios, 1243  
SFPE Handbook of Fire Protection Engineering and, 1255–1260
- Performance-based fire protection,** 1233, 1235–1245, 1247, 1255, 1257, 1260, 1262, 1277, 1315, 2032, 2035, 2825, 2960, 2998, 3013, 3023, 3189, 3207–3209, 3333, 3334, 3362, 3386



- Performance shaping factor**, 2921, 2924–2927, 3352
- PET**. *See* Polyethylene terephthalate (PET)
- Phase-Doppler anemometer (PDA)**, 1598–1600
- Phenolic resins, thermal decomposition**, 224–225
- Piezo-electrification, electric charge separation**, 682
- Piezometer tube**, 1381
- Pillows, heat release rates**, 589
- Piloted ignition**, 389, 572, 649–650, 653, 707, 714, 920, 921, 1147, 1149, 1150, 1258, 3244, 3312, 3358
- Pipe(s)**  
 dimensions/weights of copper, 3491  
 dimensions/weights of extra-strong, 3491  
 dimensions/weights of red brass, 3491  
 fluid flow in, 2, 98  
 laminar/turbulent, 1382  
 heat conduction through walls of, 3250  
 properties of copper, 3490–3491  
 properties of steel, 3483–3489
- Pipe flows**  
 boundary layer concept, 65–75  
 energy losses in  
 compound networks, 1400–1401  
 critical zone, 1389  
 equations, 1387–1401  
 Hazen-Williams-based data, 1393  
 minor losses, 1395–1399  
 pipes in parallel, 1399–1400  
 pipes in series, 1399  
 flow measurement  
 ASME flow nozzle, 1402–1403  
 ASME orifice meters, 1402–1403  
 pitot tube, 21, 1403–1405  
 Venturi flow meter, 1402  
 laminar/turbulent, 1382  
 water hammer, 1407–1409
- Pipe insulation, heat release rates**, 859
- Pitot tube**, 21, 407, 459, 1401, 1403–1405, 1438
- Planck constant**, 3400
- Planck mean absorption coefficient**, 124, 125, 128–130
- Planck's law**, 104
- Plastic-based commodities, pallet storage and heat release rates**, 836
- Plastics**  
 arc tracking in, 671–673  
 dielectric strength, 664, 666  
 heats of combustion/properties, 1144
- Plate thermometers**, 749, 789, 790, 1105–1107, 1127–1129
- Plunge tests, detector sensitivity**, 1333
- PMA**. *See* Polymethyl acrylate (PMA)
- PMMA**. *See* Polymethyl methacrylate (PMMA)
- Pneumatic transport systems, static electricity and**, 687
- Poisson distribution**, 2842, 2844, 2847, 2915  
 fire frequency analysis, 2844
- Polarization, electrical charge separation**, 682
- Polyacrylics**  
 thermal decomposition, 167–247
- Polyacrylonitrile (PAN)**, 143, 168, 173, 185, 186, 197, 198, 217–218, 244, 673, 913, 2221, 2223, 2246, 2276, 2282, 2283, 2296, 2359, 2390, 3445, 3456, 3464  
 arc tracking in, 671  
 heat of combustion, 143  
 thermal decomposition, 198, 217–218
- Polyamides**, 168, 170, 216, 227, 246, 3445  
 thermal decomposition, 170, 216
- Polybutadiene, thermal decomposition**, 173
- Polycarbonates (PC)**  
 heat of combustion, 143  
 thermal decomposition, 215–216
- Polychloroprene**, 3453, 3457, 3465  
 thermal decomposition, 3457
- Polycrystalline material**, 278
- Polyester, heat of combustion**, 143
- Polyesters**, 168, 170, 216–218, 228–229, 231, 246, 1164
- Polyethylene (PE)**  
 calculating combustion yields, 993  
 heat of combustion, 143  
 thermal decomposition, 169, 182  
 water application rate, 1689
- Polyethylene terephthalate (PET)**  
 heat of combustion, 143  
 thermal decomposition, 169, 216–217
- Polyisoprene, thermal decomposition**, 173, 220–223
- Polymeric materials**  
 decomposition temperatures, 182, 222  
 fire propagation/smoke development index, 1163
- Polymers**  
 arc tracking in, 672, 673  
 chain structure, 167  
 classifying, 241  
 composite construction, 1974  
 effect of additives on  
 decomposition, 28  
 fiber-reinforced (*see* Fiber-reinforced polymers (FRP))  
 fluorine-containing, 1301  
 gasification, 167  
 glass transition temperature, 171, 179, 642  
 halogenated, 218–220, 1152, 2244  
 nitrogen-containing, 2237, 2278, 2279  
 oxygen-containing, 2255, 2282  
 synthetic carbon-oxygen chain, 227  
 thermal decomposition (*see* Thermal decomposition of polymers)  
 thermally stable, 222  
 vinyl-derived, 168
- Polymethyl acrylate (PMA), thermal decomposition**, 170, 198, 215
- Polymethyl methacrylate (PMMA)**  
 calculating combustion yields, 993  
 heat of combustion, 143  
 thermal decomposition, 215  
 water application rate, 169
- Polyolefins**, 887  
 thermal decomposition, 884, 3459
- Polyoxymethylene (POM)**  
 heat of combustion, 145  
 thermal decomposition, 83, 173  
 water application rate, 147
- Polypropylene (PP)**  
 calculating combustion yields, 993  
 decomposition products, 2255  
 heat of combustion, 143  
 thermal decomposition, 168, 170
- Polystyrene (PS)**  
 calculating combustion yields, 993  
 dielectric strength, 664, 666, 2692  
 heat of combustion, 143  
 thermal decomposition, 168, 170  
 water application rate, 1689
- Polysulfides, thermal decomposition**, 810
- Polysulfones, thermal decomposition**, 810
- Polytetrafluoroethylene (PTFE)**  
 dielectric strength, 220, 664  
 thermal decomposition, 173, 178, 220
- Polyurethanes**, 168, 170, 224, 231, 246, 2246, 2255, 2256, 2288, 2291, 2296, 3452  
 thermal decomposition, 224

- Polyvinyl acetate, thermal decomposition**, 168
- Polyvinyl chloride (PVC)**  
arc tracking in electrical insulation, 220, 671  
combustion yields, 993  
dielectric strength, 666  
heat of combustion, 143  
thermal decomposition, 170, 191
- Polyvinylidene chloride (PVDC)**, 913, 3447, 3458, 3465  
thermal decomposition, 93
- POM.** *See* Polyoxymethylene (POM)
- Pool fires.** *See also* Liquid fuel fires  
fire size  
blended fuel, 2573, 2574  
flame height, 2582  
fuel burning regression rate, 2572, 2574  
pool tank lip height, 2582  
wind speed, 2582  
flame height/length, 2583  
flame radiation to external target (*see* Flame radiation to external target, pool fires)  
flame spread  
empirical data, 2564  
pool dimensions and, 2593  
temperature effects, 2562  
flame spread velocities and rate of pool involvement, 2570–2572  
flame tilt, 2593, 2595–2596  
geometry  
flame height/length, 2594, 2595  
flame tilt angle, 2595–2596  
trench/line fires, 2596  
heat release rates  
room radiation and, 2600  
rough surfaces, 2674  
thin-layer, 866  
pool defined, 2647  
pool size, 2552–2558  
pyrolysis rate, 2995  
room effects on heat release rates, 2603  
surface flame spread, 2569  
thermal radiation hazards  
emissive radiation, 107  
external targets, 2600  
targets within fires, 2628  
virtual origin, 1835  
wind and, 2595
- Porosity**  
building materials, 278  
high-strength concrete (HSC), 280, 289, 303
- Portable fire extinguishers**  
dry chemical, 1302–1303  
foam, 1299
- Portland Cement Association (PCA)**, 1965, 1966
- Powders.** *See* Dust(s)
- Power function of the test, statistics**, 2862
- PP.** *See* Polypropylene (PP)
- PRA.** *See* Probabilistic risk assessment (PRA)
- Prandtl number**, 3, 11, 18, 57, 65, 67, 72, 75, 78, 86, 89, 100, 351, 362, 438, 439, 451, 1062, 2670
- Preaction sprinkler system**, 1765
- Pre-heating zone, flames**, 3314
- Premixed combustion**  
effect of additives on flame propagation, 2750  
flame propagation, 2647  
flame propagation mechanism, 2647, 2648  
practical applications, 1031, 2910  
pressure rise in closed vessels, 139, 2792
- Premixed flames**  
adiabatic flame temperature, 388–389, 536–538  
burning velocity, 2637, 2739  
conical, 654, 958  
diffusion flames distinguished, 237, 352  
flammability limits, 546, 565  
idealized (flat), 1800  
turbulence, 12, 80, 389
- Pressure, fluids**, 1379–1380, 1382
- Primary reaction zone, flames**, 328
- Probabilistic fire models**, 1024, 2965
- Probabilistic methods, fire risk analysis**, 3226
- Probabilistic risk assessment (PRA)**, 2310, 2919, 2923, 2960, 2977–2979, 3326, 3333, 3365  
nuclear power plants, 3326, 3329–3331
- Probability**  
decision analysis and (*see* Decision analysis, probability)  
defined, 2827  
fire types, 3051  
human error, 2920, 2927, 3192  
in reliability analysis, 2840, 2876, 3351
- Probability distributions.** *See also specific distributions (cont.)*  
discrete, 2831  
discrete/continuous, 2831  
failure/hazard rate, 2880, 2884  
fire growth and (*see* Stochastic models of fire growth)  
kurtosis, 2834  
mean/median, 2855  
moments, 2833  
multivariate, 2836  
parameters, 2841, 2845, 2854  
populations, 2835  
for reliability analysis, 2840, 2879  
for significance tests  
chi-square distribution, 2839, 2866  
*F* distribution, 2840  
Student's *t* distribution, 2839, 2864  
skewness, 2834  
uniform, 2834, 2850
- Probability measure**, 2828–2829
- Probability sample**, 2871
- Probability theory**  
concepts, 2857  
conditional probability, 2830  
fire risk analysis and, 2888  
formulas, 2829–2890  
frequency interpretation, 2829  
independent/dependent events, 2828, 2830  
prior/posterior probabilities, 2830  
probability distributions (*see* Probability distributions)  
random variables, 2831  
standard deviation, 2833  
subjective interpretation, 2820  
survival function, 2832
- Process flaring**, 2630
- Production flaring**, 2630
- Products (finished), fire risk analysis**  
assumptions, 3212  
data sources  
code requirements, 2963  
expert judgment, 3358, 3392  
product/property surveys, 3220  
importance of, 3326  
process steps, 3013  
relevant fire scenarios  
building dimensions/geometry, 3219  
exposure of people/property, 3220–3221  
fire protection systems/features, 3221–3222  
initiating fire, 3205  
openings, 3219  
room linings, 3218  
scope of products included, 3212  
specifying class of properties, 3212

- Products (finished), fire risk analysis** (*cont.*)  
 specifying goals/objectives/measures of loss, 3212  
 test methods/models  
 calibration/sensitivity/uncertainty, 3222–3223  
 ignition probability, 2846
- Propane (C<sub>3</sub>H<sub>8</sub>)**  
 adiabatic burning, 147  
 boiling point, 559, 735  
 flammability limits, 537, 547  
 heat of combustion, 143  
 heat of formation, 144, 1182  
 oxygen/air required for total oxidation, 141, 1182
- Property protection goals**, 3213
- Propylene (C<sub>3</sub>H<sub>6</sub>), compartment fire source examples**, 1079
- Protective action decision model**, 2076–2079, 2081, 2082
- Protein foam**, 1647, 1656, 1665, 1668–1670, 1673, 1681, 1682, 2554
- PS**. *See* Polystyrene (PS)
- PTFE**. *See* Polytetrafluoroethylene (PTFE)
- Pumps**  
 brake horsepower, 1418, 1439, 1629  
 centrifugal pump affinity relations, 1420–1422  
 classes, 1426  
 net positive suction head (NPSH), 1417–1419  
 operating characteristics, 1416–1419  
 parallel installation, 2930  
 selection, 1419–1420  
 series installation, 2930  
 water horsepower, 1418
- PVC**. *See* Polyvinyl chloride (PVC)
- PVDC**. *See* Polyvinylidene chloride (PVDC)
- Pyroelectrification, electric charge separation**, 682, 689
- Pyrolysis**, 141, 167, 172, 177, 181, 183, 192–195, 197, 198, 200–206, 209–213, 215–217, 226, 227, 231, 239, 240, 244, 247, 290, 327, 396, 397, 502, 538, 582–585, 591, 593, 594, 600, 635–637, 639–644, 646, 647, 649–652, 655, 710, 712–715, 717, 721, 729, 805, 828, 830, 833, 928, 929, 932, 956, 964, 973, 977, 984, 986,
- Pyrolysis** (*cont.*)  
 996, 997, 999, 1000, 1010, 1026, 1043–1045, 1081, 1135, 1146, 1150, 1154–1159, 1166, 1174–1175, 1178–1182, 1205, 1207, 1208, 1211, 1219, 1297, 1299, 1352, 1448, 1459, 1590, 1592, 1604, 1785, 1824, 1985, 1986, 1992–1994, 2005, 2208, 2210, 2212, 2221, 2223, 2253, 2255, 2271, 2273, 2274, 2284, 2302, 2303, 2321, 2390–2392, 2395, 2404, 2643, 2775, 2995, 3214, 3287, 3296, 3314
- Pyrolysis front**, 640, 641, 713, 714, 1154–1159, 1166
- Pyrolysis gas chromatography (PGC)**, 192–194
- Q**
- Quartile**, 2856
- Quenching distances**, 554
- Quota sample**, 2871
- R**
- RABT-ZTV fire resistance test**, 791
- Rack storage**  
 ignition source location and fire development, 847  
 quick-response sprinkler activation, 444, 1428, 1444
- Radiant energy detection**, 1257, 1357, 1358
- Radiant intensity**, 106, 107, 114, 117, 124, 1042, 1062, 2647, 3398
- Radiation blanketing**, 940
- Radiation blockage**, 3321
- Radiation heat transfer**. *See* Thermal radiation
- Radiative heat release rate**, 424, 1145, 1146, 1148, 1184, 1187, 1188, 1221, 1222
- Rail transportation**  
 bridges, 3374  
 car heat release rates, 3386, 3389, 3390  
 fire risk decision making  
 decision tree, 3381, 3384, 3385  
 NFPA 130 and, 1753, 2027, 2029, 2043, 3374, 3385–3386  
 regulation of combustible materials, 3384, 3387  
 fire safety objectives, 3384, 3386–3389  
 incidents, 3386  
 subways, 3385  
 tunnels, 3386, 3387
- Random-chain scission, decomposition mechanism**, 181
- Random sample**, 2870–2872, 3078, 3122, 3133, 3351  
 simple/stratified, 2871, 3078
- Random variables**  
 correlation, 2857–2859  
 expected value/average, 2832  
 regression analysis, 2857, 2859  
 variance, 2857
- Range, data**, 2651
- Raoult's Law**, 562, 564
- Rayleigh number**, 11, 79, 89, 100, 366, 438, 452
- Refrigerators, heat release rates**, 867, 868
- Regression analysis**, 1150, 1171, 2107, 2518, 2857, 2859, 2861, 3117
- Reinforced Concrete Fire Resistance (Concrete Reinforcing Steel Institute)**, 1968
- Reliability**, 1865–1866, 2840–2850, 2875–2983  
 software (*see* Software reliability)
- Reliability analysis**  
 accelerated testing, 2879, 2915–2916  
 complete/censored data, 2879, 2911–2913  
 data collection, 2879, 2911, 2918  
 human  
 definitions, 2919  
 models, 2920, 2927–2928  
 process, 2923–2927  
 value of, 2920  
 models  
 Arrhenius life-temperature relationship, 2916  
 inverse power relationship, 2917  
 probabilistic life-stress relationships, 2917  
 nonrepairable items  
 conditional distributions, 2834, 2884–2886, 2892, 2896, 2913  
 empirical distribution, 2880, 2882–2884, 2886  
 exponential distribution, 2840–2844, 2880–2881, 2885–2886, 2912–2913  
 generic reliability values for fire protection systems, 2889–2891  
 hazard rate, 2840, 2880, 2884–2887, 2918, 2919, 2929, 2930  
 log-normal distribution, 2838–2839, 2882, 2883, 2886, 2887, 2895, 2913

- Reliability analysis** (*cont.*)
- stress/strength interference model, 2887–2889
  - Weibull distribution, 2881, 2882, 2886, 2898, 2912–2914
  - operational/test-generated data, 2879, 2911
  - parameter estimation
    - Bayesian analysis, 2914–2915
    - exponential distribution, 2912–2913
    - log-normal distribution, 2913
    - nonhomogeneous Poisson process, 2913
    - renewal process, 2913–2914
    - Weibull distribution, 2912–2913
  - probability and, 2880–2884
  - process, 2891, 2893, 2895, 2913, 2923
  - repairable items
    - chronological graphing of failure history, 2892
    - Laplace or centroid test, 2892–2893
    - nonhomogeneous Poisson process, 2895, 2896, 2913
    - numerical algorithm for failure prediction, 2896, 2913
    - probabilistic models for failure prediction, 2891
    - renewal process, 2891, 2893–2898
    - superimposed renewal process, 2895
    - trend concept, 2877, 2891–2893, 2897, 2928
  - system modeling/analysis
    - block diagrams, 2929–2932
    - cut sets, 2931
    - dependent/common cause failures, 2935–2937
    - fault tree quantification, 2935
    - fault trees, 2932–2935
    - modeling common cause failures, 2936–2937
    - other systems, 2930–2931
    - parallel systems, 2929
    - path sets, 2931
    - series systems, 2929
    - share load systems, 2930
    - standby systems, 2930
- Representative sample**, 1597, 2871, 2978
- Required safe egress time (RSET)**
- components, 2435, 2437
  - impact of tenability on, 2145–2148
- Residence dwellings**
- high-rise evacuation, 1743
  - occupant behavior, 1242, 1266, 2166
- Residuals, statistics**, 2859
- Resin**, 168, 170, 224, 309, 310, 313, 684, 810, 2771, 3105, 3267
- Resistance network analogy, thermal radiation**, 122
- Response time index (RTI)**, 1029, 1045, 1265, 1321–1326, 1328, 1329, 1331, 1334, 1336–1340, 1342, 1343, 1444, 1691, 3040, 3229, 3235
- Reynolds analogy**, 71
- Reynolds-averaged Navier-Stokes approach**. *See* Computational fluid dynamics (CFD) models; Reynolds-averaged Navier-Stokes approach; Reynolds-averaged Navier-Stokes approach/turbulence modeling; Turbulence modeling
- Reynolds number**, 10–20, 65–67, 72, 81, 86, 87, 89, 94, 96, 401, 416, 423, 438, 457, 463, 474, 725, 726, 988, 1320, 1321, 1387, 1388, 1391, 1393, 1399, 1401, 1446, 1574, 1827, 1828, 2632, 2637–2639, 2644
- Reynolds stresses**, 13, 1038, 1039
- RFIRES zone fire model**, 1025
- Risk analysis**
- defined, 3227
  - health care facilities, 2825, 3178
  - performance-based design, 1255, 1256
  - qualitative, 2822, 2957, 3186, 3207, 3341, 3364
  - quantitative, 3364
- Risk assessment**
- defined, 2831, 2888
  - hazard-based assessment compared, 1247, 3389
  - use of fault/event trees, 2823, 2929
- @RISK decision analysis model**, 3025
- Risk defined**, 2817, 2941
- Risk estimation defined**, 2818, 2821
- Risk evaluation defined**, 2821, 3186
- Risk identification defined**, 2083, 2821
- Risk-informed industrial fire protection engineering**. *See* Fire protection engineering, risk-informed industrial
- RiskPro fire risk model**, 82
- Roof assemblies, fire resistance testing**, 1910, 1911, 1913, 1917
- Room/corner tests**, 711, 712, 788, 789, 934–939, 942, 946
- standards, 788, 935–936
- Room fires**. *See* Compartment fires
- Rosland mean absorption coefficient**, 124–125
- RSET**. *See* Required safe egress time (RSET)
- Rubber, synthetic**. *See* Polyisoprene
- Runaway reaction**, 605, 616
- Runehamar test tunnel (Norway)**, 1616
- Runge-Kutta methods, solving initial value problems**, 1096
- S**
- Safety factors/margins**
- combining, 2992, 3004–3005
  - derivation of, 3005
  - FOSM method, 3005
  - implied/explicit, 3003
  - in prescriptive/performance codes, 3003
  - selection, 3003–3004
- Safety of Life at Sea (SOLAS) convention**, 935, 1535, 1547, 1556, 1561–1566, 1614, 3377, 3379
- SAFIR computer program**, 1111, 1127, 1957, 1994
- SAFIRE risk assessment method**, 2968–2969
- Sample design**, 1244, 2871
- Sample space**, 2828, 2829, 2831
- Sampling frame**, 2871
- Sampling theory**, 2870–2871
- San Pedro de Anes test facility (Spain)**, 1611, 1618
- Scatter plot/diagram**, 2457, 2857, 2860
- Schmidt number**, 3, 57, 351, 1038, 1040, 2669
- Secondary reaction zone, flames**, 216
- Self-heating, spontaneous combustion and**, 604–630
- Self-ignition**. *See* Autoignition
- Semenov theory, autoignition assumptions**, 611–614
- and Biot number, 618, 622–623
  - complex chemistry and, 615
  - inclusion of fuel consumption, 614–615
  - and reactions in continuously stirred tank reactor, 615–616
  - thermal runaway, 615–616
- Separation of variables, heat transfer analysis**, 38–39
- Set theory**
- set operators
    - complement, 2827–2828
    - formulas related to, 2829–2830
    - intersection, 2828
    - relationships among, 2828
    - union, 2828
  - sets/subsets, 2827

- SFPE Engineering Guide on Human Behavior in Fire**, 1243
- SFPE Engineering Guide to Fire Risk Assessment**, 1291, 2037, 2039, 2825, 3380
- SFPE Engineering Guide to Performance-Based Fire Protection**, 1233, 1235, 1237–1245, 1255, 1257, 1260, 1262, 2032, 2825, 2960, 2998, 3023
- SFPE Engineering Guide to Piloted Ignition of Solid Materials Under Radiant Exposure**, 1258
- SFPE Guide to Fire Exposures to Structural Elements**, 1909
- Shaft flows**, 992
- Shear and moment diagrams**, 263
- Shear force, fluids**, 54
- Shear stress, fluids**, 1, 54, 1379, 1385, 1654
- Shop displays, heat release rates**, 820, 836, 867–869
- Shopping malls**. *See* Large-volume spaces, smoke management in
- Side chain cyclization mechanism, thermal decomposition**, 217, 218
- Side chain elimination mechanism, thermal decomposition**, 213
- Signs**
- ability of handicapped/impaired persons to locate/read, 2181, 2203
  - escape guidance systems, 2200–2202
  - flashing light source, 2198–2200
  - light-emitting/-reflecting, 2187
  - traveling flashing light sources, 2181, 2200, 2202
  - visibility/conspicuousness, 2199
  - visibility of colored, 2188
  - visibility of light-reflecting, 2186, 2187
  - visibility through irritant smoke, 2188–2190
- Silver Spring (Md.) rail collision (1996)**, 3374
- SIMPLE numerical scheme for CFD models**, 1047
- Simultaneous thermal analyzer (STA)**, 188–189, 191, 192
- Situation assessment**, 2264, 2922
- Situation model**, 2922
- Skewness, probability distributions**, 2834
- Skin burns**
- correction factors, 2725–2729
  - human variability, 2707–2713
  - prediction, 2713–2724
  - statistics, 2713
- SMARTFIRE CFD model**, 1035, 1609
- Smoke**
- aerosols, 727
  - behavioral response in (*see* Behavioral response to fire/smoke)
  - buoyancy, 1785, 1787, 1789–1792, 1817, 1829, 1842–1845, 1848, 1849, 2310
  - and carbon monoxide generation efficiency, 2394
  - carbon particles in (*see* Soot)
  - coagulation of particles, 725, 727–729
  - decrease of visual acuity in irritant, 2188–2190
  - defined, 727, 732, 1785
  - detection (*see* Detection system design; Smoke detectors)
  - directional sounders, 2181, 2202–2204
  - escape guidance systems
    - directional sound, 2202–2204
    - flashing light source, 2198–2200
    - traveling flashing light source, 2181, 2200, 2202, 2205
  - fire ventilation and yields, 2396–2404
  - fractional effective concentration (FEC), 2318, 2324, 2338
  - incapacitation by, 2321–2323, 2349–2351
  - including effects into hydraulic model of egress performance, 1788, 2309
  - irritant, 2188–2190, 2196, 2336–2337, 2370
  - light obscuration, 1825–1826, 1841
  - modeling effects on visibility, 2187–2188
  - occupant movement through, 2320, 2412
  - optical density measurement, 2192, 2319, 2384, 2386, 2387, 2411, 2412, 2416
  - optically dense irritant, 2336–2345
  - tenability limits, 2342–2345
  - particle size, 729–730
  - particle size distribution, 729
  - measurement, 729
  - production of, 1824, 1848
  - properties, 724, 728
  - specific/mass optical density, 1841
  - spectral extinction properties, 2188, 2189
  - toxicity assessment model, 2309–2311
  - vapor/particulate phases, 2341
  - venting, 2404
- Smoke (*cont.*)**
- visibility in, 2187, 2189
  - smoke density and, 2186–2187
  - walking speed through, 2337
  - yields, 728, 729
- Smoke control**
- acceptance testing, 1820
  - barriers, 1786, 1799, 1813, 1817, 1824
  - compartmented stairwells, 1792
  - computer analysis, 1818
  - design parameters
    - airflow, 1787, 1790
    - number of open, 1087
    - pressure differences, 1790, 1799–1800
    - weather data, 1785
  - door opening forces, 1799
  - elevator shafts
    - piston effect, 1793–1794
    - pressurization, 1807–1808
  - flow areas, 1797, 1798, 1801, 1808, 1809
  - effective, 1794–1796
  - pressurization, 1787–1788, 1807–1808
  - pressurized stairwells, 1800–1806
    - analysis, 1800
  - principles of
    - airflow, 1787, 1790
    - pressurization, 1787–1788
  - smoke management (*see* Smoke management)
  - smoke movement (*see* Smoke movement)
  - symmetry concept, 1796–1797, 1801
  - tenability systems
    - fire scenario, 1817
    - smoke transport, 1817
    - smoke transport calculations, 1817–1818
    - tenability, 1817
    - tenability calculations, 1818–1819
  - tunnels, 1818
  - ventilation, 1789, 1793, 1826, 1830
  - zoned control, 1813–1814
- Smoke conversion factor**, 3397–3424
- Smoke damage**, 724, 725, 728, 733, 735, 738–740, 742, 1240
- Smoke detectors**
- activation times, 1061, 2327, 3235
  - audibility, 1257
  - ceiling jet flows and, 429
  - entry resistance, 1348–1350
  - and forced ventilation systems, 3356
  - ionization type, 1348
  - light-scattering (photoelectric) type, 1346–1348



- Smoke detectors** (*cont.*)  
 modeling response, 1344–1345  
 and obscuration/attenuation, 1345–1346  
 occupant response to  
 children, 2040, 2064, 2175  
 sleeping occupants, 2040  
 projected-beam type, 1345, 1351, 1356, 1854  
 response functions, 1344–1350
- Smoke Development Index (SDI)**, 1162–1164
- Smoke layers, heat flux calculations**, 133–135
- Smoke management**, 1027, 1067, 1092, 1094, 1099, 1258, 1267, 1274, 1280, 1286, 1352, 1781, 1787, 1817, 1824, 1826–1827, 1829, 1843, 1855, 1857, 2034, 2043, 3260, 3315, 3316  
 large-volume spaces (*see* Large-volume spaces, smoke management in)
- Smoke movement**  
 buoyancy, 1792  
 computational fluid dynamics models  
 fire source, 1045  
 open boundary conditions, 1045  
 visibility, 1045  
 design fire scenarios and, 1273, 1274  
 expansion, 1789  
 HVAC systems and, 1789  
 reverse stack effect, 1789, 1790  
 stack effect, 1789–1792  
 in tall buildings, 1794  
 wind effects, 1792–1793
- Smoke point**  
 defined, 1211  
 predicting fire properties with, 1214, 1215
- Smoldering**  
 char oxidation, 582, 593, 599, 600  
 defined, 581  
 factors favoring, 1627  
 in flammable liquids, 554, 1271  
 self-sustained propagation  
 forward propagation, 584, 585, 591, 600  
 horizontal fuel layer, 591  
 multidimensional spread, 584, 590  
 one-dimensional spread, 584  
 other fuel configurations, 592  
 reverse propagation, 584  
 transition to flaming, 598–600  
 and victim incapacitation, 2391–2392
- Society for Risk Analysis**, 2819, 2826
- Society of Fire Protection Engineers (SFPE)**. *See* SFPE entries
- SOFIE CFD model**, 956, 1035, 1609
- Software availability**, 2918
- Software bug**, 2918
- Software error**, 2918
- Software failure**, 2918, 2919
- Software fault**, 2918
- Software maintainability**, 2918
- Software reliability**  
 defined, 2875, 2918  
 and fire risk assessment, 2919
- Software verification/validation**, 2919
- SOLAS**. *See* Safety of Life at Sea (SOLAS) convention
- Solids**  
 flaming ignition (*see* Solids, flaming ignition)  
 heat conduction in  
 pipe walls, 35, 36  
 plates, 38, 39  
 spherical with internal generation, 30  
 ignition by arcing, 670–671
- Solids, flaming ignition**  
 fuels, 633–658  
 gas phase  
 autoignition, 647–649  
 flashpoint/firepoint, 650–651  
 piloted ignition, 649–650  
 process of ignition, 634  
 simplifications/standardization  
 absorption of radiation and global properties, 653  
 boundary conditions, 653–655  
 ignition condition, 655  
 inert solid assumption, 651–653  
 solution, 656–657  
 thermally thin materials, 657–658  
 solid phase  
 charring, 639  
 melting/evaporation of water, 641–642  
 production of gaseous fuel, 637–639  
 pyrolysis/charring depth, 640–641  
 pyrolysis process, 635–637  
 semi-infinite solid, 640  
 surface boundary conditions, 644–646  
 temperature distribution, 642–644  
 thermal depth, 639–640  
 thermally thick/thin solids, 640
- Soot**  
 agglomerates, 128  
 defined, 325, 724  
 formation, 151, 352, 353, 1035, 1042, 1172, 1175, 1211, 2640  
 particle contribution to thermal radiation, 106, 353  
 radiation properties of, 128–130  
 smoke point and formation of, 241, 354, 1211, 1212  
 yields, 915, 919, 971, 1079, 1080, 1090, 1348, 3005
- Sorption isotherm, building materials**, 279
- Southwest Research Institute**, 816, 937, 1692, 3254
- Spark, electric/mechanical distinguished**, 666
- Species production, effect of combustion conditions on**  
 chemical kinetics, 505–508  
 compartment fire experiments, 499–505  
 engineering methodology, 520–526  
 equivalence ratio, 489–493  
 full-scale studies, 504  
 hood experiments, 493–499  
 overventilated conditions, 491, 494, 498, 499, 501, 506, 507, 509  
 species yields, 488–489  
 transient conditions, 509–510  
 transport to adjacent spaces  
 burning in confined adjacent areas, 512–515  
 burning in unconfined adjacent areas, 512  
 effects of burning outside compartment, 511  
 effects of oxygen-deficient smoke layers, 517–519  
 entrainment, 493, 499  
 forced ventilation and, 519  
 predicting species levels, 515–517  
 underventilated conditions, 486–488, 491, 492, 496–500, 504–506, 509, 510, 521, 523
- Specific Commercial Property Evaluation Schedule, insurance rating**, 3161–3162
- Specific heat**  
 brick, 305–306  
 building materials, 286–287  
 calculation of, 244  
 concrete, 296–304  
 defined, 140, 286  
 gypsum wallboard, 314–315  
 selected gases, 141  
 wood, 306–309
- Specific surface, pore structure**, 278, 279
- Specific volume, fluids**, 1, 286, 299, 300, 314, 375, 376, 1512, 1554, 1562, 1563, 2802
- Spill(s)**  
 confined/static, 2553  
 continuously flowing, 2552, 2553, 2576, 2580, 2583  
 defined, 2552  
 estimating depth, 2553  
 fire growth rate  
 empirical data, 2564–2570  
 flame spread regimes, 2559–2561  
 pool dimensions, 2561–2562

**Spill(s)** (*cont.*)

- porous surfaces, 2559, 2569
- temperature effects, 2562–2563
- fire size
  - enclosure fires, 2582
  - flame height, 2582–2583
  - fuel burning regression rate, 2572, 2574, 2586
  - inclined/cluttered surfaces, 2582
  - wind speed, 2582
- flame spread velocities and rate of spill involvement, 2570–2572
- foam system protection, 1708–1709
- gasoline, 2554, 2556, 2576

**Spontaneous combustion.**

*See* Autoignition

**Spontaneous ignition.** *See*

Autoignition

**Sprinklers**

- ceiling jet flows and, 429, 430, 444
- K-factor, 1429–1431
- response time index, 27
- spacing, 1343, 1427, 1428, 1430

**Sprinkler system calculations**

- drawbacks of using water, 1423
- hanging/bracing
  - earthquake braces, 1443–1444
  - hangers/hanger supports, 1442
  - trapeze hangers, 1442–1443
- hydraulics considerations
  - density-based demand, 1426–1429
  - elevation losses, 1434
  - Hardy Cross method, 1434
  - Hazen-Williams method, 1430, 1431
  - loops and grids, 1434–1437
  - pressure losses through piping/fittings/valves, 1430–1432
  - pressure requirements for most remote sprinkler, 1429–1430
  - use of velocity pressures, 1432–1434
- limits of calculations, 1425–1426
- performance calculations
  - droplet size/motion, 1445–1446
  - dry system water delivery time, 1444–1445
  - spray density and cooling, 1446–1447
  - sprinkler response as detector, 1444
- standards, 1424–1425
- suppression by sprinkler sprays, 1447–1448
- water supply calculations
  - available supply, 1437–1439
  - pump selection/testing, 1439–1440
  - tank sizing, 1440–1442

**Sprinkler systems**

- required on passenger ships, 1622, 1637
- types, 1423–1424
- SPYVAP wood charring model**, 1993
- Stairs/stairwells**
  - compartmented, 2021
  - effect on evacuation time, 1816, 2022, 2107
  - pressurized, 1791, 1792, 1794, 1798, 1800–1802, 1804–1808, 1812, 1814–1817, 1820, 2058, 2066, 3260

- Standard deviation**, 260, 496, 729, 896, 915, 976, 1053, 1054, 1132, 1133, 1137–1141, 1179, 1671, 1868, 2335, 2339–2341, 2414, 2446, 2448, 2460, 2464–2468, 2478, 2479, 2484, 2487–2497, 2521–2523, 2525–2536, 2554, 2578, 2728, 2833, 2835–2840, 2843, 2845, 2854, 2855, 2857, 2860, 2862–2866, 2881, 2882, 2889, 3005–3007, 3009–3010, 3041–3042, 3044, 3115, 3134, 3153, 3230, 3234, 3235

**Standard Methods for the Examination of Water and Wastewater (American Public Health Assn.)**, 1700

- STANJAN computer code**, 2740, 2752

- Stanton number**, 71, 89, 438, 445, 446

- STAR-CD CFD model**, 1609

- STAR-Fire risk assessment method**, 2968–2969

- Star Princess cruise ship fire (2006)**, 3390

- Static electricity.** *See* Electrical fires, static electricity discharge

- Station Nightclub fire (2003)**, 2096, 2405

**Statistics**

- basic concepts
  - descriptive, 2855–2857
  - inferences, classical/Bayesian, 2853–2855
- correlation, 2857–2859
- data characterization
  - data variability, 2871–2872
  - error, 2835, 2838, 2861–2863, 2872, 2873
  - precision/bias information, 2872
  - and propagation of uncertainties, 2852
  - repeatability/reproduceability, 2872
  - testing models for goodness of fit, 2872–2874

**Statistics** (*cont.*)

- hypothesis, 2861–2862
- hypothesis testing
  - confidence coefficient/limits, 2861
  - contingency test of independence, chi-square test, 2869–2870
  - error types, 2861–2862
  - nonparametric tests, 2870
  - power function of the test, 2862
  - test of difference between two means,  $z$  test, 2863
  - test of difference between two proportions,  $z$  test, 2863
  - test of goodness of fit to a distribution, chi-square test, 2866–2869
  - test of mean,  $t$  test, 2864–2866
  - test of mean,  $z$  test, 2862
  - test of proportion,  $z$  test, 2863
  - test of variance, chi-square test, 2866
- method of least squares, 2859
- parameters of descriptive mode, 2855–2857
- regression analysis, 2859
- regression coefficients, 2859–2861
- residuals, 2859
- sampling theory, 2870–2871

**Steel**

- cold-formed light-gauge/hot-rolled structural, 295
- creep, 282–283
- critical temperature, 288–289
- crystalline structure, 1913
- density, 1117
- modulus of elasticity, 281–282, 293–295, 1912, 1913, 1951, 1953, 1954
- pipes, properties, 1393, 1395, 1430, 1431, 1433, 1477, 1568, 1574, 1579, 1580, 1912–1914, 3483
- strength, 294, 1911, 1961
- stress-strain diagrams, 281
- thermal expansion, 284
- thermal properties, 284, 1112
- yield/ultimate strengths, 281–282

**Steel members**

- architecturally exposed, 1910
- bending strength, 1925
- in compression, 1925
- critical temperature (*see* Critical temperature, algebraic equations for steel members)
- design criteria, 1909
- fire resistance determination by analytical methods
  - beams, 1923–1924
  - columns, 1920–1923
  - empirically derived correlations, 1919–1927

**Steel members** (*cont.*)

- standard test, 1919, 1929
- time-temperature curve, 1910, 1911, 1935
- trusses, 1924–1927
- heat transfer analyses
  - computer-based analyses, 1934–1936
  - exterior columns, 1929–1930
  - graphical solutions, 1930–1934
  - Jeanes's graph, 1932–1934
  - liquid-filled columns, 1930
  - numerical methods, 1928–1930
  - protected members, 1928–1929
  - quasi-steady-state approach, 1933–1934
  - spandrel beams, 1929–1930
  - unprotected elements, 1928
- heat transfer/temperature profiles
  - thermally protected, 1917
  - unprotected, 1920, 1928
- methods of protection
  - board products, 1914–1915
  - concrete encasement, 1916–1917
  - concrete filling, 1917
  - flame shields, 1917
  - heat sinks, 1917–1919
  - insulation, 1914–1917
  - membrane, 1917
  - spray-applied materials, 1915–1916
- structural analyses
  - critical load, 1938
  - critical temperature, 1938
  - deflection, 1938
  - in tension, 1925
  - thermal degradation at high temperatures, 1876–1877

**Steel structures**

- temperature in fire-exposed
  - calculation example, 1112–1117
  - insulated steel, 1112–1114
  - shadow effects, 1118
  - unprotected, 1118

**Stefan-Boltzmann constant**, 646, 806, 1171, 2645, 2916, 3313, 3400

**Steric hindrance**, 333

**Stochastic models of fire growth**

- basic features
  - general model, 1030
  - probability distributions, 2834, 2895, 3012
  - spread to another object, 1030
- Markov model
  - Markov process, 2901
  - mathematical representation, 2907

**Stochastic models of fire growth** (*cont.*)

- state transition model, 2901–2903
- networks
- other models
  - fuel-state model, 1026
- stochastic differential equation
  - deterministic model, 1024, 1025
  - simulation/illustration, 1027, 1030
  - stochastic model, 2978

**Stochastic process**, 210, 2834, 2891, 2893, 2895, 2901, 3031, 3122, 3129

**Stoichiometric mass fuel-to-air ratio**, 490

**Stoichiometry**, 140–141, 160, 336, 347, 365, 513, 517, 522, 542, 912, 984, 1001, 1010–1011, 1078, 1182, 2647, 3437–3439

**Storage units, heat release rates**, 816

**Stored commodities, FMRC classifications**, 836–846

**Strathclyde study (U.K.)**, 2214

**Stream function**, 68, 73, 2645

**Streamline, fluid flow**, 4, 21, 22, 81, 83, 865, 987, 1050, 1383, 1386

**Streamtube, fluid flow**, 4

**Strength**, 17, 170–172, 180, 189, 226, 231, 244, 255, 258, 259, 261, 264–270, 274, 275, 281–283, 289–291, 293–299, 301–307, 309–312, 315, 469, 596, 664–669, 674, 683–685, 966, 1102, 1121, 1127, 1162, 1272, 1371, 1438, 1498, 1506, 1548, 1567, 1612, 1636, 1662, 1663, 1863–1865, 1872–1876, 1878, 1879, 1884, 1885, 1889, 1890, 1892, 1897, 1899, 1904, 1906, 1911–1914, 1938, 1949–1964, 1966–1973, 1975, 1976, 1984, 1994–2003, 2005, 2092–2094, 2419, 2442, 2537, 2649, 2664, 2692, 2699, 2700, 2744, 2745, 2754, 2758, 2759, 2774, 2781, 2785, 2787, 2793, 2820, 2829, 2877, 2887–2889, 2994, 2996, 3003, 3011, 3049, 3193, 3252, 3257, 3291, 3386, 3398

**Stress**, 1, 2, 6–14, 17, 19, 54, 55, 58, 60, 61, 82, 86, 89, 171, 189, 190, 257–258, 264–266, 268, 269, 274, 281–283, 291–293, 296, 299, 310, 311, 719, 1036, 1037, 1063, 1379, 1380, 1385, 1418, 1442, 1499, 1654, 1656, 1864, 1876–1880, 1891, 1892, 1897, 1902, 1909, 1910, 1914,

**Stress** (*cont.*)

- 1938–1943, 1961, 1967, 1970, 1972, 1998, 1999, 2073, 2078, 2097, 2098, 2100–2101, 2106, 2108, 2254, 2505, 2707, 2806, 2844, 2876, 2877, 2887–2890, 2895, 2910, 2915–2918, 2921, 2925, 2932, 2957, 3002, 3192, 3257, 3271, 3398

**Stress-strain diagrams**

- fiber-reinforced polymers (FRP), 309–314
- steel, 291–296

**Structural analysis and fire resistance**

- building assemblies and frames, 1871–1874
- catenary action of composite floors, 1872–1873
- connection moment-rotation behavior, 1873
- floor slab effects, 1872
- local/member/frame instability, 1872
- material strength limit states, 1874
- nonuniform heating, 1873
- thermal strains, 1872
- thermophysical properties of fire protection materials, 1871

**Structural Design for Fire Safety (Buchanan)**, 1950, 1974

**Structural Fire Protection (Lie, ed.)**, 291, 293, 309, 1061, 1258, 1616, 1737, 1875, 1943, 2022, 2037, 2038, 2041, 2960, 3318

**Structural mechanics**

- control parameters, 258
- design process, 256
- engineering models, 261
- failure modes
  - compression members, 265–267
  - flexural, 264, 268–270
  - flexural members, 268–270
  - statically indeterminate beams, 262, 264, 272
  - tension members, 264–265
- fire conditions and, 260–261
- internal forces, statical analysis, 262–263
- loading conditions, 256–257
- reactions, statical analysis for, 261–262

**Structural members**

- fire resistance, 277
  - load-bearing/non-load-bearing, 277
- Structures, predicting temperatures in fire-exposed**
- concrete structures
    - fire-insulated, 1126–1127
    - one-dimensional calculations, 1124–1126

- Structures, predicting temperatures in fire-exposed** (*cont.*)  
 penetration depth in semi-infinite structures, 1122–1124  
 finite element calculations  
 basic equations, 1109–1111  
 computer codes/accuracy, 1111–1112  
 heat transfer in fire resistance furnaces  
 ASTM E119, 1128–1129  
 ISO 834 and EN1363-1, 1127–1128  
 heat transfer to structures  
 adiabatic surface temperature, 1104  
 calculation using plate thermometers, 105–1107  
 convection, 1104  
 radiation, 1103–1104  
 total heat transfer, 1104  
 modeling of conduction in materials  
 measurement of thermal properties, 1108  
 solid materials, 1107–1108  
 steel structures  
 calculation example, 1112–1121  
 insulated steel structures, 1112–1114  
 shadow effects, 1118  
 thermal properties of steel, 1112  
 unprotected, 1112  
 timber structures, 1127
- Student's *t* distribution**, 2839, 2864
- Styrenics**, 116, 168, 169, 176, 198, 214, 535, 559, 688, 809, 1215, 2233, 2255, 3444, 3461, 3466, 3473
- Subcritical behavior**, 604, 605
- Subjectivity, decision analysis**, 2823, 3048, 3049
- Sublimation**, 85, 555, 1537, 1566, 1914
- Submerged surfaces, forces on**, 429
- SUPER-TEMPCALC program**, 1934, 1935
- Suppression**. *See* Aqueous film-forming foam (AFFF); Clean agent halon replacements; Fire protection mechanisms; Foam entries; Halocarbon extinguishing agents; Halogenated entries; Halon entries; Inert gas extinguishing agents; Sprinkler entries; Water; Water mist fire suppression systems
- Surface flame spread**  
 flame spread process, 705–706  
 opposed-flow  
 mechanism, 714–717  
 modeling, 717
- Surface flame spread** (*cont.*)  
 over liquids, 719–721  
 properties of materials, 711, 712  
 research background, 706–707  
 urban areas, 717  
 wildland fires, 717–719  
 wind-aided  
 beneath a ceiling, 713–714  
 upward turbulent wall flame, 708–713
- Surface tension**, 572, 719, 720, 1299, 1647–1649, 1655–1659, 1663, 1666, 1697, 1700, 2553–2556, 2559, 2667, 2668, 3428
- Survival function, random variables**, 2832
- Sustained burning**, 199, 231, 236, 555, 568, 662, 831
- Synthetic rubber**. *See* Polyisoprene
- System analysis**  
 hardware/complex systems, 2877  
 use of fault tree model, 2928, 2929
- Systematic sample**, 2871
- T**
- Tag tester, flashpoint measurement**, 561, 565
- Tanks**  
 fire modeling, 1175  
 floating roof perimeter seal, 1725  
 flow of water under pressure from, 1423  
 foam system protection  
 fixed roof, 1710, 1712, 1716, 1725, 1726  
 floating roof, 1718, 1725, 1726, 1728
- TASEF computer program**, 1111, 1112
- TASEF-2 computer program**, 1934–1936, 1957
- Television sets, heat release rates**, 869–870
- Terrestrial boundary layer, wind velocity**, 596
- 4910 Test Protocol**, 1162
- t*<sup>2</sup> fires**, 443, 1272, 1327, 1829–1834, 2242, 2243, 2571
- TGA**. *See* Thermogravimetric analysis (TGA)
- Thermal conductivity**  
 brick, 288, 305, 306  
 building materials, 287–288  
 changes in, 288  
 concrete, 29, 284, 287–288, 291, 296, 299, 1923
- Thermal conductivity** (*cont.*)  
 gypsum wallboard, 1920, 1921  
 insulation, 1932  
 wood, 28, 309, 1994, 2003
- Thermal decomposition of polymers**  
 chain scission mechanisms, 197–199, 247  
 charring, 223, 224, 228, 240  
 chemical processes, 181, 200, 247  
 cross-linking mechanisms, 172, 182  
 decomposition defined, 167  
 degradation distinguished, 167, 210, 215  
 effect of additives, 231–232  
 fire performance, implications for, 234, 239  
 glass transition temperatures, 179, 311  
 interaction of chemical/physical processes, 178, 183  
 kinetics of, 172, 199, 203  
 melting temperatures, 179, 180  
 physical changes during, 138  
 physical processes, 167, 178, 183, 187  
 side chain cyclization mechanism, 172, 197  
 side chain elimination mechanism, 172, 197  
 testing, 234, 236
- Thermal diffusivity, building materials**, 284, 288
- Thermal expansion**  
 compressibility and, 1407  
 concrete, 1976  
 steel, 274
- Thermal radiation**  
 calculation methods, 2600–2601  
 combustion product properties and gases, 126–128  
 gas-soot mixtures, 129–130  
 soot, 128–129  
 compartment fire modeling and, 981–993  
 contribution of soot particles, 128–130, 133  
 equation of transfer, 123  
 flame heat flux, 1181, 1225, 2629  
 fuel pyrolysis rate  
 boundary layer combustion, 1208  
 pool fires, 2604, 2622, 2658  
 heat transfer to structures, 1102–1103  
 ignition applications, 2729  
 intensity and flux, 106–107  
 nonparticipating medium, energy exchange in, 107, 134  
 gray diffuse surfaces, 122–123  
 resistance network method, 135  
 one-dimensional analysis, 1383

**Thermal radiation** (*cont.*)

- participating media
  - mean absorption coefficient, 124–125, 128–130, 134
  - mean beam length, 125–126
  - spectral emissivity/absorptivity, 123–124
  - total emissivity, 110, 126, 127
- role in fires, 53
- smoke layer heat flux, 115, 116, 133–135

**Thermal response parameter**

- (TRP), 1149–1154, 1159–1162, 1167, 1216, 1217, 1225, 3451, 3456, 3458

**Thermal runaway**, 374, 588, 605, 606, 615–616, 621**Thermal volatilization analysis** (TVA), 194**Thermochemistry**

- calculation of adiabatic flame temperatures, 147–150
- enthalpy, 139–140
- heat release rates, equivalence ratio and compartment fires, 146
- heat release rates in fires, 145–146
- heats of combustion, measurement of, 141–144
- heats of formation, 144–145
- internal energy of a closed system, 138–139
- specific heat, 140

**Thermodynamics, first law of**, 7, 25, 26, 30, 62, 138, 142, 144, 908**Thermogravimetric analysis**

- (TGA), 183–186, 188, 191, 192, 196, 203, 210, 221, 246, 635–637, 1175

**Thermomechanical analysis** (TMA), 189**Thermophysical properties**, 95, 187, 358, 964–966, 1028–1030, 1505, 1871, 1950–1956, 1994**Thermoplastics**

- decomposition, 170
- deformability, 171
- glass transition temperature, 179

**Thermosets**

- decomposition, 170, 181
- glass transition temperature, 171, 179

**Timber members**

- bending strength, 1984, 1999
- charring, 1985
  - rate, 1984–1988, 1991, 1992, 1994, 1997–1999, 2002
- in compression, 1998, 1999, 2002
- connections, 2000
- direct protection, 1984

**Timber members** (*cont.*)

- fire resistance determination by
  - analytical methods, 1979–2005
  - component additive method, 1981–1983
  - composite models, 2001–2002
  - contribution of protective membrane, 1980–1981
- decks, 1999–2000
- effect of fire-retardants/adhesives, 1988
- Hadvig's equations, 1988–1992
- influence of char layer, 1983
- load-carrying capacity of uncharred wood, 1994–1996
- National Design Specification® for Wood Construction* (NOS®) method, 1979
- nonstandard fire exposures, 1988
- onset of char method, 1983
- property data, 2002–2005
- reduced cross-section area models, 1997–1998
- reduced properties models, 1996–1997
- theoretical models, 1992–1994
- T.T. Lie method, 1979
- fire resistance ratings, 1979–1982, 1988, 1999
- heat transfer/temperature profiles, 1983
- high-temperature thermal degradation, 1985
- membrane protection
  - asymmetrical wall assemblies, 1982
  - fasteners/spacing, 1981
  - models for light-frame construction, 1983
  - strength and grain direction, 1988
  - in tension, 1996, 1998, 1999, 2001

**Timber structures**

- shrinking/cracking, 189
- temperature in fire-exposed, 1127

**TMA.** *See* Thermomechanical analysis (TMA)**Toluene, spill/fire calculations**, 496, 2622**Toxicity**

- clean agent halon replacements, 1483
- combustion product atmospheres, 2225, 2232, 2266, 2390–2391
- Haber's rule, 2216
- halogenated agents, 1458
- major determinants of, 2287
- water mist additives, 1601

**Toxicity assessment**

- asphyxiants
  - predicting time to incapacitation, 2353, 2361, 2371, 2387
  - tenability limits, 2342–2345
  - tenability limits/hazard calculations, 2231, 2257, 2258, 2263, 2303, 2338, 2342, 2382
- asphyxiants, 2215, 2220, 2221, 2223–2226, 2228, 2230, 2231, 2232
- CO/CO<sub>2</sub> ratio, 595
- Ct product dose, 2231, 2232, 2234, 2247, 2265, 2332, 2416
- carbon monoxide, 2232, 2332, 2416
- dose/response relationships, concentration inhaled/duration of exposure/toxicity, 2216, 2269, 2329, 2949
- example, 2211, 2212, 2215, 2224, 2331, 2332
- foam agents, 1701
- fractional effective dose (FED), 1818, 2035, 2212, 2230–2231, 2324–2325, 2332–2333
- fractional incapacitating dose (FID), 194, 2247, 2300, 2332, 2355, 2373, 2374, 2383, 2384, 2386, 2405, 2417, 2419
- carbon monoxide, 2355, 2373
- fractional irritant concentration (FIC), 2231, 2261
- fractional lethal dose (FLD), 2232, 2247, 2332, 2388, 2416
- full-scale fire requirements, 2208, 2209, 2240–2244
- glossary of terms, 1743, 2298
- importance, 486
- incapacitating effects, 2214, 2218, 2249, 2269, 2308, 2345, 2367, 2378, 2405 (*see also* Incapacitation, from toxic effects)
- interactions between toxic gases, 2218, 2368, 2371
- irritants
  - animal models/extrapolation to humans, 2250
  - components of thermal decomposition atmospheres, 2255
  - concerns sensory, 2233, 2250, 2258, 2298, 2299, 2386
  - dense smoke as, 2218, 2250, 2294, 2317, 2320, 2327–2329
  - effects of concentration levels, 2222



- Toxicity assessment** (*cont.*)  
 lung inflammatory reactions, 2254  
 predicting incapacitation, 2356  
 respiratory rate depression test, 2251  
 sensory/pulmonary, 2233, 2249, 2252, 2254, 2300, 2386  
 tenability limits, 2303, 2342–2345, 2386, 2387, 2413  
 materials-/combustion product-based approaches, 2211–2212  
 phases of fire effects on occupants, 2213–2215  
 models  
 effects of fire effluent/heat, 2224, 2230, 2285, 2411  
 FED methodology, 2335, 2414  
 and fractional effective concentration (FEC) smoke, 2322  
 smoke, 1345, 1769  
 tenability/hazard calculations for exposure to heat/burns, 2417–2419  
 nominal atmosphere concentration (NAC), 2217, 2235, 2253, 2258, 2260, 2296, 2298, 2302, 2386  
 nonflaming decomposition, 2217, 2256, 2267, 2274, 2342  
 postflashover conditions, 2246, 2294–2296  
 respiratory minute volume (RMV), 2253, 2300, 2302, 2330, 2331, 2350, 2357, 2365–2367, 2420  
 small-scale tests  
 adaptation of data, 2295  
 applications of data, 2266  
 conduct and application, 2296–2298  
 cone calorimeter, 2289  
 criteria for methods, 2268  
 development of FED expressions, 2266–2267  
 DIN test, 2270, 2290, 2294, 2295  
 measurement of toxic gas yield data, 2267  
 misuse of test data, 2242, 2257, 2270, 2283, 2284, 2296, 2568  
 NBS test, 2270, 2271, 2287  
 NIST radiant method, 2275  
 practical methods, 2269, 2332  
 product specification, 2207, 2209, 2210, 2266, 2267  
 second-generation test methods, 2242, 2274  
 toxic potencies in small-/full-scale tests, 2283–2287  
 tube furnace method, 2226, 2233, 2242, 2267, 2275, 2289, 2294  
 and type of fire, 2250, 2257, 2295  
 UPITT test, 2270
- Toxicity assessment** (*cont.*)  
 susceptibility variations and, 2333–2334  
 toxic potencies, 2208, 2210, 2225, 2232–2240, 2283  
 under differing fire conditions, 2235, 2237  
 mass loss method, 2232, 2233, 2235, 2236  
 use of product yield data, 2242–2244  
 well-ventilated flaming conditions, 2240, 2246, 2256, 2285, 2289–2291
- Transient corridor flows**, 992
- Transportation vehicles, fire risk assessment**. *See* Mass transportation
- Trash bags/containers, heat release rates**, 882–885
- Trusses**  
 fire protection methods, 1925, 1927  
 fire resistance in steel, 1911–1912, 1915, 1919, 1924–1927  
 interstitial, 1924, 1925  
 load-transfer, 1919, 1924  
 staggered, 1925–1927
- Tube furnace method toxicity test**, 2226, 2242, 2268, 2294
- Tunnels**  
 CFD model applications, 1044, 1046, 1057–1058  
 fire testing, 1619  
 rail, 1616, 1637, 2406, 3314  
 time-temperature test curves, 2771  
 ventilation to mitigate fire hazard, 1692  
 water mist fire suppression systems, 1616–1620
- Turbulence**  
 convection heat transfer, 54, 80, 81, 84, 85, 89, 97  
 field models, 1609  
 fluid flow, 1049  
 modeling, 15–16, 1037  
 premixed flames, 389
- Turbulent scalar flux**, 1038, 1039
- TVA**. *See* Thermal volatilization analysis (TVA)
- U**
- UL 263, Fire Tests of Building Construction and Materials**, 1866
- UL 1058, Halogenated Agent Extinguishing System Units**, 1513, 1523
- UL 1709, Rapid Rise Fire Tests of Protection Materials for Structures**, 790
- UL 162, Standard for Foam Equipment and Liquid Concentrates**, 1660, 1661
- Ultimate strength, building materials**, 277–320  
 steel, 291–296
- Unavailability**, 805, 2890, 2900, 2901, 2906, 2907, 2910, 2936, 3086, 3194, 3336
- Uncertainty**  
 aleatory/epistemic, 3033  
 benefit-cost analysis and, 3146  
 computer simulation models and, 2120, 2144  
 decision analysis  
 analytical model, 3033  
 @ RISK model, 3032  
 defining, 211, 258  
 design process  
 barriers to achieving fire safety, 2036  
 switchover, 2956  
 design process and, 3038  
 difficulties with, 3001–3002  
 fire protection engineering  
 behavior variability, 2096–2097  
 and design process, 2998–3001  
 identifying, 2995–2998  
 life-cycle use/safety of buildings, 2998  
 providing for equity/incorporation of social values, 2998  
 scientific, 2095–2096  
 variability in risk perceptions/values, 2997–2998  
 heat release rate measurements, 943–945  
 propagation of, 934, 3027, 3035, 3037, 3041, 3238  
 sources of  
 indeterminacy, 2993, 2994  
 linguistic imprecision, 2993, 2994  
 randomness, 2993, 2994  
 variability, 2993–2994
- Uncertainty analysis**  
 completeness uncertainty, 3035  
 decision making and  
 analysis of uncertainty, 3029–3032  
 comparison of PRA results/acceptance criteria, 3029  
 definition of problem, 3023  
 developing fire risk models, 3029–3032  
 identifying sources of uncertainty, 3032–3034  
 input uncertainty, 3034

**Uncertainty analysis** (*cont.*)

- interpreting results of PRA, 3028
- propagation of uncertainty, 3035
- risk-based approach, 3028
- risk-informed approach, 3028
- role of PRA, 3028–3029
- decision making and, 3024–3025
- model uncertainty
  - differential/direct method, 3010
  - fire models, 1249
  - Monte Carlo sampling, 3010–3011
  - response surface replacement, 3010
  - sensitivity of output predictions/ input values, 3010
- parameter uncertainty, 3032, 3034
- performance-based design process application
  - develop distribution of design fire scenarios, 3016–3017
  - develop/evaluate candidate designs, 3018
  - judge acceptability of design, 3023
  - probabilistic statement of performance, 3015–3016
  - scope/goals/objectives, 3024
  - selection/documentation, 3023
  - steps, 3016–3020
- quantitative treatment of uncertainty
  - bounding, 3007–3008
  - comparative analysis, 3008
  - expert elicitation, 3008
  - importance analysis, 3008
  - in measurement, 3008
  - in parameters/assumptions/values, 3007–3008
  - parametric analysis, 3008
  - sensitivity analysis, 3008
  - switchover, 3008

**Underwriters Laboratories Inc.**

(UL), 1318, 1334, 1512.

*See also* UL entries**UN Globally Harmonized System**

(GHS), 571, 572

**Unimodal data**, 2855**United States Federal Safety**

**Standards for Liquefied Natural Gas Facilities (49 CFR, Part 193, 1980)**, 2657

**University of Greenwich***Dreadnought Building*, 2091**University of Pittsburgh (UPITT)***toxicity test*, 2271–2273**Unzipping, decomposition***mechanism*, 197–198**Upholstered furniture**

- cigarette smoldering and*, 2342
- heat release rates, 3212, 3213

**UPITT toxicity test.** *See* University of Pittsburgh (UPITT) toxicity test

**Upper flammability limits (UFL)**, 567, 570, 1207, 1208

**Urban areas, flame spread**, 2674**U.S. Coast Guard (USCG)**

- marine regulations, 1561
- Star Princess* Safety Alert, 3390

**USFA.** *See* U.S. Fire Administration (USFA)

**U.S. Fire Administration (USFA)**, 3076, 3079, 3084, 3095

**V****Vapor clouds**

- dispersion, 2664, 2679, 2686, 2746, 2762
- explosions, 2664, 2666, 2673, 2679, 2687, 2691–2697, 2699–2701, 2745, 2756–2763
- modeling, 2679–2688
- sources, 2664–2673
- thermal radiation from burning
  - flame geometry model, 2648
  - flame propagation velocity, 2647–2650, 2652
  - thermal radiation, 2647, 2650, 2652

**Vapor, distinguished from gas**, 85, 412, 491, 919, 1620, 2374, 2560, 2568

**Vaporization**

- calculation of vapor pressure, 558–562
- critical temperatures/pressures, 557, 651
- and ignition of liquids, 554–558
- phase diagrams, 555

**Vapor pressure**, 290, 304, 345, 531, 555–558, 562–566, 570, 576, 578, 1417, 1418, 1454, 1511, 1517, 1518, 1524, 1535–1537, 1548, 1575, 1606, 1648, 1649, 1666, 1702, 2421, 2560, 2654, 2655, 2669, 2670, 2673, 2795, 2800, 2811, 3428

**Variation, coefficient of**, 1133, 1139–1141, 1875, 2857

**Vegetation.** *See* Bushes, heat release rates; Christmas trees, heat release rates

**Vehicle tunnels**

- fire characteristics, 3309
- full scale experiments, 3303–3304
- passive fire protection, 3318–3319
- ventilation, 3303–3318, 3321, 3322
- water spray systems, 3316, 3319–3322

**Vena contracta**, 467, 1402–1404, 1407

**Venn diagrams**, 2828**Vent flames**, 992**Vent flows**

- accuracy of calculations, 472–474
- in buildings, 455, 457–459, 464, 466, 470, 474, 475, 477, 478, 480, 483, 484
- buoyancy and, 467, 469, 470
- fire spread to second room, 463
- large-volume spaces, 1824, 1831
- measuring in fire experiment
  - hot/cold layer method (Method 4), 462
  - locating bottom of outflow in vent method (Method 3), 462
  - plane of vent method (Method 1), 459–461
  - pressure difference at floor method (Method 2), 461–462
- nonbuoyant, 455–457, 463, 472, 474
- room pressure
  - computation of, 480–483
  - equation to control pressure at steady state, 477–480
  - general equation to control, 477–480
- temperature distributions, 465, 484
- through horizontal vents, 466–472
- through vertical vents, 457–459

**Ventilation**

- effect on halogenated agent application, 1469
- effect on species production, 502, 508
- forced
  - CFD application, 1054
  - compartment fire modeling and, 981–993
  - effect on smoke movement, 1055–1061
- heat release rates and, 800, 801, 803, 827–829, 848, 892
- smoke management and, 1824, 1826–1827, 1829, 1843, 1855, 1857
- in tunnels, 3303, 3309, 3314, 3316–3318

**Ventilation-limited fires**, 486**Vents**

- defined, 461, 467
- roof, 474, 478
- series of, 442, 459, 478

**Venturi flow meter**, 1402

**Video games, heat release rates**, 890–896

**Video image flame detection (VIFD)**, 1684

**Virtual stresses.** *See* Reynolds stresses

- Viscosity**, 1–2, 4, 7, 11, 12, 15–18, 54–56, 64, 65, 81, 100, 166, 169, 170, 177, 190, 241, 278, 351, 367, 416, 425, 438, 457, 484, 649, 689, 720, 721, 725, 742, 1037–1040, 1062, 1063, 1251, 1321, 1359, 1375, 1379, 1385–1387, 1391, 1393, 1401, 1422, 1506, 1536, 1537, 1539, 1574, 1647, 1650, 1654–1656, 1659, 1663, 1665, 1666, 1699, 1702, 1716, 2557, 2569, 2571, 2638, 2670, 2750, 3398, 3410, 3428
- Volumetric expansion effect, compartment fires**, 985
- Volunteer fire fighters, value of donated time**, 3108, 3109
- Vorticity, fluid flow**, 1379, 1382  
free vortex, 13, 84, 399
- VTT CFD model**, 827, 828, 830, 832, 833, 859, 867, 868, 870–872, 882, 892, 894, 895, 934, 1035, 1589, 2160, 2444, 2476
- VULCAN computer program**, 1945
- Vulnerability**, 1237, 1249, 1865, 2038, 2054, 2822, 2923, 3087, 3103, 3152, 3185, 3190, 3197, 3198, 3203–3206, 3220, 3355, 3371
- W**
- Wake**, 84, 85, 530, 624, 626, 1370, 2031, 2039, 2040, 2054, 2175, 2176, 2395, 2809
- Walking speed, through irritant smoke**, 2249, 2340
- Wall/ceiling lining materials, heat release rates**, 890–892, 1028
- WALL2D computer program**, 1983
- Wall function**, 1044
- Walls**  
conduction heat transfer through cavity-type, 990, 1935  
conduction heat transfer through solid, 990, 1935  
effect on plume, 399, 424, 1092  
fire resistance  
load-bearing, 1886–1889  
separating function in fire conditions, 1885–1887  
separating function in normal conditions, 1886  
testing, 789, 1906, 1980  
thermal gradient across thickness, 185, 272, 640, 657, 1039, 1175, 1873, 1880, 1885, 1888, 1889, 1891  
heat transfer to, 789–791  
reinforced concrete, 1968
- Wardrobes, heat release rates**, 892–894, 1272
- Warehouses, high-expansion foam system calculations**, 1729–1732, 1734, 1736, 1737
- Washing machines, heat release rates**, 894–895
- Water**  
bacteriological growth in stored, 1602  
drawbacks as extinguishing agent, 595  
extinguishment mechanisms, 1592, 1604  
heat of formation, 144, 145, 150, 287, 1182, 1374  
large-scale extinguishment/suppression tests, 1610  
properties, 1298, 1378, 3429  
small-scale extinguishment tests, 548, 1494, 1680
- Water hammer**, 1407–1409, 1686
- Water mist fire suppression systems**  
acceptance testing, 1634–1636  
development, 1589, 1603, 1609, 1611–1615, 1625, 1636  
engineering details  
application systems, 1615, 1621, 1622  
methods of spray, 1624–1626  
pressure regimes, 1626–1628  
extinguishment/suppression mechanisms  
enclosure effects/turbulent mixing/cycling, 1593–1594  
explosion hazard mitigation, 1594–1597  
gas phase cooling, 1590–1593, 1604, 1621  
kinetic effects, 1590, 1592–1593  
oxygen depletion and flammable vapor dilution, 1590, 1592  
radiation attenuation, 1590, 1592  
wetting/cooling of fuel surface, 1592  
fire suppression modeling, field models (CFD models), 1608–1611  
quasi-steady-state zone models, 1605–1607  
transient zone models, 1607–1608  
zone models, 1605–1609, 1612  
fundamentals, 1590–1605  
required extinguishing medium portion (REMP) parameter, 1591  
spray characteristics  
additives and health concerns, 1601  
discharge rate, 1598, 1607, 1608, 1610, 1622
- Water mist fire suppression systems** (*cont.*)  
drop size distribution, 1587, 1596–1601, 1604, 1609, 1625  
measurement of drop size distributions, 1598–1599  
spray cone angle, 1598, 1601  
spray momentum, 1597, 1598  
spray velocity, 1598–1601  
spray heat absorption ratio, 1590  
testing importance  
development of fire test protocols, 1589, 1613–1615, 1618  
protocols for tunnels, 1611, 1615–1622, 1637  
types  
high-pressure systems, 1626, 1627  
local application systems, 1615, 1621, 1622  
low-/intermediate-pressure systems, 1626, 1628  
mist generation by flashing of superheated water, 1625  
pre-engineered/engineered systems, 1623, 1624, 1627  
total compartment application systems, 1620, 1621  
twin-fluid/single-fluid nozzles, 1620, 1624, 1626, 1634, 1635  
zoned application systems, 1620, 1622  
water mist defined, 1595
- Water Mist Fire Suppression Systems Health Hazard Evaluation (Halon Alternatives Research Corp.)**, 1601
- Water vapor**  
heat of formation, 144–145  
specific heat, 2, 140
- Weber-Fechner's law**, 24
- Weibull distribution**, 2839, 2843–2844, 2846, 2854, 2873, 2881, 2882, 2886, 2895, 2896, 2898, 2912–2914, 2917, 2938  
reliability analysis and, 2846, 2885, 2891
- Wet pipe sprinkler system**, 1687, 1748, 2890
- Wien's displacement law**, 104, 115, 920
- Wildland fires**  
fire behavior, 3283, 3284, 3286–3294, 3296–3299  
firebrands, 3285, 3291, 3298  
fire impact, 3298, 3299  
models, 3284, 3286, 3292–3296

**Wind**

buildings and, 23–24  
 characteristics, 22–23  
 effect on flame height, 422, 707–722  
 effect on vapor cloud propagation, 2647  
 effects generally, 18, 396, 987, 991, 1797, 1804, 1810, 1811, 1817, 1842, 1845, 1848, 2594, 3243, 3245, 3289, 3296  
 effects on smoke movement, 1059, 1789, 1791, 1792  
 flame trailing, 422  
 and spill/pool fire size, 1847  
 terrestrial boundary layer, 18, 22, 23, 2674

**Windows**

heat flux from, 812, 821, 848, 864, 892  
 heat release rates of plastic, 895

*Wisconsin Administrative Code*, 3172

**Wood**

air required for complete combustion, 1182  
 charring, 265, 290, 309, 639, 1137, 1983–1985  
 coefficient of linear thermal expansion, 284, 307, 320  
 components, 1988, 1997, 2000  
 compressive strength, 307, 1874  
 density, oven-dry, 2002  
 dilatometric/thermogravimetric curves, 284, 285, 302, 305, 307, 308, 315, 316

**Wood (cont.)**

grain factor, 28, 290, 309, 1987  
 heat of combustion, 1993  
 members (*see* Timber members)  
 modulus of elasticity, 264, 274, 307, 309  
 properties, 1994, 2002  
 specific heat, 1994  
 structures (*see* Timber structures)  
 tensile strength, 265, 282, 290, 307, 310, 2001  
 thermal conductivity, 1994, 2003

*Wood Handbook: Wood as an Engineering Material (Forest Products Soc.)*, 2002

**Wool**

heat of combustion, 143  
 thermal decomposition, 167, 173, 174, 217, 227, 228, 240

**Workstations, office, heat release**

**rates.** *See* Office workstations, heat release rates

**World Fire Statistics Centre**

**(WFSC), comparative data,** 3098, 3099

**World Trade Center bombing**

**(1993),** 2024, 2040, 2099

**World Trade Center fire (1975),** 2216**World Trade Center terrorist attack**

**(2001),** 1874, 2054, 2073

**WPI/FIRE zone fire model,** 987,

1058, 1454, 1464, 1744, 1750, 1788, 1869, 2968, 3167, 3168, 3339, 3356

**Y**

**Yates continuity correction,** 2867

**Yield strength, building**

**materials,** 281, 282, 293, 295, 312  
 steel, 265, 293, 295, 1892, 1961

**Z**

**Zener-Hollomon parameter,** 283, 320

**Zone models**

application, 1030–1032  
 compartment fires, 1029  
 smoke filling (*see* Compartment fires, modeling smoke filling)  
 forced ventilation, 1030  
 overview, 1026–1032  
 pyrolysis/combustion products, 1026, 2036  
 selection, 1030–1031  
 smoke management in large-volume spaces, 1099, 1824  
 submodels, 1026–1030  
 upper/lower layers, 1025, 1026, 1028, 1029  
 validation, 1030–1032  
 vent flows, 447, 464, 483, 1026, 1069

**Zone smoke control,** 1750